

**Ultrafast Rectifier**

**BYV32-200**

**FEATURES**



- High surge capacity
- Low Forward Voltage
- Low Leakage Current
- 150°C Operating Junction Temperature
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**APPLICATIONS**

- Power supply-output rectification
- Power management
- Instrumentation

**ABSOLUTE MAXIMUM RATINGS(T<sub>a</sub>=25°C)**

SYMBOL	PARAMETER	VALUE	UNIT
V <sub>RRM</sub> V <sub>RWM</sub> V <sub>R</sub>	Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	200	V
I <sub>F(AV)</sub>	Average Rectified Forward Current <b>Per Leg</b> (Rated V <sub>R</sub> ) <b>Total Device</b>	8 16	A
I <sub>FM</sub>	Peak Repetitive Forward Current (Rated V <sub>R</sub> , Square Wave,20kHz) <b>Per Diode Leg</b>	16	A
I <sub>FSM</sub>	Nonrepetitive Peak Surge Current (Surge applied at rated load conditions half-wave, single phase, 60Hz)	100	A
T <sub>J</sub>	Junction Temperature	-65~150	°C
T <sub>stg</sub>	Storage Temperature Range	-65~150	°C



## Fast Recovery Rectifier

## BYV32-200

## THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	0.9	$^{\circ}C/W$
$R_{th\ j-a}$	Thermal Resistance, Junction to Ambient	60	$^{\circ}C/W$

ELECTRICAL CHARACTERISTICS ( $T_a=25^{\circ}C$ ) (Pulse Test: Pulse Width=300  $\mu$  s, Duty Cycle  $\leq$  2%)

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT
$V_F$	Maximum Instantaneous Forward Voltage	$I_F=5A; T_j=100^{\circ}C$ $I_F=20A; T_j=25^{\circ}C$	0.85 1.15	V
$I_R$	Maximum Instantaneous Reverse Current	$V_{RRM}=200V$	50	$\mu$ A
$t_{rr}$	Maximum Reverse Recovery Time	$I_F=2A, di/dt=50A/\mu s$ $I_F=0.5A, I_R=1A, I_{REC}=0.25A$	35 25	ns