

Ultra fast Rectifier

BYV32E

FEATURES



- High surge capacity
- Low forward voltage
- Fast switching
- Soft recovery characteristic
- Reverse surge capability
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Power supply-output rectification
- Power management
- Instrumentation

ABSOLUTE MAXIMUM RATINGS(T<sub>a</sub>=25°C)

SYMBOL	PARAMETER	VALUE	UNIT	
V <sub>RRM</sub> V <sub>RWM</sub> V <sub>R</sub>	Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	150	V	
I <sub>FM</sub>	Peak Repetitive Forward Current (Rated V <sub>R</sub> , Square Wave,20kHz)	20	A	
I <sub>FSM</sub>	Nonrepetitive Peak Surge Current (Surge applied at rated load conditions half-wave, single phase)	50Hz 60Hz	125 137	A
T <sub>J</sub>	Junction Temperature	-40~150	°C	
T <sub>stg</sub>	Storage Temperature Range	-40~150	°C	



## Ultra fast Rectifier

## BYV32E

## THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R <sub>th j-b</sub>	Thermal Resistance, Junction to Mounting Base	2.4	°C/W
R <sub>th j-a</sub>	Thermal Resistance, Junction to Ambient	60	°C/W

ELECTRICAL CHARACTERISTICS (T<sub>a</sub>=25°C) (Pulse Test: Pulse Width=300 μs, Duty Cycle≤2%)

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT
V <sub>F</sub>	Maximum Instantaneous Forward Voltage	I <sub>F</sub> = 8A ; T <sub>j</sub> =150°C I <sub>F</sub> = 20A ; T <sub>j</sub> =25°C	0.85 1.15	V
I <sub>R</sub>	Maximum Instantaneous Reverse Current	V <sub>R</sub> = V <sub>RWM</sub> ; T <sub>j</sub> =25°C V <sub>R</sub> = V <sub>RWM</sub> ; T <sub>j</sub> =100°C	30 600	μA
t <sub>rr</sub>	Maximum Reverse Recovery Time	I <sub>F</sub> =2A; di/dt = 50A/μs; V <sub>R</sub> =30V	60	ns

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.