



BZX84C...Series

SILICON PLANAR ZENER DIODES

This series of Zener diodes is offered in the convenient, surface mount plastic SOT-23 package. These devices are designed to provide voltage regulation with minimum space requirement. They are well suited for applications such as cellular phones, hand held portables, and high density PC boards.



1. Anode 3. Cathode
SOT-23 Plastic Package


Features

- Zener breakdown voltage range – 2.0 V to 75 V
- Package designed for optimal automated board assembly
- Small package size for high density applications

Absolute Maximum Ratings ($T_a = 25\text{ }^\circ\text{C}$)


Parameter	Symbol	Value	Unit
Power Dissipation	P_D	350	mW
Thermal Resistance, Junction to Ambient ¹⁾	$R_{\theta JA}$	417	$^\circ\text{C/W}$
Junction and Storage Temperature Range	T_j, T_s	- 65 to + 150	$^\circ\text{C}$

¹⁾ Alumina = 0.4 X 0.3 X 0.024 in, 99.5% alumina



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



Dated : 24/04/2007


BZX84C...Series

Electrical Characteristics ($T_a = 25\text{ }^\circ\text{C}$ unless otherwise noted, $V_F < 0.9\text{ V}$ at $I_F = 10\text{ mA}$)


Type	Marking Code	$V_{Z1}\text{ (V)}$ @ $I_{ZT1} = 5\text{ mA}^1$			$Z_{ZT1}\text{ (}\Omega\text{)}$ @ $I_{ZT1} = 5\text{ mA}$	$V_{Z2}\text{ (V)}$ @ $I_{ZT2} = 1\text{ mA}^1$		$Z_{ZT2}\text{ (}\Omega\text{)}$ @ $I_{ZT2} = 1\text{ mA}^2$	$V_{Z3}\text{ (V)}$ @ $I_{ZT3} = 20\text{ mA}^1$		$Z_{ZT3}\text{ (}\Omega\text{)}$ @ $I_{ZT3} = 20\text{ mA}$	Maximum Reverse Leakage Current	
		Min.	Nom.	Max.		Min.	Max.		Min.	Max.		I_R μA	V_R V
BZX84C2V0	A8	1.8	2.0	2.15	100	-	-	-	-	-	-	120	0.5
BZX84C2V2	B8	2.08	2.2	2.33	100	-	-	-	-	-	-	120	0.7
BZX84C2V4	C8	2.2	2.4	2.6	100	1.7	2.1	600	2.6	3.2	50	50	1
BZX84C2V7	D8	2.5	2.7	2.9	100	1.9	2.4	600	3	3.6	50	20	1
BZX84C3V0	E8	2.8	3	3.2	95	2.1	2.7	600	3.3	3.9	50	10	1
BZX84C3V3	F8	3.1	3.3	3.5	95	2.3	2.9	600	3.6	4.2	40	5	1
BZX84C3V6	H8	3.4	3.6	3.8	90	2.7	3.3	600	3.9	4.5	40	5	1
BZX84C3V9	J8	3.7	3.9	4.1	90	2.9	3.5	600	4.1	4.7	30	3	1
BZX84C4V3	K8	4	4.3	4.6	90	3.3	4	600	4.4	5.1	30	3	1
BZX84C4V7	M8	4.4	4.7	5	80	3.7	4.7	500	4.5	5.4	15	3	2
BZX84C5V1	N8	4.8	5.1	5.4	60	4.2	5.3	480	5	5.9	15	2	2
BZX84C5V6	P8	5.2	5.6	6	40	4.8	6	400	5.2	6.3	10	1	2
BZX84C6V2	R8	5.8	6.2	6.6	10	5.6	6.6	150	5.8	6.8	6	3	4
BZX84C6V8	X8	6.4	6.8	7.2	15	6.3	7.2	80	6.4	7.4	6	2	4
BZX84C7V5	Y8	7	7.5	7.9	15	6.9	7.9	80	7	8	6	1	5
BZX84C8V2	Z8	7.7	8.2	8.7	15	7.6	8.7	80	7.7	8.8	6	0.7	5
BZX84C9V1	A9	8.5	9.1	9.6	15	8.4	9.6	100	8.5	9.7	8	0.5	6
BZX84C10	B9	9.4	10	10.6	20	9.3	10.6	150	9.4	10.7	10	0.2	7
BZX84C11	C9	10.4	11	11.6	20	10.2	11.6	150	10.4	11.8	10	0.1	8
BZX84C12	D9	11.4	12	12.7	25	11.2	12.7	150	11.4	12.9	10	0.1	8
BZX84C13	E9	12.4	13	14.1	30	12.3	14	170	12.5	14.2	15	0.1	8
BZX84C15	F9	14.3	15	15.8	30	13.7	15.5	200	13.9	15.7	20	0.05	10.5
BZX84C16	H9	15.3	16	17.1	40	15.2	17	200	15.4	17.2	20	0.05	11.2
BZX84C18	J9	16.8	18	19.1	45	16.7	19	225	16.9	19.2	20	0.05	12.6
BZX84C20	K9	18.8	20	21.2	55	18.7	21.1	225	18.9	21.4	20	0.05	14
BZX84C22	M9	20.8	22	23.3	55	20.7	23.2	250	20.9	23.4	25	0.05	15.4
BZX84C24	N9	22.8	24	25.6	70	22.7	25.5	250	22.9	25.7	25	0.05	16.8
Type	Marking Code	V_{Z1} Below @ $I_{ZT1} = 2\text{ mA}$			Z_{ZT1} Below @ $I_{ZT1} = 2\text{ mA}$	V_{Z2} Below @ $I_{ZT2} = 0.1\text{ mA}$		Z_{ZT2} Below @ $I_{ZT2} = 0.5\text{ mA}^2$	V_{Z3} Below @ $I_{ZT3} = 10\text{ mA}$		Z_{ZT3} Below @ $I_{ZT3} = 10\text{ mA}$	Maximum Reverse Leakage Current	
		Min.	Nom.	Max.		Min.	Max.		Min.	Max.		I_R μA	V_R V
BZX84C27	P9	25.1	27	28.9	80	25	28.9	300	25.2	29.3	45	0.05	18.9
BZX84C30	R9	28	30	32	80	27.8	32	300	28.1	32.4	50	0.05	21
BZX84C33	X9	31	33	35	80	30.8	35	325	31.1	35.4	55	0.05	23.1
BZX84C36	Y9	34	36	38	90	33.8	38	350	34.1	38.4	60	0.05	25.2
BZX84C39	Z9	37	39	41	130	36.7	41	350	37.1	41.5	70	0.05	27.3
BZX84C43	A0	40	43	46	150	39.7	46	375	40.1	46.5	80	0.05	30.1
BZX84C47	B0	44	47	50	170	43.7	50	375	44.1	50.5	90	0.05	32.9
BZX84C51	C0	48	51	54	180	47.6	54	400	48.1	54.6	100	0.05	35.7
BZX84C56	D0	52	56	60	200	51.5	60	425	52.1	60.8	110	0.05	39.2
BZX84C62	E0	58	62	66	215	57.4	66	450	58.2	67	120	0.05	43.4
BZX84C68	F0	64	68	72	240	63.4	72	475	64.2	73.2	130	0.05	47.6
BZX84C75	H0	70	75	79	255	69.4	79	500	70.3	80.2	140	0.05	52.5

¹⁾ Tested with pulses $t_p = 20\text{ ms}$.

²⁾ The Zener impedance, Z_{ZT2} , for the 27 through 75 volt types is tested at 0.5 mA rather than the test current of 0.1 mA used for V_{Z2}



SEMTECH ELECTRONICS LTD.
 (Subsidiary of Sino-Tech International Holdings Limited, a company
 listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
 Certificate No. 05103


ISO 14001:2004
 Certificate No. 7116

ISO 9001:2000
 Certificate No. 0506098


Dated : 24/04/2007

BZX84C...Series


Temperature Coefficient





Temperature Coefficient




Power Derating Curve



Typical Forward Voltage



Zener Voltage Regulator



SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)



ISO/TS 16949 : 2002
Certificate No. 05103



ISO 14001:2004
Certificate No. 7116



ISO 9001:2000
Certificate No. 0506098

Dated : 24/04/2007