

## 2SC1470



### SILICON NPN POWER TRANSISTOR

#### ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ\text{C}$ )

| SYMBOL         | PARAMETER   | VALUE   | UNIT             |
|----------------|---|---------|------------------|
| $V_{CEV}$      | Collector-Emitter Voltage                           | 850     | V                |
| $V_{CEO(SUS)}$ | Collector-Emitter Voltage                           | 450     | V                |
| $V_{EBO}$      | Emitter-Base Voltage                                | 6       | V                |
| $I_C$          | Collector Current-Continuous                        | 20      | A                |
| $I_{CM}$       | Collector Current-Peak                              | 30      | A                |
| $I_B$          | Base Current-Continuous                             | 10      | A                |
| $I_{BM}$       | Base Current-Peak                                   | 20      | A                |
| $P_C$          | Collector Power Dissipation@ $T_c=25^\circ\text{C}$ | 250     | W                |
| $T_J$          | Junction Temperature                                | 200     | $^\circ\text{C}$ |
| $T_{stg}$      | Storage Temperature                                 | -65~200 | $^\circ\text{C}$ |

#### THERMAL CHARACTERISTICS

| SYMBOL       | PARAMETER                            | MAX | UNIT               |
|--------------|--------------------------------------|-----|--------------------|
| $R_{th-j-c}$ | Thermal Resistance, Junction to Case | 0.7 | $^\circ\text{C/W}$ |



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.

Quality Semi-Conductors

## ELECTRICAL CHARACTERISTICS

$T_c=25^\circ\text{C}$  unless otherwise specified

| SYMBOL          | PARAMETER                            | CONDITIONS   | MIN | TYP. | MAX         | UNIT |
|-----------------|--------------------------------------|--|-----|------|-------------|------|
| $V_{CEO(SUS)}$  | Collector-Emitter Sustaining Voltage | $I_C=100\text{mA}$ ; $I_B=0$   | 450 |      |             | V    |
| $V_{CE(sat)-1}$ | Collector-Emitter Saturation Voltage | $I_C=10\text{A}$ ; $I_B=1\text{A}$   |     |      | 2.5         | V    |
| $V_{CE(sat)-2}$ | Collector-Emitter Saturation Voltage | $I_C=15\text{A}$ ; $I_B=1.5\text{A}$<br>$I_C=15\text{A}$ ; $I_B=1.5\text{A}$ , $T_C=100^\circ\text{C}$                           |     |      | 3.0<br>3.0  | V    |
| $V_{BE(sat)}$   | Base-Emitter Saturation Voltage      | $I_C=15\text{A}$ ; $I_B=1.5\text{A}$<br>$I_C=15\text{A}$ ; $I_B=1.5\text{A}$ , $T_C=100^\circ\text{C}$                           |     |      | 1.5<br>1.5  | V    |
| $I_{CEV}$       | Collector Cutoff Current             | $V_{CEV}=850\text{V}$ ; $V_{BE(off)}=1.5\text{V}$<br>$V_{CEV}=850\text{V}$ ; $V_{BE(off)}=1.5\text{V}$ ; $T_C=100^\circ\text{C}$ |     |      | 0.25<br>1.5 | mA   |
| $I_{CER}$       | Collector Cutoff Current             | $V_{CE}=850\text{V}$ ; $R_{BE}=50\ \Omega$ ; $T_C=100^\circ\text{C}$   |     |      | 2.5         | mA   |
| $I_{EBO}$       | Emitter Cutoff Current               | $V_{EB}=6\text{V}$ ; $I_C=0$   |     |      | 1.0         | mA   |
| $h_{FE}$        | DC Current Gain                      | $I_C=20\text{A}$ ; $V_{CE}=5\text{V}$  | 7   |      |             |      |
| $C_{OB}$        | Output Capacitance                   | $I_E=0$ ; $V_{CB}=10\text{V}$ ; $f_{test}=1.0\text{kHz}$   |     |      | 500         | pF   |

Switching times; Resistive Load

|       |              |  |  |     |      |    |
|-------|--------------|--|--|-----|------|----|
| $t_d$ | Delay Time   | $I_C=15\text{A}$ , $V_{CC}=250\text{V}$ , $R_{B2}=1.6\ \Omega$<br>$I_{B1}=1.5\text{A}$ ; $I_{B2}=-3\text{A}$ , $PW=30\ \mu\text{s}$<br>Duty Cycle $\leq 2.0\%$ |  | 20  | 50   | ns |
| $t_r$ | Rise Time    |  |  | 200 | 500  | ns |
| $t_s$ | Storage Time |  |  | 900 | 2200 | ns |
| $t_f$ | Fall Time    |  |  | 100 | 250  | ns |