

C3M0032120K1

Silicon Carbide Power MOSFET
N-Channel Enhancement Mode

Features

- Optimized package with separate driver source pin
- Lower profile TO-247-4 package body
- High blocking voltage with low on-resistance
- High-speed switching with low capacitances
- Fast intrinsic diode with low reverse recovery (Q_{rr})
- Halogen free, RoHS compliant


Benefits

- Reduce switching losses and minimize gate ringing
- Higher system efficiency
- Reduce cooling requirements
- Increase power density
- Increase system switching frequency

Typical Applications

- Motor Control
- EV Battery Chargers
- High Voltage DC/DC Converters
- Solar/ESS
- UPS
- Enterprise PSU

Package



| Part Number | Package | Marking |
|--------------|--------------|--------------|
| C3M0032120K1 | TO-247-4L LP | C3M0032120K1 |

Key Parameters

| Parameter | Symbol | Min. | Typ. | Max | Unit | Conditions | Note |
|--|----------------|------|-------|-------------|--------------|--|---------|
| Drain - Source Voltage | V_{DS} | | | 1200 | v | $T_c = 25^\circ\text{C}$ | |
| Maximum Gate - Source Voltage | $V_{GS(max)}$ | -8 | | +19 | | Transient | |
| Operational Gate-Source Voltage | $V_{GS op}$ | | -4/15 | | | Static | Note 1 |
| DC Continuous Drain Current | I_D | | | 67 | A | $V_{GS} = 15\text{ V}, T_c = 25^\circ\text{C}, T_J \leq 175^\circ\text{C}$ | Fig. 19 |
| | | | | 48 | | $V_{GS} = 15\text{ V}, T_c = 100^\circ\text{C}, T_J \leq 175^\circ\text{C}$ | Note 2 |
| Pulsed Drain Current | I_{DM} | | | 156 | | t_{Pmax} limited by T_{Jmax} $V_{GS} = 15\text{ V}, T_c = 25^\circ\text{C}$ | Fig. 22 |
| Power Dissipation | P_D | | | 278 | W | $T_c = 25^\circ\text{C}, T_J = 175^\circ\text{C}$ | Fig. 20 |
| Operating Junction and Storage Temperature | T_J, T_{stg} | | | -40 to +175 | °C | | |
| Solder Temperature | T_L | | | 260 | | According to JEDEC J-STD-020 | |
| Mounting Torque | M_D | | | 1 8.8 | Nm lbf-in | M3 or 6-32 screw | |

Note (1): Recommended turn-on gate voltage is 15V with $\pm 5\%$ regulation tolerance, see Application Note PRD-04814 for additional details

Note (2): Verified by design


Electrical Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise specified)

| Symbol | Parameter | Min. | Typ. | Max. | Unit | Test Conditions | Note |
|---------------|---|------|------|------|---------------|--|--------------|
| $V_{(BR)DSS}$ | Drain-Source Breakdown Voltage | 1200 | | | V | $V_{GS} = 0\text{ V}, I_D = 100\ \mu\text{A}$ | |
| $V_{GS(th)}$ | Gate Threshold Voltage | 1.8 | 2.9 | 3.8 | V | $V_{DS} = V_{GS}, I_D = 10.7\ \text{mA}$ | Fig. 11 |
| | | | 2.4 | | V | $V_{DS} = V_{GS}, I_D = 10.7\ \text{mA}, T_J = 175^\circ\text{C}$ | |
| I_{DSS} | Zero Gate Voltage Drain Current | | 1 | 50 | μA | $V_{DS} = 1200\ \text{V}, V_{GS} = 0\ \text{V}$ | |
| I_{GSS} | Gate-Source Leakage Current | | 10 | 250 | nA | $V_{GS} = 15\ \text{V}, V_{DS} = 0\ \text{V}$ | |
| $R_{DS(on)}$ | Drain-Source On-State Resistance | | 32 | 43 | m Ω | $V_{GS} = 15\ \text{V}, I_D = 38.9\ \text{A}$ | Fig. 4, 5, 6 |
| | | | 55 | | | $V_{GS} = 15\ \text{V}, I_D = 38.9\ \text{A}, T_J = 175^\circ\text{C}$ | |
| g_{fs} | Transconductance | | 23 | | S | $V_{DS} = 20\ \text{V}, I_{DS} = 38.9\ \text{A}$ | Fig. 7 |
| | | | 22 | | | $V_{DS} = 20\ \text{V}, I_{DS} = 38.9\ \text{A}, T_J = 175^\circ\text{C}$ | |
| C_{iss} | Input Capacitance | | 3460 | | pF | $V_{GS} = 0\ \text{V}, V_{DS} = 0\ \text{V to } 1000\ \text{V}$ $F = 100\ \text{kHz}$ $V_{AC} = 25\ \text{mV}$ | Fig. 17, 18 |
| C_{oss} | Output Capacitance | | 126 | | | | |
| C_{riss} | Reverse Transfer Capacitance | | 7 | | | | |
| E_{oss} | C_{oss} Stored Energy | | 71 | | μJ | | Fig. 16 |
| $C_{o(er)}$ | Effective Output Capacitance (Energy Related) | | 158 | | pF | $V_{GS} = 0\ \text{V}, V_{DS} = 0... 800\ \text{V}$ | Note: 3 |
| $C_{o(tr)}$ | Effective Output Capacitance (Time Related) | | 242 | | pF | | |
| E_{ON} | Turn-On Switching Energy (External Diode) | | 387 | | μJ | $V_{DS} = 800\ \text{V}, V_{GS} = -4\ \text{V}/15\ \text{V}, I_D = 38.9\ \text{A},$ $R_{G(ext)} = 2.5\ \Omega, L = 99\ \mu\text{H}, T_J = 175^\circ\text{C}$ FWD = External SiC DIODE | Fig. 26, 28 |
| E_{OFF} | Turn Off Switching Energy (External Diode) | | 91 | | | | |
| E_{ON} | Turn-On Switching Energy (Body Diode FWD) | | 791 | | μJ | $V_{DS} = 800\ \text{V}, V_{GS} = -4\ \text{V}/15\ \text{V}, I_D = 38.9\ \text{A},$ $R_{G(ext)} = 2.5\ \Omega, L = 99\ \mu\text{H}, T_J = 175^\circ\text{C}$ FWD = Internal Body Diode | Fig. 26, 28 |
| E_{OFF} | Turn-Off Switching Energy (Body Diode FWD) | | 103 | | | | |
| $t_{d(on)}$ | Turn-On Delay Time | | 16 | | ns | $V_{DD} = 800\ \text{V}, V_{GS} = -4\ \text{V}/15\ \text{V}$ $I_D = 38.9\ \text{A}, R_{G(ext)} = 2.5\ \Omega,$ Timing relative to V_{DS} Inductive load | Fig. 27, 28 |
| t_r | Rise Time | | 19 | | | | |
| $t_{d(off)}$ | Turn-Off Delay Time | | 24 | | | | |
| t_f | Fall Time | | 8 | | | | |
| $R_{G(int)}$ | Internal Gate Resistance | | 1.9 | | Ω | $f = 1\ \text{MHz}, V_{AC} = 25\ \text{mV}$ | |
| Q_{gs} | Gate to Source Charge | | 41 | | nC | $V_{DS} = 800\ \text{V}, V_{GS} = -4\ \text{V}/15\ \text{V}$ $I_D = 38.9\ \text{A}$ Per IEC60747-8-4 pg 21 | Fig. 12 |
| Q_{gd} | Gate to Drain Charge | | 31 | | | | |
| Q_g | Total Gate Charge | | 113 | | | | |

Note (3): $C_{o(er)}$, a lumped capacitance that gives same stored energy as C_{oss} while V_{ds} is rising from 0 to 800V
 $C_{o(tr)}$, a lumped capacitance that gives same charging time as C_{oss} while V_{ds} is rising from 0 to 800V


Reverse Diode Characteristics ($T_c = 25^\circ\text{C}$ unless otherwise specified)

| Symbol | Parameter | Typ. | Max. | Unit | Test Conditions | Note |
|-----------|----------------------------------|------|------|------|---|---------------|
| V_{SD} | Diode Forward Voltage | 4.9 | | V | $V_{GS} = -4\text{ V}, I_{SD} = 20\text{ A}, T_J = 25^\circ\text{C}$ | Fig. 8, 9, 10 |
| | | 4.3 | | V | $V_{GS} = -4\text{ V}, I_{SD} = 20\text{ A}, T_J = 175^\circ\text{C}$ | |
| I_S | Continuous Diode Forward Current | | 50 | A | $V_{GS} = -4\text{ V}, T_c = 25^\circ\text{C}$ | |
| I_{SM} | Diode pulse Current | | 156 | A | $V_{GS} = -4\text{ V}$, pulse width t_p limited by T_{Jmax} | |
| t_{rr} | Reverse Recover time | 20 | | ns | $V_{GS} = -4\text{ V}, I_{SD} = 38.9\text{ A}, V_R = 800\text{ V}$ $dif/dt = 7460\text{ A}/\mu\text{s}, T_J = 175^\circ\text{C}$ | |
| Q_{rr} | Reverse Recovery Charge | 894 | | nC | | |
| I_{rrm} | Peak Reverse Recovery Current | 75 | | A | | |
| t_{rr} | Reverse Recover time | 37 | | ns | $V_{GS} = -4\text{ V}, I_{SD} = 38.9\text{ A}, V_R = 800\text{ V}$ $dif/dt = 1780\text{ A}/\mu\text{s}, T_J = 175^\circ\text{C}$ | |
| Q_{rr} | Reverse Recovery Charge | 680 | | nC | | |
| I_{rrm} | Peak Reverse Recovery Current | 28 | | A | | |

Thermal Characteristics

| Symbol | Parameter | Typ. | Unit | Test Conditions | Note |
|-----------------|--|------|---------------------------|-----------------|---------|
| $R_{\theta JC}$ | Thermal Resistance from Junction to Case | 0.44 | $^\circ\text{C}/\text{W}$ | | Fig. 21 |



Typical Performance




Figure 1. Output Characteristics $T_J = -40\text{ }^\circ\text{C}$




Figure 2. Output Characteristics $T_J = 25\text{ }^\circ\text{C}$




Figure 3. Output Characteristics $T_J = 175\text{ }^\circ\text{C}$




Figure 4. Normalized On-Resistance vs. Temperature




Figure 5. On-Resistance vs. Drain Current For Various Temperatures




Figure 6. On-Resistance vs. Temperature For Various Gate Voltage



Typical Performance




Figure 7. Transfer Characteristic for Various Junction Temperatures




Figure 8. Body Diode Characteristic at -40 °C




Figure 9. Body Diode Characteristic at 25 °C




Figure 10. Body Diode Characteristic at 175 °C




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristics



Typical Performance




Figure 13. 3rd Quadrant Characteristic at -40 °C




Figure 14. 3rd Quadrant Characteristic at 25 °C




Figure 15. 3rd Quadrant Characteristic at 175 °C




Figure 16. Output Capacitor Stored Energy




Figure 17. Capacitances vs. Drain-Source Voltage (0 - 200V)




Figure 18. Capacitances vs. Drain-Source Voltage (0 - 1200V)



Typical Performance




Figure 19. Continuous Drain Current Derating vs. Case Temperature




Figure 20. Maximum Power Dissipation Derating vs. Case Temperature




Figure 21. Transient Thermal Impedance (Junction - Case)




Figure 22. Safe Operating Area




Figure 23. Clamped Inductive Switching Energy vs. Drain Current ($V_{DD} = 600V$)




Figure 24. Clamped Inductive Switching Energy vs. Drain Current ($V_{DD} = 800V$)



Typical Performance




Figure 25. Clamped Inductive Switching Energy vs. $R_{G(ext)}$




Figure 26. Clamped Inductive Switching Energy vs. Temperature




Figure 27. Switching Times vs. $R_{G(ext)}$




Figure 28. Switching Times Definition

Test Circuit Schematic





Figure 29. Clamped Inductive Switching Waveform Test Circuit


Package Dimensions





Recommended Solder Pad Layout

All dimensions in mm





Revision history

| Document Version | Date of release | Description of changes |
|------------------|-----------------|------------------------|
| 1.0 | April-2024 | Initial datasheet |
| 2.0 | October - 2024 | Legal Disclaimer |



Notes & Disclaimer

WOLFSPEED PROVIDES TECHNICAL AND RELIABILITY DATA, DESIGN RESOURCES, APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, WITH RESPECT THERETO, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, SUITABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

This document and the information contained herein are subject to change without notice. Any such change shall be evidenced by the publication of an updated version of this document by Wolfspeed. No communication from any employee or agent of Wolfspeed or any third party shall effect an amendment or modification of this document. No responsibility is assumed by Wolfspeed for any infringement of patents or other rights of third parties which may result from use of the information contained herein. No license is granted by implication or otherwise under any patent or patent rights of Wolfspeed.

The information contained in this document (excluding examples, as well as figures or values that are labeled as “typical”) constitutes Wolfspeed’s sole published specifications for the subject product. “Typical” parameters are the average values expected by Wolfspeed in large quantities and are provided for informational purposes only. Any examples provided herein have not been produced under conditions intended to replicate any specific end use. Product performance can and does vary due to a number of factors.

This product has not been designed or tested for use in, and is not intended for use in, any application in which failure of the product would reasonably be expected to cause death, personal injury, or property damage. For purposes of (but without limiting) the foregoing, this product is not designed, intended, or authorized for use as a critical component in equipment implanted into the human body, life-support machines, cardiac defibrillators, and similar emergency medical equipment; air traffic control systems; or equipment used in the planning, construction, maintenance, or operation of nuclear facilities. Notwithstanding any application-specific information, guidance, assistance, or support that Wolfspeed may provide, the buyer of this product is solely responsible for determining the suitability of this product for the buyer’s purposes, including without limitation (1) selecting the appropriate Wolfspeed products for the buyer’s application, (2) designing, validating, and testing the buyer’s application, and (3) ensuring the buyer’s application meets applicable standards and any other legal, regulatory, and safety-related requirements.

RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Wolfspeed representative or from the Product Documentation sections of www.wolfspeed.com.

REACH Compliance

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact your Wolfspeed representative to ensure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request. SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

Contact info:

4600 Silicon Drive
Durham, NC 27703 USA
Tel: +1.919.313.5300
www.wolfspeed.com/power

© 2024 Wolfspeed, Inc. All rights reserved. Wolfspeed® and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
PATENT: <https://www.wolfspeed.com/legal/patents>

The information in this document is subject to change without notice.