


2SC4057
(T8W45FX)

8A NPN

OUTLINE DIMENSIONS



RATINGS


● Absolute Maximum Ratings

Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	T_{stg}		-55~150	°C
Junction Temperature	T_j		150	°C
Collector to Base Voltage	V_{CBO}		600	V
Collector to Emitter Voltage	V_{CEO}	$V_{EB} = 5V$	450	V
	V_{CEX}		600	
Emitter to Base Voltage	V_{EBO}		7	V
Collector Current DC	I_C		8	A
Collector Current Peak	I_{CP}		16	
Base Current DC	I_B		4	A
Base Current Peak	I_{BP}		8	
Total Transistor Dissipation	P_T	$T_c = 25^\circ C$	80	W
Mounting Torque	TOR		0.8	N·m


● Electrical Characteristics ($T_c=25^\circ C$)

Item	Symbol	Conditions	Ratings	Unit
Collector to Emitter Sustaining Voltage	$V_{CEO}(sus)$	$I_C = 0.2A$	Min 450	V
Collector Cutoff Current	I_{CBO}	At rated Voltage	Max 0.1	mA
	I_{CEO}		Max 0.1	
Emitter Cutoff Current	I_{EBO}	At rated Voltage	Max 0.1	mA
DC Current Gain	h_{FE}	$V_{CE} = 5V, I_C = 4A$	Min 10	
	h_{FEL}	$V_{CE} = 5V, I_C = 1mA$	Min 5	
Collector to Emitter Saturation Voltage	$V_{CE}(sat)$	$I_C = 4A$	Max 1.0	V
Base to Emitter Saturation Voltage	$V_{BE}(sat)$	$I_B = 0.8A$	Max 1.5	V
Thermal Resistance	θ_{jc}	Junction to case	Max 1.56	°C/W
Transition Frequency	f_T	$V_{CE} = 10V, I_C = 0.8A$	STD 20	MHz
Turn on Time	t_{on}	$I_C = 4A$	Max 0.5	μs
Storage Time	t_s	$I_{B1} = 0.8A, I_{B2} = 1.6A$	Max 2.0	
Fall Time	t_f	$R_L = 37.5\Omega, V_{BB2} = 4V$	Max 0.2	

2SC4057 $h_{FE} - I_C$




2SC4057 Saturation Voltage




2SC4057

Switching Time - I_C




2SC4057 Switching Time - V_{CC}




2SC4057


Switching Time - Tc




2SC4057 L-Load Switching Time - I_C




2SC4057 L-Load Switching Time - I_C (At High Temperature)



2SC4057 Transient Thermal Impedance



2SC4057 Forward Bias SOA



2SC4057 Collector Current Derating



2SC4057

Reverse Bias SOA

