

# 2SC5270, 2SC5270A

Silicon NPN triple diffusion mesa type


For horizontal deflection output

## Features

- High breakdown voltage, and high reliability through the use of a glass passivation layer
- High-speed switching
- Wide area of safe operation (ASO)

## Absolute Maximum Ratings (T<sub>C</sub>=25°C)


Parameter	Symbol	Rated	Unit
Collector to base voltage	V <sub>CBO</sub>	1500	V
base voltage		1600	
Collector to base voltage	V <sub>CES</sub>	1500	V
base voltage		1600	
Collector to emitter voltage	V <sub>CEO</sub>	600	V
Emitter to base voltage	V <sub>EBO</sub>	5	V
Peak collector current	I <sub>CP</sub>	20	A
Collector current	I <sub>C</sub>	12	A
Base current	I <sub>B</sub>	8	A
Collector power dissipation	P <sub>C</sub>	120	W
(T <sub>a</sub> =25°C)		3	
Junction temperature	T <sub>j</sub>	150	°C
Storage temperature	T <sub>stg</sub>	-55 to +150	°C




## Electrical Characteristics (T<sub>C</sub>=25°C)

Parameter	Symbol	Conditions	min	typ	max	Unit
Collector cutoff current	I <sub>CBO</sub>	V <sub>CB</sub> = 1000V, I <sub>E</sub> = 0			50	μA
					50	
		V <sub>CB</sub> = 1500V, I <sub>E</sub> = 0			1	mA
			V <sub>CB</sub> = 1600V, I <sub>E</sub> = 0			
Emitter cutoff current	I <sub>EBO</sub>	V <sub>EB</sub> = 5V, I <sub>C</sub> = 0			50	μA
Forward current transfer ratio	h <sub>FE</sub>	V <sub>CE</sub> = 5V, I <sub>C</sub> = 6A	5		12	
Collector to emitter saturation voltage	V <sub>CE(sat)</sub>	I <sub>C</sub> = 6A, I <sub>B</sub> = 1.5A			3	V
Base to emitter saturation voltage	V <sub>BE(sat)</sub>	I <sub>C</sub> = 6A, I <sub>B</sub> = 1.5A			1.5	V
Transition frequency	f <sub>T</sub>	V <sub>CE</sub> = 10V, I <sub>C</sub> = 0.1A, f = 0.5MHz		3		MHz
Storage time	t <sub>stg</sub>	I <sub>C</sub> = 6A, I <sub>B1</sub> = 1.5A, I <sub>B2</sub> = -3A		1.5	2.5	μs
Fall time	t <sub>f</sub>			0.12	0.2	


$P_C - T_a$




$h_{FE} - I_C$




$V_{CE(sat)} - I_C$




Area of safe operation (ASO)



Area of safe operation, horizontal operation ASO



$t_f - I_B$



$t_{stg} - I_B$

