



# CEP6030L/CEB6030L

## N-Channel Enhancement Mode Field Effect Transistor

### FEATURES

- 30V, 52A,  $R_{DS(ON)} = 13.5m\Omega$  @  $V_{GS} = 10V$ .  
 $R_{DS(ON)} = 20m\Omega$  @  $V_{GS} = 4.5V$ .
- Super high dense cell design for extremely low  $R_{DS(ON)}$ .
- High power and current handling capability.
- Lead free product is acquired.
- TO-220 & TO-263 package.



### ABSOLUTE MAXIMUM RATINGS $T_C = 25^\circ C$ unless otherwise noted

Parameter	Symbol	Limit	Units
Drain-Source Voltage	$V_{DS}$	30	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Drain Current-Continuous	$I_D$	52	A
Drain Current-Pulsed <sup>a</sup>	$I_{DM}$	156	A
Maximum Power Dissipation @ $T_C = 25^\circ C$ - Derate above $25^\circ C$	$P_D$	75	W
		0.5	W/ $^\circ C$
Operating and Store Temperature Range	$T_J, T_{stg}$	-65 to 175	$^\circ C$

### Thermal Characteristics

Parameter	Symbol	Limit	Units
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	2	$^\circ C/W$
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	62.5	$^\circ C/W$



# CEP6030L/CEB6030L

## Electrical Characteristics $T_C = 25^\circ\text{C}$ unless otherwise noted

4

Parameter	Symbol	Test Condition	Min	Typ	Max	Units	
<b>Off Characteristics</b>							
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS} = 0V, I_D = 250\mu A$	30			V	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 24V, V_{GS} = 0V$			1	$\mu A$	
Gate Body Leakage Current, Forward	$I_{GSSF}$	$V_{GS} = 20V, V_{DS} = 0V$			100	nA	
Gate Body Leakage Current, Reverse	$I_{GSSR}$	$V_{GS} = -20V, V_{DS} = 0V$			-100	nA	
<b>On Characteristics<sup>b</sup></b>							
Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS} = V_{DS}, I_D = 250\mu A$	1	1.6	3	V	
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS} = 10V, I_D = 26A$		11	13.5	$m\Omega$	
		$V_{GS} = 4.5V, I_D = 21A$		16	20.0	$m\Omega$	
Forward Transconductance	$g_{FS}$	$V_{DS} = 10V, I_D = 26A$		32		S	
<b>Dynamic Characteristics<sup>c</sup></b>							
Input Capacitance	$C_{iss}$	$V_{DS} = 15V, V_{GS} = 0V, f = 1.0\text{ MHz}$		1200		pF	
Output Capacitance	$C_{oss}$				480		pF
Reverse Transfer Capacitance	$C_{rss}$				130		pF
<b>Switching Characteristics<sup>c</sup></b>							
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = 15V, I_D = 52A, V_{GS} = 10V, R_{GEN} = 24\Omega$		6	16	ns	
Turn-On Rise Time	$t_r$			120	250	ns	
Turn-Off Delay Time	$t_{d(off)}$			40	90	ns	
Turn-On Fall Time	$t_f$			105	200	ns	
Total Gate Charge	$Q_g$	$V_{DS} = 15V, I_D = 48A, V_{GS} = 5V$		19	23	nC	
Gate-Source Charge	$Q_{gs}$			5		nC	
Gate-Drain Charge	$Q_{gd}$			9		nC	
<b>Drain-Source Diode Characteristics and Maximum Ratings</b>							
Drain-Source Diode Forward Current	$I_S$				52	A	
Drain-Source Diode Forward Voltage <sup>b</sup>	$V_{SD}$	$V_{GS} = 0V, I_S = 26A$		0.9	1.3	V	
<b>Notes :</b> a.Repetitive Rating : Pulse width limited by maximum junction temperature. b.Pulse Test : Pulse Width $\leq 300\mu s$ , Duty Cycle $\leq 2\%$ . c.Guaranteed by design, not subject to production testing.							



# CEP6030L/CEB6030L




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Temperature




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Body Diode Forward Voltage Variation with Source Current



# CEP6030L/CEB6030L




Figure 7. Gate Charge




Figure 8. Maximum Safe Operating Area



Figure 9. Switching Test Circuit




Figure 10. Switching Waveforms




Figure 11. Normalized Thermal Transient Impedance Curve