

QSOP Dual-Channel Digital Isolators High Speed CE0832XX-XG Series

Features:

- Compliance Halogens Free
(Br < 900 ppm, Cl < 900 ppm, Br+Cl < 1500 ppm)
- Data rate: 10M ~ 200Mbps
- Low propagation delay: 9ns typical
- Isolation voltages 3000Vrms
- Human body model (HBM) $\pm 8\text{kV}$
- Wide temperature range: -40°C to 125°C

Description


The CE0832XX-XG isolator data channels are independent.

The devices operate with the supply voltage on either side ranging from 3.0 V to 5.5 V, providing compatibility with lower voltage systems as well as enabling voltage translation functionality across the isolation barrier. The fail-safe state is available in which the outputs transition to a preset state when the input power supply is not applied.

Applications

- General-purpose multichannel isolation
- Industrial field bus isolation
- Isolation Industrial automation systems
- Isolated switch mode supplies
- Isolated ADC, DAC
- Motor control

Functional Diagram



Pin Description

NAME	PIN			DESCRIPTION
	CE08320	CEQ8321	CEQ8622	
V _{DD1}	1	1	1	Power supply, side 1
V _{DD2}	8	8	8	Power supply, side 2
GND1	4	4	4	Ground , side 1
GND2	5	5	5	Ground , side 2
INA	2	2	7	Input, channel A
INB	3	6	3	Input, channel B
OUTA	7	7	2	Output, channel A
OUTB	6	3	6	Output, channel B

Truth Table

V _{IX} Input	V _{DDI} State	V _{DD2} State	Default Low V _{OX} Output	Default High V _{OX} Output	Test Conditions /Comments
L	P	P	L	L	Normal operation
H	P	P	H	H	Normal operation
NC	P	P	L	H	Default output
X ^{*2}	UP	P	L	H	Default output ^{*3}
X ^{*2}	P	UP	Z	Z	

Notes:

1. V_{IX}/V_{OX} are the input/output signals of a given channel. V_{DDI}/V_{DD2} are the supply voltages on the input/output signal sides of this given channel.
2. Input signal (V_{IX}) must be in a low state to avoid powering the given V_{DDI} through its ESD protection circuitry.
3. If the V_{DDI} goes into unpowered status, the channel outputs the default logic signal after around 1us. If the V_{DDI} goes into powered status, the channel outputs the input status logic signal after around 5us.

Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Rating	Unit
Supply Voltage	V _{DDX}	7	V
Maximum Input Voltage	V _{IN}	V _{DD} +0.5	V
Maximum Output Voltage	V _{OUT}	V _{DD} +0.5	V
Output Current	I _O	10	mA
Isolation Voltage *1	V _{ISO}	3000	V rms
Operating Temperature	T _{OPR}	-40 ~ +125	°C
Storage Temperature	T _{STG}	-55 ~ +150	°C
Soldering Temperature *2	T _{SOL}	260	°C

Notes:

*1 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1 to 8 are shorted together, and pins 9 to 16 are shorted together.

*2 For 10 seconds.

Recommended Operating Conditions

Parameter	Symbol	Min	Max	Unit
Supply Voltage	V _{DDX}	3	5.5	V
High Level Input Voltage	V _{IH}	V _{DDX} *0.7	V _{DDX}	V
Low Level Input Voltage	V _{IL}	0	V _{DDX} *0.3	V

Electro-Optical Characteristics $V_{DD1} - V_{GND1} = V_{DD2} - V_{GND2} = 3.3V$ or $5V$, $T_A = 25^\circ C$, unless otherwise noted.

Parameter	Symbol	Min	Typ.	Max.	Unit	Condition
High Level Input Voltage	V_{IH}		$0.6 \cdot V_{DDX}$	$0.7 \cdot V_{DDX}$	V	
Low Level Input Voltage	V_{IL}	$0.3 \cdot V_{DDX}$	$0.4 \cdot V_{DDX}$		V	
High Level Output Voltage	V_{OH}	$V_{DDX} - 0.1$	V_{DDX}		V	$I_O = -20\mu A$
		$V_{DDX} - 0.2$	$V_{DDX} - 0.1$			$I_O = -2mA$
Low Level Output Voltage	V_{OL}		0	0.1	V	$I_O = 20\mu A$
			0.1	0.2		$I_O = 2mA$
Input Current per Signal Channel	I_{IN}	-10	0.5	10	μA	$0V \leq \text{Signal voltage} \leq V_{DD}$
V_{DDX} Undervoltage Rising Threshold	V_{DDXUV+}	2.45	2.75	2.95	V	
V_{DDX} Undervoltage Falling Threshold	V_{DDXUV-}	2.30	2.60	2.75	V	
V_{DDX} Hysteresis	V_{DDXUVH}		0.15		V	
Common Mode Transient Immunity	CMTI		75	-	kV/ μS	$V_{CM} = 1000V$

Switching Characteristics $V_{DD1} - V_{GND1} = V_{DD2} - V_{GND2} = 3.3V$ or $5V$, $T_A = 25^\circ C$, unless otherwise noted.

Parameter	Symbol	Min	Typ.	Max.	Unit	Condition
Minimum Pulse Width	PW			100	nS	
Propagation Delay	t_{PLH} 、 t_{PLH}	5.5		13.5	nS	
Pulse Width Distortion	PWD			3	nS	
Part to Part Propagation Delay Skew	t_{PSK}			2	nS	
Channel-to-Channel Delay Skew	t_{CSK}			2	nS	
Rising Time	T_r		1.5		nS	
Falling Time	T_f		1.5		nS	


Supply Current

Parameter	Symbol	Min	Typ.	Max.	Unit	Condition
CE08320X	I _{DD1}	0.06	0.08	0.1	mA	V _{DD} = 5V VI=0V for CE08320X-L VI=5V for CE08320X-H
	I _{DD2}	0.78	0.98	1.27	mA	
	I _{DD1}	0.16	0.20	0.26	mA	V _{DD} = 5V VI=5V for CE08320X-L VI=0V for CE08320X-H
	I _{DD2}	0.74	0.92	1.2	mA	
	I _{DD1}	0.06	0.08	0.10	mA	V _{DD} = 3.3V VI=0V for CE08320X-L VI=3.3V for CE08320X-H
	I _{DD2}	0.77	0.97	1.26	mA	
	I _{DD1}	0.12	0.15	0.19	mA	V _{DD} = 3.3V VI=3.3V for CE08320X-L VI=0V for CE08320X-H
	I _{DD2}	0.71	0.89	1.15	mA	
CE08321X	I _{DD1}	0.42	0.52	0.68	mA	V _{DD} = 5V VI=0V for CE08321X-L VI=5V for CE08321X-H
	I _{DD2}	0.42	0.52	0.68	mA	
	I _{DD1}	0.44	0.55	0.71	mA	V _{DD} = 5V VI=5V for CE08321X-L VI=0V for CE08321X-H
	I _{DD2}	0.44	0.55	0.71	mA	
	I _{DD1}	0.41	0.52	0.67	mA	V _{DD} = 3.3V VI=0V for CE08321X-L VI=3.3V for CE08321X-H
	I _{DD2}	0.41	0.52	0.67	mA	
	I _{DD1}	0.41	0.52	0.66	mA	V _{DD} = 3.3V VI=3.3V for CE08321X-L VI=0V for CE08321X-H
	I _{DD2}	0.41	0.52	0.66	mA	
CE08322X	I _{DD1}	0.42	0.52	0.68	mA	V _{DD} = 5V VI=0V for CE08322X-L VI=5V for CE08322X-H
	I _{DD2}	0.42	0.52	0.68	mA	
	I _{DD1}	0.44	0.55	0.71	mA	V _{DD} = 5V VI=5V for CE08322X-L VI=0V for CE08322X-H
	I _{DD2}	0.44	0.55	0.71	mA	
	I _{DD1}	0.41	0.52	0.67	mA	V _{DD} = 3.3V VI=0V for CE08322X-L VI=3.3V for CE08322X-H
	I _{DD2}	0.41	0.52	0.67	mA	
	I _{DD1}	0.41	0.51	0.66	mA	V _{DD} = 3.3V VI=3.3V for CE08322X-L VI=0V for CE08322X-H
	I _{DD2}	0.41	0.51	0.66	mA	

Supply Current- AC signal


Parameter	Symbol	Min	Typ.	Max.	Unit	Condition
CE08340E	I _{DD1} (10M)		0.24	0.36	mA	V _{DD} = 5V
	I _{DD2} (10M)		1.76	2.63	mA	
	I _{DD1} (10M)		0.18	0.27	mA	V _{DD} = 3.3V
	I _{DD2} (10M)		1.43	2.14	mA	
CE08341E	I _{DD1} (10M)		0.97	1.46	mA	V _{DD} = 5V
	I _{DD2} (10M)		0.97	1.46	mA	
	I _{DD1} (10M)		0.77	1.16	mA	V _{DD} = 3.3V
	I _{DD2} (10M)		0.77	1.16	mA	
CE08342E	I _{DD1} (10M)		0.97	1.60	mA	V _{DD} = 5V
	I _{DD2} (10M)		0.97	1.60	mA	
	I _{DD1} (10M)		0.77	1.20	mA	V _{DD} = 3.3V
	I _{DD2} (10M)		0.77	1.20	mA	
CE08340E	I _{DD1} (200M)		3.72	5.95	mA	V _{DD} = 5V
	I _{DD2} (200M)		17.20	27.52	mA	
	I _{DD1} (200M)		2.16	3.46	mA	V _{DD} = 3.3V
	I _{DD2} (200M)		11.14	17.82	mA	
CE08341E	I _{DD1} (200M)		10.40	16.64	mA	V _{DD} = 5V
	I _{DD2} (200M)		10.40	16.64	mA	
	I _{DD1} (200M)		6.58	10.53	mA	V _{DD} = 3.3V
	I _{DD2} (200M)		6.58	10.53	mA	
CE08342E	I _{DD1} (200M)		10.40	16.64	mA	V _{DD} = 5V
	I _{DD2} (200M)		10.40	16.64	mA	
	I _{DD1} (200M)		6.58	10.53	mA	V _{DD} = 3.3V
	I _{DD2} (200M)		6.58	10.53	mA	

Parameter	Symbol	Min	Typ.	Max.	Unit	Condition
CE08340M	$I_{DD1}(10M)$		0.24	0.36	mA	$V_{DD} = 5V$
	$I_{DD2}(10M)$		1.76	2.63	mA	
	$I_{DD1}(10M)$		0.18	0.27	mA	$V_{DD} = 3.3V$
	$I_{DD2}(10M)$		1.43	2.14	mA	
CE08341M	$I_{DD1}(10M)$		0.97	1.46	mA	$V_{DD} = 5V$
	$I_{DD2}(10M)$		0.97	1.46	mA	
	$I_{DD1}(10M)$		0.77	1.16	mA	$V_{DD} = 3.3V$
	$I_{DD2}(10M)$		0.77	1.16	mA	
CE08342M	$I_{DD1}(10M)$		0.97	1.60	mA	$V_{DD} = 5V$
	$I_{DD2}(10M)$		0.97	1.60	mA	
	$I_{DD1}(10M)$		0.77	1.20	mA	$V_{DD} = 3.3V$
	$I_{DD2}(10M)$		0.77	1.20	mA	

Fig. 1 Switching Time waveform measurement


Order Information


Part Number




Option	Description	Packing quantity
(TA)	Surface mount lead form + TA tape & reel option	4000 units per reel

Package Dimension
(Dimensions in mm)



Device Marking**Notes**

CE	denotes EVERLIGHT
032XX	denotes Device Number
Y	denotes 1 digit Year code
WW	denotes 2 digit Week code

Precautions for Use**1. Soldering Condition****1.1 (A) Maximum Body Case Temperature Profile for evaluation of Reflow Profile**

Note:

Reference: IPC/JEDEC J-STD-020D

Preheat

Temperature min (T_{smin})	150 °C
Temperature max (T_{smax})	200°C
Time (T_{smin} to T_{smax}) (t_s)	60-120 seconds
Average ramp-up rate (T_{smax} to T_P)	3 °C/second max

Other

Liquidus Temperature (T_L)	217 °C
Time above Liquidus Temperature (t_L)	60-100 sec
Peak Temperature (T_P)	260°C
Time within 5 °C of Actual Peak Temperature: $T_P - 5^\circ\text{C}$	30 s
Ramp- Down Rate from Peak Temperature	6°C /second max.
Time 25°C to peak temperature	8 minutes max.
Reflow times	3 times

DISCLAIMER

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
3. When using this product, please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
4. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without the specific consent of EVERLIGHT.
5. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.
6. Statements regarding the suitability of products for certain types of applications are based on Everlight's knowledge of typical requirements that are often placed on Everlight products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Everlight's terms and conditions of purchase, including but not limited to the warranty expressed therein.