

ISSUE 7; July 2016



Description

- Surface mount temperature compensated voltage controlled crystal oscillator (TCVCXO) in a hermetically sealed ceramic package

Frequency Parameters

- Frequency: 10.0MHz to 26.0MHz
- Frequency Tolerance: $\pm 0.50\text{ppm}$
- Frequency Stability: $\pm 1.50\text{ppm}$ to $\pm 5.00\text{ppm}$
- Ageing: $\pm 1\text{ppm}$ typ in 1st year @ 25°C
- Supply Voltage Variation (@ $\pm 5\%$ change): $\pm 0.2\text{ppm}$ max
- Load Variation (@ $\pm 10\%$ change): $\pm 0.2\text{ppm}$ max

Electrical Parameters

- Supply Voltage: 3.0V $\pm 0.3\text{V}$

Frequency Adjustment

- Pulling: $\pm 5\text{ppm}$ min
- Control Voltage: 1.5V $\pm 1.0\text{V}$
- Input Impedance: 1M Ω
- Frequency movement is positive sense
- Input Impedance (Pad 1): 1.0M Ω min

Operating Temperature Ranges

- 0 to 50°C
- 10 to 60°C
- 20 to 70°C
- 30 to 80°C
- 40 to 85°C
- 30 to 85°C

Output Details

- Output Compatibility: Clipped Sine
- Drive Capability: 10k Ω /10pF $\pm 10\%$
- Output Level: 0.8Vpk-pk minimum

Noise Parameters




- Phase Noise (typical @ 10MHz):
 - 90dBc/Hz @ 10Hz
 - 110dBc/Hz @ 100Hz
 - 140dBc/Hz @ 1kHz
 - 145dBc/Hz @ 10kHz

Environmental Parameters

- Storage Temperature Range: -55 to 125°C
- Shock: MIL-STD-883D, Method 2002.3, Test Condition B: 1500G, 0.5ms, 1/2 sine wave, 3 shocks in each of 3 mutually perpendicular planes
- Vibration: MIL-STD-883D, Method 2005.2, Test Condition B: 20G (20Hz-2000Hz), 1.5mm amplitude, in 3 mutually perpendicular planes, 4hrs in each plane




Outline (mm)




Pad Connections

- Voltage Control
- GND
- Output
- +Vs

Solder Pad Layout



Test Circuit



* Inclusive of jiggging and equipment capacitance

Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com

Ordering Information

- Frequency*
Model*
Output
Frequency Stability (over operating temperature range)*
Operating Temperature Range*
Supply Voltage
- Example
13.0MHz CFPT-123
Clipped Sine ± 2.5 ppm -30 to 80C 3.0V

Compliance

- RoHS Status (2011/65/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

Packaging Details

- Pack Style: Reel Tape & reel in accordance with EIA-481-D
Pack Size: 1,000
- Pack Style: Bulk Loose in bulk pack
Pack Size: 100
- Pack Style: Cutt In tape, cut from a reel
Pack Size: 1

Electrical Specification - maximum limiting values 3.0V ± 0.3 V

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
10.0MHz	26.0MHz	0 to 50	± 1.5	2.5	-	-
		-10 to 60	± 1.5	2.5	-	-
		-20 to 70	± 2.0	2.5	-	-
		-30 to 85	± 2.0	2.5	-	-
		-40 to 85	± 2.5	2.5	-	-

This document was correct at the time of printing; please contact your local sales office for the latest version.
[Click to view latest version on our website.](#)

Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com