

ISSUE 6; September 2016

Description

2 x 6mm watch crystal with pre-formed legs to make a SMD package. Suitable for real time clock applications.

Frequency Parameters

Frequency **Frequency Tolerance** 32.768kHz

- **Tolerance Condition**
- Ageing

±20.00ppm @ 25°C

±5ppm max in 1st year

Electrical Parameters

Load Capacitance (CL)

6.0pF to 12.5pF 1.6pF typical

- Shunt Capacitance (C0) 1.0µW max
- Drive Level
- Motional Capacitance (C1) 3.2fF typ
- Frequency Stability Coefficient: -0.034ppm/°C² ±0.006ppm/°C²

Operating Temperature Ranges

-40 to 85°C

Environmental Parameters

- High Temperature Storage: 85°C for 24hrs
- Drop: 75cm drop (3 times) onto hard wooden board
- Storage Temperature Range: -40 to 85°C

Manufacturing Details

- Suitable for reflow soldering at 245°C max for 10sec max x 1 cycle
- Note: Do not solder the body of the device to any PCB pads. Use other bonding methods such as adhesive, sealant, sticky-pads.

Ordering Information

- Frequency* Model* Frequency Tolerance @25°C Load Capacitance* Example
- 32.768kHz CFPX-56 20/-/-/12.5

Compliance


- RoHS Status (2011/65/EU) Compliant
- **REACh Status** Compliant
- Not Applicable MSL Rating (JDEC-STD-033):

Packaging Details

- Pack Style: Bulk Loose in bulk pack Pack Size: 100
- Pack Style: Reel Tape & reel in accordance with EIA-481-D Pack Size: 3,000



Outline (mm)




Sales Office Contact Details: UK: +44 (0)1460 270200 Germany: 0800 1808 443

France: 0800 901 383 USA: +1.760.318.2824 Email: info@iqdfrequencyproducts.com Web: www.iqdfrequencyproducts.com




Quartz Crystal Specification **CFPX-56**

Typical Frequency Stability Characteristics



Reflow Temperature Profile



Electrical Specification - maximum limiting values

Frequency	Temperature Range	Stability (Min)	Over Tone Order	ESR
	۵°	ppm		Ω
32.768000kHz	-40 to 85	-	Fundamental	40,000

France: 0800 901 383 USA: +1.760.318.2824 Email: info@iqdfrequencyproducts.com Web: www.iqdfrequencyproducts.com