

Main Product Characteristics

$I_{F(AV)}$	3A
V_{RRM}	60V
T_J	150°C
$V_{F(Typ)}$	0.42V

Features

- Low forward voltage drop.
- Excellent high temperature stability.
- Fast switching capability.
- Lead-free parts meet environmental standards of MIL-STD-19500 /228

Mechanical data


- Epoxy:UL94-V0 rated flame retardant
- Case : Molded plastic, DO-214AC / SMA
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity : Indicated by cathode band
- Weight : Approximated 0.08 gram

Maximum ratings and electrical characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Outline

SMA(DO-214AC)



Dimensions in inches and (millimeters)

Parameter	Conditions	Symbol	CL36AG	UNIT
Working peak reverse voltage		V_{RWM}	60	V
Forward rectified current		I_O	3	A
Forward surge current	8.3ms single half sine-wave superimposed on rate load (JEDEC method)	I_{FSM}	60	A
Typical Thermal resistance (per leg)	Junction to case	R_{BJC}	25	°C/W
	Junction to ambient	R_{BJA}	70	°C/W
Storage temperature		T_{STG}	-55 ~ +150	°C
Junction temperature		T_J	-55 ~ +150	°C

Parameter	Conditions	Symbol	MIN.	TYP.	MAX.	UNIT
Forward voltage drop	$I_F = 3A, T_J = 25^\circ C$	V_F		490	550	mV
	$I_F = 3A, T_J = 125^\circ C$			420		
Reverse current	$V_R = 60V, T_J = 25^\circ C$	I_R		0.002	0.1	mA
	$V_R = 60V, T_J = 125^\circ C$			2	20	
Reverse Breakdown Voltage(per diode)	$I_F = 0.1A, T_J = 25^\circ C$	V_{BR}	60			V

■ Rating and characteristic curves

Fig. 1 - Forward Characteristics




Fig. 2 - Reverse Characteristics




Fig. 3 - Forward Power Dissipation




Fig. 4 - Forward Current Derating Curve






Fig. 5 - Junction Capacitance



■ Marking Information




CL36 : Product type marking code

■ Ordering / Packing Information

	Part number	Case	Q'TY/Reel (PCS)	Q'TY/Box (PCS)	Q'TY/Carton (PCS)
	CL36AG	SMA	5,000	10,000	50,000

Notes : 1. For packaging details please reference our website at <http://www.citcorp.com.tw/tchinese/products/index.php>

■ SMA foot print



A	B	C
0.068 (1.70)	0.104 (2.60)	0.060 (1.50)

- CITC reserves the right to make changes to this document and its products and specifications at any time without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- CITC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does CITC assume any liability for application assistance or customer product design.
- CITC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of CITC.
- CITC products are not authorized for use as critical components in life support devices or systems without express written approval of CITC.