


CLT-13-6013**Temperature Compensated Amplifier
6 GHz - 13 GHz**

This Amplifier offers exceptional performance over the band 6 GHz to 13 GHz with 14 dBm P1dB output power and 24 dB Gain.

Teledyne Microwave amplifiers are balanced or feedback designs and manufactured with the latest MIC & MMIC technology. The GaAs FET's used in these amplifiers are well established proven devices from multiple sources.

Teledyne Microwave offers a complete line of Narrow and broadband Amplifiers covering the frequency range 500 MHz to 40 GHz. These products are available in either connectorized packages or as modules. For a complete list of these products and more, please visit our website.

Other products from Teledyne Microwave include: Transceivers, Synthesizers, and YIG Products

**Specifications:**

DataSheet4U.com


Model Number: CLT-13-6013
 Frequency Range: 6 GHz - 13 GHz
 Gain (min): 24 dB
 Gain Vs Temp at any Frequency: +/-1.25 dB
 Noise Figure (max): 4.2 dB
 Output Power @ 1dB Compression: 14 dBm
 Gain Flatness Vs Frequency: +/-1.0 dB
 3rd Order Intercept (Typ): 27 dBm
 Power Supply:
 Input Voltage: 11.5 to 15 VDC
 Current @ 12 VDC (typ): 240 mA
 Current @ 12 VDC (max): 270 mA
 Case Type (See attached Outline): SX4
 Temperature Range: -54 to +90C



ISO 9001:2000

CLT-13-6013

Temperature Compensated Amplifier 6 GHz - 13 GHz



ISO 9001:2000