


< HVIGBT MODULES >

CM1500HG-66R

HIGH POWER SWITCHING USE
INSULATED TYPE

4th-Version HVIGBT (High Voltage High Insulated Gate Bipolar Transistor) Modules

CM1500HG-66R




- I_C 1500A
- V_{CES} 3300V
- 1-element in a Pack
- High Insulated Type
- LPT-IGBT / Soft Recovery Diode
- AISiC Baseplate

APPLICATION

Traction drives, High Reliability Converters / Inverters, DC choppers

OUTLINE DRAWING & CIRCUIT DIAGRAM

Dimensions in mm



< HVIGBT MODULES >

CM1500HG-66RHIGH POWER SWITCHING USE
INSULATED TYPE

4th-Version HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules

MAXIMUM RATINGS

Symbol	Item	Conditions	Ratings	Unit
V_{CES}	Collector-emitter voltage	$V_{GE} = 0V, T_j = -40...+150^{\circ}C$	3300	V
		$V_{GE} = 0V, T_j = -50^{\circ}C$	3200	
V_{GES}	Gate-emitter voltage	$V_{CE} = 0V, T_j = 25^{\circ}C$	± 20	V
I_C	Collector current	DC, $T_c = 90^{\circ}C$	1500	A
I_{CRM}		Pulse (Note 1)	3000	A
I_E	Emitter current (Note 2)	DC	1500	A
I_{ERM}		Pulse (Note 1)	3000	A
P_{tot}	Maximum power dissipation (Note 3)	$T_c = 25^{\circ}C$, IGBT part	14700	W
V_{iso}	Isolation voltage	RMS, sinusoidal, $f = 60Hz$, $t = 1$ min.	10200	V
V_e	Partial discharge extinction voltage	RMS, sinusoidal, $f = 60Hz$, $Q_{PD} \leq 10$ pC	5100	V
T_j	Junction temperature		$-50 \sim +150$	$^{\circ}C$
T_{jop}	Operating junction temperature		$-50 \sim +150$	$^{\circ}C$
T_{stg}	Storage temperature		$-55 \sim +150$	$^{\circ}C$
t_{psc}	Short circuit pulse width	$V_{CC} = 2500V, V_{CE} \leq V_{CES}, V_{GE} = 15V, T_j = 150^{\circ}C$	10	μs

ELECTRICAL CHARACTERISTICS

Symbol	Item	Conditions	Limits			Unit
			Min	Typ	Max	
I_{CES}	Collector cutoff current	$V_{CE} = V_{CES}, V_{GE} = 0V$	$T_j = 25^{\circ}C$	—	6.0	mA
			$T_j = 125^{\circ}C$	—	6.0	
			$T_j = 150^{\circ}C$	—	36.0	
$V_{GE(th)}$	Gate-emitter threshold voltage	$V_{CE} = 10V, I_C = 150mA, T_j = 25^{\circ}C$	5.7	6.2	6.7	V
I_{GES}	Gate leakage current	$V_{GE} = V_{GES}, V_{CE} = 0V, T_j = 25^{\circ}C$	-0.5	—	0.5	μA
C_{ies}	Input capacitance	$V_{CE} = 10V, V_{GE} = 0V, f = 100kHz$ $T_j = 25^{\circ}C$	—	210.0	—	nF
C_{oes}	Output capacitance		—	13.0	—	nF
C_{res}	Reverse transfer capacitance		—	6.0	—	nF
Q_G	Total gate charge	$V_{CC} = 1800V, I_C = 1500A, V_{GE} = \pm 15V$	—	16.0	—	μC
V_{CESat}	Collector-emitter saturation voltage	$I_C = 1500A$ (Note 4) $V_{GE} = 15V$	$T_j = 25^{\circ}C$	—	2.45	V
			$T_j = 125^{\circ}C$	—	3.10	
			$T_j = 150^{\circ}C$	—	3.25	
$t_{d(on)}$	Turn-on delay time	$V_{CC} = 1800V$ $I_C = 1500A$ $V_{GE} = \pm 15V$	$T_j = 25^{\circ}C$	—	1.00	μs
			$T_j = 125^{\circ}C$	—	0.95	
			$T_j = 150^{\circ}C$	—	0.95	
t_r	Turn-on rise time	$V_{CC} = 1800V$ $I_C = 1500A$ $V_{GE} = \pm 15V$	$T_j = 25^{\circ}C$	—	0.28	μs
			$T_j = 125^{\circ}C$	—	0.30	
			$T_j = 150^{\circ}C$	—	0.30	
$E_{on(10\%)}$	Turn-on switching energy (Note 5)	$R_{G(on)} = 1.6\Omega$ $L_s = 100nH$ Inductive load	$T_j = 25^{\circ}C$	—	2.10	J
			$T_j = 125^{\circ}C$	—	2.75	
			$T_j = 150^{\circ}C$	—	3.00	
E_{on}	Turn-on switching energy (Note 6)		$T_j = 25^{\circ}C$	—	2.20	J
			$T_j = 125^{\circ}C$	—	2.90	
			$T_j = 150^{\circ}C$	—	3.20	
$t_{d(off)}$	Turn-off delay time	$V_{CC} = 1800V$ $I_C = 1500A$ $V_{GE} = \pm 15V$	$T_j = 25^{\circ}C$	—	2.70	μs
			$T_j = 125^{\circ}C$	—	2.80	
			$T_j = 150^{\circ}C$	—	2.85	
t_f	Turn-off fall time	$V_{CC} = 1800V$ $I_C = 1500A$ $V_{GE} = \pm 15V$	$T_j = 25^{\circ}C$	—	0.30	μs
			$T_j = 125^{\circ}C$	—	0.35	
			$T_j = 150^{\circ}C$	—	0.40	
$E_{off(10\%)}$	Turn-off switching energy (Note 5)	$R_{G(off)} = 5.6\Omega$ $L_s = 100nH$ Inductive load	$T_j = 25^{\circ}C$	—	2.00	J
			$T_j = 125^{\circ}C$	—	2.45	
			$T_j = 150^{\circ}C$	—	2.50	
E_{off}	Turn-off switching energy (Note 6)		$T_j = 25^{\circ}C$	—	2.20	J
			$T_j = 125^{\circ}C$	—	2.70	
			$T_j = 150^{\circ}C$	—	2.80	

ELECTRICAL CHARACTERISTICS (continuation)

Symbol	Item	Conditions		Limits			Unit
				Min	Typ	Max	
V _{EC}	Emitter-collector voltage (Note 2)	I _E = 1500 A (Note 4) V _{GE} = 0 V	T _J = 25°C	—	2.15	—	V
			T _J = 125°C	—	2.30	2.80	
			T _J = 150°C	—	2.25	—	
t _{rr}	Reverse recovery time (Note 2)	V _{CC} = 1800 V I _C = 1500 A V _{GE} = ±15 V R _{G(on)} = 1.6 Ω L _s = 100 nH Inductive load	T _J = 25°C	—	0.50	—	μs
			T _J = 125°C	—	0.70		
			T _J = 150°C	—	0.80	—	
I _{rr}	Reverse recovery current (Note 2)		T _J = 25°C	—	1250	—	A
			T _J = 125°C	—	1500	—	
			T _J = 150°C	—	1550	—	
Q _{rr}	Reverse recovery charge (Note 2)		T _J = 25°C	—	1050	—	μC
			T _J = 125°C	—	1700		
			T _J = 150°C	—	2000	—	
E _{rec(10%)}	Reverse recovery energy (Note 2) (Note 5)		T _J = 25°C		1.05	—	J
			T _J = 125°C	—	1.75		
			T _J = 150°C	—	2.00	—	
E _{rec}	Reverse recovery energy (Note 2) (Note 6)		T _J = 25°C		1.20	—	J
			T _J = 125°C	—	2.00		
			T _J = 150°C	—	2.30	—	

THERMAL CHARACTERISTICS





Symbol	Item	Conditions	Limits			Unit
			Min	Typ	Max	
$R_{th(j-c)Q}$	Thermal resistance	Junction to Case, IGBT part	—	—	8.5	K/kW
$R_{th(j-c)D}$		Junction to Case, FWDi part	—	—	15.5	K/kW
$R_{th(c-s)}$	Contact thermal resistance	Case to heat sink, $\lambda_{grease} = 1\text{ W/m}^2\text{K}$, $D_{(c-s)} = 100\mu\text{m}$	—	6.0	—	K/kW





MECHANICAL CHARACTERISTICS





Symbol	Item	Conditions	Limits			Unit
			Min	Typ	Max	
M_t	Mounting torque	M8 : Main terminals screw	7.0	—	22.0	N·m
M_s		M6 : Mounting screw	3.0	—	6.0	N·m
M_t		M4 : Auxiliary terminals screw	1.0	—	3.0	N·m
m	Mass		—	1.4	—	kg
CTI	Comparative tracking index		600	—	—	—
d_a	Clearance		26.0	—	—	mm
d_s	Creepage distance		56.0	—	—	mm
L_{PCE}	Parasitic stray inductance		—	15.0	—	nH
R_{CC+EE}	Internal lead resistance	$T_C = 25^\circ\text{C}$	—	0.18	—	m Ω
r_g	Internal gate resistance	$T_C = 25^\circ\text{C}$	—	1.5	—	Ω




Note1. Pulse width and repetition rate should be such that junction temperature (T_J) does not exceed T_{opmax} rating(150°C).

- The symbols represent characteristics of the anti-parallel, emitter to collector free-wheel diode (FWD).
- Junction temperature (T_J) should not exceed T_{Jmax} rating (150°C).
- Pulse width and repetition rate should be such as to cause negligible temperature rise.
- $E_{on(10\%)}$ / $E_{off(10\%)}$ / $E_{rec(10\%)}$ are the integral of $0.1V_{CE} \times 0.1I_C \times dt$.
- Definition of all items is according to IEC 60747, unless otherwise specified.

PERFORMANCE CURVES**OUTPUT CHARACTERISTICS
(TYPICAL)****TRANSFER CHARACTERISTICS
(TYPICAL)****COLLECTOR-EMITTER SATURATION VOLTAGE
CHARACTERISTICS (TYPICAL)****FREE-WHEEL DIODE FORWARD
CHARACTERISTICS (TYPICAL)**




PERFORMANCE CURVES**CAPACITANCE CHARACTERISTICS
(TYPICAL)****GATE CHARGE CHARACTERISTICS
(TYPICAL)****HALF-BRIDGE SWITCHING ENERGY
CHARACTERISTICS (TYPICAL)****HALF-BRIDGE SWITCHING ENERGY
CHARACTERISTICS (TYPICAL)**

PERFORMANCE CURVES**HALF-BRIDGE SWITCHING ENERGY CHARACTERISTICS (TYPICAL)****HALF-BRIDGE SWITCHING ENERGY CHARACTERISTICS (TYPICAL)****HALF-BRIDGE SWITCHING TIME CHARACTERISTICS (TYPICAL)****HALF-BRIDGE SWITCHING TIME CHARACTERISTICS (TYPICAL)**

PERFORMANCE CURVES**FREE-WHEEL DIODE REVERSE RECOVERY CHARACTERISTICS (TYPICAL)****FREE-WHEEL DIODE REVERSE RECOVERY CHARACTERISTICS (TYPICAL)****TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS**

$$Z_{th(j-c)}(t) = \sum_{i=1}^n R_i \left\{ 1 - \exp\left(-\frac{t}{\tau_i}\right) \right\}$$

	1	2	3	4
R_i [K/kW] :	0.0055	0.2360	0.4680	0.2905
t_i [sec] :	0.0001	0.0131	0.0878	0.6247

PERFORMANCE CURVES**REVERSE BIAS SAFE OPERATING AREA (RBSOA)****SHORT CIRCUIT SAFE OPERATING AREA (SCSOA)****FREE-WHEEL DIODE REVERSE RECOVERY SAFE OPERATING AREA (RRSOA)**

Keep safety first in your circuit designs!

Mitsubishi Electric Corporation puts the maximum effort into making semiconductor products better and more reliable, but there is always the possibility that trouble may occur with them. Trouble with semiconductors may lead to personal injury, fire or property damage. Remember to give due consideration to safety when making your circuit designs, with appropriate measures such as (i) placement of substitutive, auxiliary circuits, (ii) use of non-flammable material or (iii) prevention against any malfunction or mishap.

Notes regarding these materials

- These materials are intended as a reference to assist our customers in the selection of the Mitsubishi semiconductor product best suited to the customer's application; they do not convey any license under any intellectual property rights, or any other rights, belonging to Mitsubishi Electric Corporation or a third party.
- Mitsubishi Electric Corporation assumes no responsibility for any damage, or infringement of any third-party's rights, originating in the use of any product data, diagrams, charts, programs, algorithms, or circuit application examples contained in these materials.
- All information contained in these materials, including product data, diagrams, charts, programs and algorithms represents information on products at the time of publication of these materials, and are subject to change by Mitsubishi Electric Corporation without notice due to product improvements or other reasons. It is therefore recommended that customers contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor for the latest product information before purchasing a product listed herein.

The information described here may contain technical inaccuracies or typographical errors. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability, or other loss rising from these inaccuracies or errors.

Please also pay attention to information published by Mitsubishi Electric Corporation by various means, including the Mitsubishi Semiconductor home page (<http://www.MitsubishiElectric.com/>).

- When using any or all of the information contained in these materials, including product data, diagrams, charts, programs, and algorithms, please be sure to evaluate all information as a total system before making a final decision on the applicability of the information and products. Mitsubishi Electric Corporation assumes no responsibility for any damage, liability or other loss resulting from the information contained herein.
- Mitsubishi Electric Corporation semiconductors are not designed or manufactured for use in a device or system that is used under circumstances in which human life is potentially at stake. Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor when considering the use of a product contained herein for any specific purposes, such as apparatus or systems for transportation, vehicular, medical, aerospace, nuclear, or undersea repeater use.
- The prior written approval of Mitsubishi Electric Corporation is necessary to reprint or reproduce in whole or in part these materials.
- If these products or technologies are subject to the Japanese export control restrictions, they must be exported under a license from the Japanese government and cannot be imported into a country other than the approved destination.
Any diversion or re-export contrary to the export control laws and regulations of Japan and/or the country of destination is prohibited.
- Please contact Mitsubishi Electric Corporation or an authorized Mitsubishi Semiconductor product distributor for further details on these materials or the products contained therein.