

698 to 960 MHz/1710 to 2700 MHz 2-port MIMO Ceiling Mount Antenna



2-PORT MIMO MULTI-BAND CEILING MOUNTED OMNIDIRECTIONAL ANTENNA

The CMD69273 is an indoor broadband 2-port MIMO omnidirectional ceiling mount antenna. It is designed to provide pattern coverage that is optimized for indoor requirements at 698-960 MHz and 1710-2700 MHz for the CELLULAR, UMTS, and LTE/WiMAX frequency bands. The individual antenna elements are designed with linear H/V-polarization components oriented to provide a pattern that has been specifically shaped to provide optimal performance from a ceiling mount location.

FEATURES

- Low Profile aesthetically neutral housing
- Mounts directly and easily to ceiling tile
- Wide bandwidth 700/850/900/1800/1900/UMTS/2300/2400/2500
- Two radiating elements optimized for indoor MIMO Applications
- Low cross correlation between radiating elements
- Conformance to RoHS

MARKETS

- Cellular
- LTE/WiMAX
- 802.11 a/b/g/n
- Warehouse, Offices and Meeting Rooms
- Hotels, Museums, Libraries, Retail Malls
- Airport, Bus Terminals and Train Stations
- Other in-building areas

BENEFITS

- Complete cellular and 3G/4G data communications in a single antenna
- Radiating elements are oriented to provide maximal coverage
- To mitigate the multipath polarization propagation issue, each radiating element is designed to have dual-linear H/V polarization characteristics

	CMD69273
Frequency	698-960 MHz / 1710-2700 MHz
Peak Gain	3.35 dBi @ 700 MHz Band, 4.4 dBi @ 800 / 900 MHz Band 5.0 dBi @ 1800/1900/UMTS MHz Band, 5.6 dBi @ 2400/ 2500 MHz Band
Average Efficiency	93% @ 700 MHz Band, 89% @ 800 / 900 MHz Band 85% @ 1800/1900/UMTS MHz Band, 85% @ 2400/ 2500 MHz Band
VSWR	2.0:1 maximum across all bands
Nominal Impedance	50 ohms
Polarization	Linear H/V for each radiator
Max Input Power	25 watts
RF Connector	Dual Type N Male (Plug)
Cable	Dual 305 mm, Plenum rated
Enclosure	PC/ABS, UV stable
Antenna Weight	0.41 kg
Mounting	Ceiling Mount (flush mount with screws and anchors)
Operational Temperature	-30°C to +70°C
Storage Temperature	-40°C to +85°C
Material Substance Compliance	RoHS 6/6
Flammability Rating (Radome)	UL 94V0 Materials
Dimensions	Diameter 218.7 mm x Height 43.5 mm

global solutions: local support™

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com


Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

www.lairdtech.com


698 to 960 MHz/1710 to 2700 MHz
2-port MIMO Ceiling Mount Antenna

PATTERNS


750 MHz Radiation Pattern




869 MHz Radiation Pattern



915 MHz Radiation Pattern




1780 MHz Radiation Pattern




698 to 960 MHz/1710 to 2700 MHz
2-port MIMO Ceiling Mount Antenna

PATTERNS


1910 MHz Radiation Pattern



2110 MHz Radiation Pattern



2600 MHz Radiation Pattern



ANT-DS-CMD69273 0811

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of Sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2011 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.