

Features

- Uses CRM(CQ) advanced Trench technology
- Extremely low on-resistance $R_{DS(on)}$
- Excellent $Q_g \times R_{DS(on)}$ product(FOM)

Product Summary


Symbol	N-Ch	P-Ch
V_{DS}	30V	-30V
$R_{DS(on)}$ typ.	22m Ω	25m Ω
I_D	16A	-16A

Applications

- Motor drive

100% DVDS Tested

100% Avalanche Tested



Package Marking and Ordering Information

Part #	Marking	Package	Packing	Reel Size	Tape Width	Qty
CRMD0309C	CRMD0309C	PDFN5x6D	Taping	N/A	N/A	4000pcs

Absolute Maximum Ratings

Parameter	Symbol	Maximum		Unit
		N-Ch	P-Ch	
Drain-source voltage	V_{DS}	30	-30	V
Continuous drain current $T_C = 25^\circ\text{C}$ (Silicon limit)	I_D	20	-20	A
Continuous drain current $T_C = 25^\circ\text{C}$ (Package limit)	I_D	16	-16	A
Pulsed drain current ($T_C = 25^\circ\text{C}$, t_p limited by T_{jmax})	$I_{D \text{ pulse}}$	65	-65	A
Avalanche energy, single pulse ($L=0.5\text{mH}$, $R_g=25\Omega$)	E_{AS}	28	86	mJ
Gate-Source voltage	V_{GS}	± 20	± 20	V
Power dissipation ($T_C = 25^\circ\text{C}$)	P_{tot}	17.5	17.5	W
Operating junction and storage temperature	T_j, T_{stg}	-55...+150		$^\circ\text{C}$

Thermal Resistance

Parameter	Symbol	Typ	Max	Unit
Thermal resistance, junction – case.	R_{thJC}	5.1	7.1	$^{\circ}C/W$
SMD version, device on PCB ¹	R_{thJA}	64.8	77.7	$^{\circ}C/W$
Thermal resistance, junction – ambient(min. footprint)				

NOTE:

1.The value of R_{thJA} is measured with the device mounted on 1in2 FR-4 board with 2oz. Copper, in a still air environment with $T_A = 25^{\circ}C$. The value in any given application depends on the user's specific board design.

N-Channel Electrical Characteristic (at $T_j = 25^{\circ}C$, unless otherwise specified)

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		

Static Characteristic

Drain-source breakdown voltage	BV_{DSS}	30	-	-	V	$V_{GS}=0V, I_D=250\mu A$
Gate threshold voltage	$V_{GS(th)}$	1.1	1.6	2.1	V	$V_{DS}=V_{GS}, I_D=250\mu A$
Zero gate voltage drain current	I_{DSS}	-	0.08	1	μA	$V_{DS}=30V, V_{GS}=0V$ $T_j=25^{\circ}C$ $T_j=125^{\circ}C$
Gate-source leakage current	I_{GSS}	-	± 10	± 100	nA	$V_{GS}=\pm 20V, V_{DS}=0V$
Drain-source on-state resistance	$R_{DS(on)}$	-	30.0	36.0	m Ω	$V_{GS}=4.5V, I_D=5A$ $V_{GS}=10V, I_D=5A$
Transconductance	g_{fs}	-	14.9	-	S	$V_{DS}=5V, I_D=5A$





Dynamic Characteristic






Input Capacitance	C_{iss}	-	400	-	pF	$V_{GS}=0V, V_{DS}=30V, f=1MHz$
Output Capacitance	C_{oss}	-	50	-		
Reverse Transfer Capacitance	C_{rss}	-	42	-		
Gate Total Charge	Q_G	-	10.3	-	nC	$V_{GS}=10V, V_{DS}=30V, I_D=5A, f=1MHz$
Gate-Source charge	Q_{gs}	-	1.9	-		
Gate-Drain charge	Q_{gd}	-	2.6	-		
Turn-on delay time	$t_{d(on)}$	-	5.2	-	ns	$V_{GS}=10V, V_{DD}=15V, R_{G_ext}=2.7\Omega, I_D=5A$
Rise time	t_r	-	15.6	-		
Turn-off delay time	$t_{d(off)}$	-	12.0	-		
Fall time	t_f	-	2.4	-		
Gate resistance	R_G	-	1.1	-	Ω	$V_{GS}=0V, V_{DS}=0V, f=1MHz$


Body Diode Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Body Diode Forward Voltage	V_{SD}	-	0.9	1.2	V	$V_{GS}=0V, I_{SD}=10A$
Body Diode Reverse Recovery Time	t_{rr}	-	5.8	-	ns	$I_F=10A, dI/dt=100A/\mu s$
Body Diode Reverse Recovery Charge	Q_{rr}	-	1.4	-	nC	

N-Channel Typical Performance Characteristics











P-Channel Electrical Characteristic (at $T_j = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)






Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Static Characteristic						
Drain-source breakdown voltage	BV _{DSS}	-30	-	-	V	V _{GS} =0V, I _D =-250uA
Gate threshold voltage	V _{GS(th)}	-1.2	-1.7	-2.2	V	V _{DS} =V _{GS} , I _D =-250uA
Zero gate voltage drain current	I _{DSS}	-	-0.08	-1	μA	V _{DS} =-30V, V _{GS} =0V T _j =25°C T _j =125°C
Gate-source leakage current	I _{GSS}	-	±10	±100	nA	V _{GS} =±20V, V _{DS} =0V
Drain-source on-state resistance	R _{DS(on)}	-	35.0	42.0	mΩ	V _{GS} =-4.5V, I _D =-5A V _{GS} =-10V, I _D =-5A
Transconductance	g _{fs}	-	18.5	-	S	V _{DS} =-5V, I _D =-5A
Dynamic Characteristic						
Input Capacitance	C _{iss}	-	1287	-	pF	V _{GS} =0V, V _{DS} =-30V, f=1MHz
Output Capacitance	C _{oss}	-	144	-		
Reverse Transfer Capacitance	C _{rss}	-	119	-		
Gate Total Charge	Q _G	-	30.6	-	nC	V _{GS} =-10V, V _{DS} =-30V, I _D =-5A, f=1MHz
Gate-Source charge	Q _{gs}	-	4.9	-		
Gate-Drain charge	Q _{gd}	-	8.2	-		
Turn-on delay time	t _{d(on)}	-	6.5	-	ns	V _{GS} =-10V, V _{DD} =-15V, R _{G_ext} =2.7Ω, ID=-5A
Rise time	t _r	-	21.3	-		
Turn-off delay time	t _{d(off)}	-	56.2	-		
Fall time	t _f	-	45.8	-		
Gate resistance	R _G	-	30.0	-	Ω	V _{GS} =0V, V _{DS} =0V, f=1MHz


Body Diode Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Body Diode Forward Voltage	V_{SD}	-	-0.9	-1.2	V	$V_{GS}=0V, I_{SD}=-10A$
Body Diode Reverse Recovery Time	t_{rr}	-	14.8	-	ns	$I_F=10A, dI/dt=100A/\mu s$
Body Diode Reverse Recovery Charge	Q_{rr}	-	5.1	-	nC	


P-Channel Typical Performance Characteristics







Package Outline: PDFN5x6D



SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.90	1.00	1.15	0.035	0.039	0.045
b	0.25	0.39	0.52	0.010	0.015	0.020
c	0.20	0.25	0.30	0.008	0.010	0.012
D	4.80	5.10	5.40	0.189	0.201	0.213
D1	4.80	4.90	5.00	0.189	0.193	0.197
D2	3.90	4.20	4.50	0.154	0.165	0.177
D3	1.50	1.70	1.90	0.059	0.067	0.075
E	5.90	6.05	6.20	0.232	0.238	0.244
E1	5.45	5.70	5.85	0.215	0.224	0.230
E2	3.30	3.50	3.80	0.130	0.138	0.150
E3	1.10	----	----	0.043	----	----
e	1.27 BSC			0.050 BSC		
L	0.05	0.15	0.25	0.002	0.006	0.010
L1	0.38	----	0.75	0.015	----	0.030
L2	0.38	----	0.75	0.015	----	0.030
i	----	----	0.18	----	----	0.007
k	0.50	----	----	0.020	----	----

NOTE

- 1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
MOLD FLASH AT THE NON-LEAD SIDES SHOULD BE LESS THAN 6 MILS EACH.
- 2.CONTROLLING DIMENSION IS MILLIMETER.
CONVERTED INCH DIMENSIONS ARE NOT NECESSARILY EXACT.

Revision History

Revision	Date	Major changes
1.1	2023/1/5	Release of formal version

Disclaimer

Unless otherwise specified in the datasheet, the product is designed and qualified as a standard commercial product and is not intended for use in applications that require extraordinary levels of quality and reliability, such as automotive, aviation/aerospace and life-support devices or systems.

Any and all semiconductor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.

CRM(CQ) reserves the right to improve product design, function and reliability without notice.