

TEL: (858) 621-2700
URL: www.zcomm.com
EMAIL: applications@zcomm.com


Voltage-Controlled Oscillator Surface Mount Module

Applications

Microwave Radios
Satellite Communications
Point to Point

Application Notes

AN-101: Mounting and Grounding
AN-102: Output Loading
AN-107: Manual Soldering




Performance Specifications	Min	Typ	Max	Units
Oscillation Frequency Range	4030		4325	MHz
Phase Noise @ 10 kHz offset (1 Hz BW)		-100		dBc/Hz
Harmonic Suppression (2nd)		-25	-20	dBc
Tuning Voltage	2		13	Vdc
Tuning Sensitivity (avg.)		50		MHz/V
Power Output	0	5	10	dBm
Load Impedance		50		Ω
Input Capacitance			50	pF
Pushing			2	MHz/V
Pulling (14 dB Return Loss, Any Phase)			1	MHz
Operating Temperature Range	-40		85	$^{\circ}\text{C}$
Package Style	MINI-16-SM			


Power Supply Requirements	Min	Typ	Max	Units
Supply Voltage (Vcc, nom.)		8		Vdc
Supply Current (Icc)		30	36	mA

Additional Notes


Tuning Curve, typ.




Power Curve, typ.



Footprint



Physical Dimensions



LFSuffix = RoHS Compliant. All specifications are subject to change without notice.