

### General Description

This product family is CRM's third generation SiC JBS, with lower  $V_F$  and offers state of the art performance. It is designed for high frequency applications where high efficiency and high reliability are required. It is qualified and manufactured on the productive 6 inch SiC line in China fully owned by CR MICRO.

### Product Summary

|                          |       |
|--------------------------|-------|
| $V_{RRM}$                | 650 V |
| $I_F (T_C=163^{\circ}C)$ | 6 A   |
| $Q_C$                    | 15 nC |

### Features

- Low conduction loss due to low  $V_F$
- Extremely low switching loss by tiny  $Q_C$
- Highly rugged due to better surge current
- Industrial standard quality and reliability



### Applications

- Server
- Telecom
- High performance SMPS
- Power factor correction

TO-252-2



Equivalent circuit



### Package Marking and Ordering Information

| Part #       | Marking      | Package  |
|--------------|--------------|----------|
| CRXL06D065G3 | CRXL06D065G3 | TO-252-2 |

**Maximum Ratings (at  $T_c = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)**

| Parameter                                                                                                                                                                             | Symbol        | Value         | Unit                 |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------------|----------------------|
| Repetitive Peak Reverse Voltage                                                                                                                                                       | $V_{RRM}$     | 650           | V                    |
| Surge Peak Reverse Voltage                                                                                                                                                            | $V_{RSM}$     | 650           | V                    |
| DC Peak Reverse Voltage                                                                                                                                                               | $V_R$         | 650           | V                    |
| Continuous Forward Current<br>$T_c = 25^{\circ}\text{C}$<br>$T_c = 135^{\circ}\text{C}$<br>$T_c = 163^{\circ}\text{C}$                                                                | $I_F$         | 22<br>11<br>6 | A                    |
| Non-Repetitive Forward Surge Current<br>$T_c = 25^{\circ}\text{C}, t_p=8.3\text{ms}, \text{Half Sine Pulse}$<br>$T_c = 110^{\circ}\text{C}, t_p=8.3\text{ms}, \text{Half Sine Pulse}$ | $I_{FSM}$     | 42<br>36      | A                    |
| $i^2t$ value<br>$T_c = 25^{\circ}\text{C}, t_p=8.3\text{ms}, \text{Half Sine Pulse}$<br>$T_c = 110^{\circ}\text{C}, t_p=8.3\text{ms}, \text{Half Sine Pulse}$                         | $\int i^2 dt$ | 7<br>5        | $\text{A}^2\text{s}$ |
| Power dissipation<br>$T_c = 25^{\circ}\text{C}$<br>$T_c = 110^{\circ}\text{C}$                                                                                                        | $P_{tot}$     | 68<br>30      | W                    |
| Operating junction Range                                                                                                                                                              | $T_j$         | -55 to +175   | $^{\circ}\text{C}$   |
| Storage temperature Range                                                                                                                                                             | $T_{stg}$     | -55 to +150   | $^{\circ}\text{C}$   |

**Thermal Resistance**

| Parameter                            | Symbol     | Max. | Unit |
|--------------------------------------|------------|------|------|
| Thermal resistance, junction – case. | $R_{thJC}$ | 2.17 | °C/W |

**Electrical Characteristic (at  $T_c = 25\text{ °C}$ , unless otherwise specified)**

| Parameter               | Symbol | Value |      |      | Unit | Test Condition                                                     |
|-------------------------|--------|-------|------|------|------|--------------------------------------------------------------------|
|                         |        | min.  | typ. | max. |      |                                                                    |
| Forward Voltage         | $V_F$  | -     | 1.31 | 1.7  | V    | $I_F=6A$<br>$T_j=25\text{ °C}$<br>$T_j=175\text{ °C}$              |
| Reverse Current         | $I_R$  | -     | 2    | 50   | μA   | $V_R=650V$<br>$T_j=25\text{ °C}$<br>$T_j=175\text{ °C}$            |
| Total Capacitive Charge | $Q_C$  | -     | 15   | -    | nC   | $V_R=400V, T_j=25\text{ °C}$<br>$Q_C = \int_0^{V_R} C(V)dV$        |
| Total Capacitance       | C      | -     | 384  | -    | pF   | $T_j=25\text{ °C}, f=1MHz$<br>$V_R=0V$<br>$V_R=200V$<br>$V_R=400V$ |

## Characteristics Curve:

Fig 1: Forward Characteristics




Fig 2: Reverse Characteristics




Fig 3: Current Derating




Fig 4: Power Derating




Fig 5: Capacitance vs. Reverse Voltage




Fig 6: Reverse Charge vs. Reverse Voltage




Fig 7: Typical Capacitance Stored Energy






Fig 8: Transient Thermal Impedance



**Package Outline: TO-252-2**


| Items | Values(mm) |       |
|-------|------------|-------|
|       | MIN        | MAX   |
| A     | 6.40       | 6.80  |
| A1    | 0.00       | 0.13  |
| B     | 5.80       | 6.20  |
| C     | 2.20       | 2.40  |
| D     | 0.40       | 0.60  |
| E1    | 0.60       | 0.80  |
| F     | 0.40       | 0.60  |
| G     | 0.80       | 1.00  |
| L1    | 9.70       | 10.20 |
| L2    | 2.70       | 3.10  |
| M     | 5.10       | 5.50  |
| N     | 4.38       | 4.78  |
| R     | 0.30       |       |
| T     | 1.40       | 1.60  |
| Y     | 5.90       | 6.30  |

## Revision History

| Revision | Date | Major changes              |
|----------|------|----------------------------|
| 1.0      |      | Release of formal version. |

## Warnings

Exceeding the maximum ratings of the device in performance may cause damage to the device, even the permanent failure, which may affect the dependability of the machine. It is suggested to be used under 80 percent of the maximum ratings of the device.

1. When installing the heatsink, please pay attention to the torsional moment and the smoothness of the heatsink.
2. This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, or air traffic control systems.