

N-Channel Trench Power MOSFET

General Description

The CS150N95 is N-channel MOS Field Effect Transistor designed for high current switching applications. Rugged E_{AS} capability and ultra low R_{DS(ON)} is suitable for PWM, load switching especially for E-Bike controller applications.

Features


- V_{DS}=150V; I_D=104A@ V_{GS}=10V;
R_{DS(ON)}<14.0mΩ @ V_{GS}=10V
- Special Designed for E-Bike Controller Application
- Ultra Low On-Resistance
- High UIS and UIS 100% Test

Application

- 96V E-Bike controller applications
- Hard Switched and High Frequency Circuits
- Uninterruptible Power Supply



To-220 Top View



Schematic Diagram

V_{DS} = 150VI_D = 104AR_{DS(ON)} = 9.3mΩ**Package Marking and Ordering Information**

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
CS150N95	CS150N95	TO-220	-	-	-

Table 1. Absolute Maximum Ratings (TA=25°C)

Symbol	Parameter	Value	Unit
V _{DS}	Drain-Source Voltage (V _{GS} =0V)	150	V
V _{GS}	Gate-Source Voltage (V _{DS} =0V)	±25	V
I _D (DC)	Drain Current (DC) at T _c =25°C	104	A
I _D (DC)	Drain Current (DC) at T _c =100°C	73	A
I _{DM} (pulse)	Drain Current-Continuous@ Current-Pulsed ^(Note 1)	416	A
dv/dt	Peak Diode Recovery Voltage	7	V/ns
P _D	Maximum Power Dissipation(T _c =25°C)	348	W
	Derating Factor	2.33	W/°C
E _{AS}	Single Pulse Avalanche Energy ^(Note 2)	1600	mJ
T _J , T _{STG}	Operating Junction and Storage Temperature Range	-55 To 175	°C

Notes 1.Repetitive Rating: Pulse width limited by maximum junction temperature

2.EAS condition:T_J=25°C,V_{DD}=50V,V_G=10V, R_G=25Ω

Table 2. Thermal Characteristic

Symbol	Parameter	Value	Max	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	---	0.43	°C/W



Table 3. Electrical Characteristics (TA=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
On/Off States						
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	150			V
$I_{DS(on)}$	Zero Gate Voltage Drain Current($T_c=25^\circ C$)	$V_{DS}=150V, V_{GS}=0V$			1	μA
$I_{DS(on)}$	Zero Gate Voltage Drain Current($T_c=125^\circ C$)	$V_{DS}=150V, V_{GS}=0V$			10	μA
I_{GSS}	Gate-Body Leakage Current	$V_{GS}=\pm 20V, V_{DS}=0V$			± 100	nA
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	3		5	V
$R_{DS(on)}$	Drain-Source On-State Resistance	$V_{GS}=10V, I_D=40A$		9.3	14.0	$m\Omega$
Dynamic Characteristics						
g_{FS}	Forward Transconductance	$V_{DS}=10V, I_D=15A$	20			S
C_{iss}	Input Capacitance	$V_{DS}=25V, V_{GS}=0V$ $f=1.0MHz$		9152		PF
C_{oss}	Output Capacitance			944		PF
C_{rss}	Reverse Transfer Capacitance			133		PF
Q_g	Total Gate Charge	$V_{DS}=50V, I_D=40A$ $V_{GS}=10V$		274		nC
Q_{gs}	Gate-Source Charge			56		nC
Q_{gd}	Gate-Drain Charge			113		nC
Switching Times						
$t_{d(on)}$	Turn-on Delay Time	$V_{DD}=65V, I_D=40A, R_L=15\Omega$ $V_{GS}=10V, R_G=2.5\Omega$		40		nS
t_r	Turn-on Rise Time			72		nS
$t_{d(off)}$	Turn-Off Delay Time			103		nS
t_f	Turn-Off Fall Time			35		nS
Source-Drain Diode Characteristics						
I_{SD}	Source-Drain Current(Body Diode)			104		A
I_{SDM}	Pulsed Source-Drain Current(Body Diode)			416		A
V_{SD}	Forward On Voltage ^(Note 1)	$T_J=25^\circ C, I_{SD}=40A, V_{GS}=0V$		0.85	0.99	V
t_{rr}	Reverse Recovery Time ^(Note 1)	$T_J=25^\circ C, I_F=40A$ $di/dt=100A/\mu s$		80		nS
Q_{rr}	Reverse Recovery Charge ^(Note 1)			200		nC
t_{on}	Forward Turn-on Time	Intrinsic turn-on time is negligible(turn-on is dominated by L_S+L_D)				



Notes 1.Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 1.5%, $R_G=25\Omega$, Starting $T_J=25^\circ C$

Test Circuit



1) E_{AS} Test Circuits



2) Gate Charge Test Circuit:



3) Switch Time Test Circuit:



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS (Curves)

Figure1. Output Characteristics




Figure2. Transfer Characteristics



Figure3. BV_{DSS} vs Junction Temperature

Figure4. ID vs Junction Temperature




Figure5. VGS(th) vs Junction Temperature




Figure6. Rdson Vs Junction Temperature




Figure7. Gate Charge




Figure8. Capacitance vs Vds




Figure9. Source- Drain Diode Forward




Figure10. Safe Operation Area






Figure11. Normalized Maximum Transient Thermal Impedance



TO-220 Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.300	4.700	0.169	0.185
A1	2.200	2.600	0.087	0.102
b	0.700	0.950	0.028	0.037
b1	1.170	1.410	0.046	0.056
c	0.450	0.650	0.018	0.026
c1	1.200	1.400	0.047	0.055
D	9.600	10.400	0.378	0.409
E	8.8500	9.750	0.348	0.384
E1	12.650	12.950	0.498	0.510
e	2.540 TYP.		0.100TYP.	
e1	4.980	5.180	0.196	0.204
F	2.650	2.950	0.104	0.116
H	7.500	7.700	0.295	0.303
h	0.000	0.300	0.000	0.012
L	12.750	14.300	0.502	0.563
L1	2.850	3.950	0.112	0.156
V	6.80 REF.		0.267 REF.	
Φ	3.400	4.000	0.134	0.157