



Silicon N-Channel Power MOSFET



CS19N40F A9R

## General Description:

CS19N40F A9R, the silicon N-channel Enhanced VDMOSFETs, is obtained by the self-aligned planar Technology which reduce the conduction loss, improve switching performance and enhance the avalanche energy. The transistor can be used in various power switching circuit for system miniaturization and higher efficiency. The package form is TO-220F, which accords with the RoHS standard.

## Features:


- | Fast Switching
- | Low ON Resistance( $R_{DS(on)} \leq 0.30\Omega$ )
- | Low Gate Charge (Typical Data:42nC)
- | Low Reverse transfer capacitances(Typical:12.3pF)
- | 100% Single Pulse avalanche energy Test

## Applications:

Power switch circuit of electron ballast and adaptor.


$V_{DSS}$	400	V
$I_D$	19	A
$P_D$ ( $T_C=25^\circ C$ )	33	W
$R_{DS(ON)Typ}$	0.23	$\Omega$

TO-220F



1. Gate 2. Drain 3. Source

Inner Equivalent Principium Chart



**Absolute** ( $T_J = 25^\circ C$  unless otherwise specified):

Symbol	Parameter	Rating	Units
$V_{DSS}$	Drain-to-Source Voltage	400	V
$I_D$	Continuous Drain Current $T_C = 25^\circ C$	19	A
	Continuous Drain Current $T_C = 100^\circ C$	12	A
$I_{DM}^{a1}$	Pulsed Drain Current $T_C = 25^\circ C$	76	A
$V_{GS}$	Gate-to-Source Voltage	$\pm 30$	V
$E_{AS}^{a2}$	Single Pulse Avalanche Energy	720	mJ
$dv/dt^{a3}$	Peak Diode Recovery $dv/dt$	5.0	V/ns
$P_D$	Power Dissipation $T_C = 25^\circ C$	33	W
	Derating Factor above $25^\circ C$	0.264	W/ $^\circ C$
$T_J, T_{stg}$	Operating Junction and Storage Temperature Range	150, -55 to 150	$^\circ C$
$T_L$	Maximum Temperature for Soldering	300	$^\circ C$

**Electrical Characteristics** ( $T_J = 25^\circ\text{C}$  unless otherwise specified):

OFF Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$V_{DSS}$	Drain to Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu\text{A}$	400	--	--	V
$\Delta BV_{DSS}/\Delta T_J$	Bvdss Temperature Coefficient	ID=250uA, Reference 25°C	--	0.46	--	V/°C
$I_{DSS}$	Drain to Source Leakage Current	$V_{DS} = 400\text{V}, V_{GS} = 0\text{V}, T_J = 25^\circ\text{C}$	--	--	1	$\mu\text{A}$
		$V_{DS} = 320\text{V}, V_{GS} = 0\text{V}, T_J = 125^\circ\text{C}$	--	--	100	
$I_{GSS(F)}$	Gate to Source Forward Leakage	$V_{DS} = 0\text{V}, V_{GS} = 30\text{V}$	--	--	100	nA
$I_{GSS(R)}$	Gate to Source Reverse Leakage	$V_{DS} = 0\text{V}, V_{GS} = -30\text{V}$	--	--	-100	nA

ON Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$R_{DS(ON)}$	Drain-to-Source On-Resistance	$V_{GS}=10\text{V}, I_D=9.5\text{A}$	--	0.23	0.30	$\Omega$
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	2.0	--	4.0	V
Pulse width $t_p \leqslant 300\mu\text{s}, \delta \leqslant 2\%$						

Dynamic Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$g_{fs}$	Forward Trans conductance	$V_{DS}=15\text{V}, I_D = 9.5\text{A}$	--	15	--	S
$R_g$	Gate resistance	f = 1.0MHz	--	2.5	--	$\Omega$
$C_{iss}$	Input Capacitance	$V_{GS} = 0\text{V} V_{DS} = 25\text{V}$ f = 1.0MHz	--	1919	--	pF
$C_{oss}$	Output Capacitance		--	206	--	
$C_{rss}$	Reverse Transfer Capacitance		--	12.3	--	

Resistive Switching Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$t_{d(ON)}$	Turn-on Delay Time	$I_D = 19\text{A} V_{DD} = 200\text{V}$ $R_G = 25\Omega$	--	21	--	ns
$t_r$	Rise Time		--	36	--	
$t_{d(OFF)}$	Turn-Off Delay Time		--	55	--	
$t_f$	Fall Time		--	55	--	
$Q_g$	Total Gate Charge	$I_D = 19\text{A} V_{DD} = 320\text{V}$ $V_{GS} = 10\text{V}$	--	42	--	nC
$Q_{gs}$	Gate to Source Charge		--	9.1	--	
$Q_{gd}$	Gate to Drain ("Miller")Charge		--	17	--	



Source-Drain Diode Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
I <sub>S</sub>	Continuous Source Current (Body Diode)	T <sub>C</sub> = 25 °C	--	--	19	A
I <sub>SM</sub>	Maximum Pulsed Current (Body Diode)		--	--	76	A
V <sub>SD</sub>	Diode Forward Voltage	I <sub>S</sub> =19A, V <sub>GS</sub> =0V	--	--	1.5	V
t <sub>rr</sub>	Reverse Recovery Time	I <sub>S</sub> =19A, T <sub>j</sub> = 25° C dI <sub>F</sub> /dt=100A/us, V <sub>GS</sub> =0V	--	347	--	ns
Q <sub>rr</sub>	Reverse Recovery Charge		--	3183	--	nC
I <sub>RRM</sub>	Reverse Recovery Current		--	18.3	--	A
Pulse width t <sub>p</sub> ≤ 300μs, δ ≤ 2%						

Symbol	Parameter	Max.	Units
R <sub>θJC</sub>	Junction-to-Case	3.76	°C/W
R <sub>θJA</sub>	Junction-to-Ambient	62.5	°C/W

<sup>a1</sup>: Repetitive rating; pulse width limited by maximum junction temperature

<sup>a2</sup>: L=10.0mH, I<sub>D</sub>=12A, Start T<sub>j</sub>=25°C

<sup>a3</sup>: I<sub>SD</sub>=19A, dI/dt ≤ 300A/us, V<sub>DD</sub> ≤ BV<sub>DS</sub>, Start T<sub>j</sub>=25°C

### Characteristics Curve:




Figure 1 Maximum Power dissipation vs Case Temperature




Figure 2 Maximum Continuous Drain Current vs Case Temperature




Figure 3 Typical Output Characteristics




Figure 4 Maximum Effective Thermal Impedance , Junction to Case




Figure 5 Typical Transfer Characteristics




Figure 6 Typical Body Diode Transfer Characteristics




Figure 7 Typical Drain to Source ON Resistance vs Drain Current




Figure 8 Typical Drian to Source on Resistance vs Junction Temperature




Figure 9 Typical Threshold Voltage vs Junction Temperature




Figure 10 Typical Breakdown Voltage vs Junction Temperature




Figure 11 Typical Capacitance vs Drain to Source Voltage




Figure 12 Typical Gate Charge vs Gate to Source Voltage

## Test Circuit and Waveform




Figure 14. Gate Charge Test Circuit



Figure 15. Gate Charge Waveforms




Figure 16. Resistive Switching Test Circuit



Figure 17. Resistive Switching Waveforms



Figure 18. Diode Reverse Recovery Test Circuit




Figure 19. Diode Reverse Recovery Waveform




Figure 20. Unclamped Inductive Switching Test Circuit

Figure 21. Unclamped Inductive Switching Waveform





## Package Information



Items	Values(mm)	
	MIN	MAX
A	9.60	10.4
B	15.4	16.2
B1	8.90	9.50
C	4.30	4.90
C1	2.10	3.00
D	2.40	3.00
E	0.60	1.00
F	0.30	0.60
G	1.12	1.42
H	3.40	3.80
	1.60	2.90
L*	12.0	14.0
N	2.34	2.74
Q	3.15	3.55
Φ P	2.90	3.30

\*adjustable

TO-220F Package

**The name and content of poisonous and harmful material in products**

Part's Name	Hazardous Substance									
	Pb	Hg	Cd	Cr(VI)	PBB	PBDE	DI BP	DEHP	DBP	BBP
Limit	≤ 0.1%	≤ 0.1%	≤ 0.01%	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%	≤0.1%
Lead Frame	○	○	○	○	○	○	○	○	○	○
Molding	○	○	○	○	○	○	○	○	○	○
Chip	○	○	○	○	○	○	○	○	○	○
Wire Bonding	○	○	○	○	○	○	○	○	○	○
Solder	×	○	○	○	○	○	○	○	○	○
Note	<p>○: Means the hazardous material is under the criterion of 2011/65/EU.</p> <p>×: Means the hazardous material exceeds the criterion of 2011/65/EU.</p> <p>The plumbum element of solder exist in products presently, but within the allowed range of Eurogroup's RoHS.</p>									

**Warnings**

1. Exceeding the maximum ratings of the device in performance may cause damage to the device, even the permanent failure, which may affect the dependability of the machine. It is suggested to be used under 80 percent of the maximum ratings of the device.
2. When installing the heatsink, please pay attention to the torsional moment and the smoothness of the heatsink.
3. VDMOSFETs is the device which is sensitive to the static electricity, it is necessary to protect the device from being damaged by the static electricity when using it.
4. This publication is made by Huajing Microelectronics and subject to regular change without notice.

**WUXI CHINA RESOURCES HUAJING MICROELECTRONICS CO., LTD.**

Add: No.14 Liangxi RD. Wuxi, Jiangsu, China Mail:214061 <http://www.crhj.com.cn>

Tel: +86 0510-85807228 Fax: +86- 0510-85800864

Marketing Part: Post: 214061 Tel: +86 0510-81805277/81805336  
Fax: +86 0510-85800360/85803016

**Application and Service: Post: 214061 Tel / Fax: +86- 0510-81805243/81805110**