



Silicon N-Channel Power MOSFET




CS3N20 A23H

General Description:

CS3N20 A23H, the silicon N-channel Enhanced VDMOSFETs, is obtained by the self-aligned planar Technology which reduce the conduction loss, improve switching performance and enhance the avalanche energy. The transistor can be used in various power switching circuit for system miniaturization and higher efficiency. The package form is SOT-223, which accords with the RoHS standard.

V_{DSS}	200	V
I_D	3	A
$P_D(T_C=25^\circ\text{C})$	2.5	W
$R_{DS(\text{ON})\text{Typ}}$	1.2	Ω




Features:

- | **Fast Switching**
- | **Low ON Resistance($R_{DSON} \leq 1.5\Omega$)**
- | **Low Gate Charge** (Typical Data: 4.3nC)
- | **Low Reverse transfer capacitances**(Typical:5.5pF)
- | **100% Single Pulse avalanche energy Test**

Applications:

Power switch circuit of adaptor and charger.

Inner Equivalent Principium Chart



Absolute ($T_C = 25^\circ\text{C}$ unless otherwise specified):

Symbol	Parameter	Rating	Units
V_{DSS}	Drain-to-Source Voltage	200	V
I_D	Continuous Drain Current	3	A
	Continuous Drain Current $T_C = 100^\circ\text{C}$	1.9	A
I_{DM}^{a1}	Pulsed Drain Current	12	A
V_{GS}	Gate-to-Source Voltage	± 30	V
E_{AS}^{a2}	Single Pulse Avalanche Energy	28	mJ
dv/dt^{a3}	Peak Diode Recovery dv/dt	5.0	V/ns
P_D	Power Dissipation	2.5	W
	Derating Factor above 25°C	0.02	$\text{W}/^\circ\text{C}$
T_J, T_{stg}	Operating Junction and Storage Temperature Range	150, -55 to 150	$^\circ\text{C}$
T_L	Maximum Temperature for Soldering	300	$^\circ\text{C}$

**Electrical Characteristics** ($T_c = 25^\circ C$ unless otherwise specified):

OFF Characteristics						
Symbol	Parameter	Test Conditions	Rating			Unit
			Min.	Typ.	Max.	
V_{DSS}	Drain to Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	200	--	--	V
$\Delta BV_{DSS}/\Delta T_J$	Bvdss Temperature Coefficient	$I_D=250\mu A, Reference 25^\circ C$	--	0.25	--	$^\circ C$
I_{DSS}	Drain to Source Leakage Current	$V_{DS}=200V, V_{GS}=0V, T_a=25^\circ C$	--	--	1	μA
		$V_{DS}=160V, V_{GS}=0V, T_a=125^\circ C$	--	--	100	μA
$I_{GSS(F)}$	Gate to Source Forward Leakage	$V_{GS}=+30V$	--	--	100	nA
$I_{GSS(R)}$	Gate to Source Reverse Leakage	$V_{GS}=-30V$	--	--	-100	nA

ON Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$R_{DS(ON)}$	Drain-to-Source On-Resistance	$V_{GS}=10V, I_D=1.5A$	--	1.2	1.5	Ω
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2.0	--	4.0	V
Pulse width $t_p \leq 300\mu s, \delta \leq 2\%$						

Dynamic Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
C_{iss}	Input Capacitance	$V_{GS}=0V, V_{DS}=25V, f=1.0MHz$	--	101	--	pF
C_{oss}	Output Capacitance		--	23	--	
C_{rss}	Reverse Transfer Capacitance		--	5.5	--	

Resistive Switching Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$t_{d(ON)}$	Turn-on Delay Time	$I_D=3A, V_{DD}=100V, R_G=10\Omega$	--	7	--	ns
t_r	Rise Time		--	12	--	
$t_{d(OFF)}$	Turn-Off Delay Time		--	27	--	
t_f	Fall Time		--	7	--	
Q_g	Total Gate Charge	$I_D=3A, V_{DD}=160V, V_{GS}=10V$	--	4.3	--	nC
Q_{gs}	Gate to Source Charge		--	1.4	--	
Q_{gd}	Gate to Drain ("Miller") Charge		--	1.6	--	

**Source-Drain Diode Characteristics**

Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
I _S	Continuous Source Current (Body Diode)		--	--	3	A
I _{SM}	Maximum Pulsed Current (Body Diode)		--	--	12	A
V _{SD}	Diode Forward Voltage	I _S =3.0A, V _{GS} =0V	--	--	1.5	V
t _{rr}	Reverse Recovery Time	I _S =3.0A, T _j = 25 °C dI _F /dt=100A/us, V _{GS} =0V	--	87	--	ns
Q _{rr}	Reverse Recovery Charge		--	223	--	nC
I _{RRM}	Reverse Recovery Current		--	5.2	--	A
Pulse width tp≤300μs, δ ≤2%						

Symbol	Parameter	Max.	Units
R _{θJC}	Junction-to-Case	50	°C/W
R _{θJA}	Junction-to-Ambient	200	°C/W

^{a1}: Repetitive rating; pulse width limited by maximum junction temperature

^{a2}: L=10mH, I_D=2.4A, Start T_j=25 °C

^{a3}: I_{SD}=3A, di/dt ≤100A/us, V_{DD}≤BV_{DS}, Start T_j=25 °C

Characteristics Curve:




Figure 1 Maximum Forward Bias Safe Operating Area




Figure 2 Maximum Power Dissipation vs Case Temperature




Figure 3 Maximum Continuous Drain Current vs Case Temperature




Figure 4 Typical Output Characteristics




Figure 5 Maximum Effective Thermal Impedance, Junction to Case



CS3N20 A23H




Figure 6 Typical Transfer Characteristics




Figure 7 Typical Body Diode Transfer Characteristics




Figure 8 Typical Drain to Source ON Resistance vs Drain Current




Figure 9 Typical Drian to Source on Resistance vs Junction Temperature




Figure 10 Typical Threshold Voltage vs Junction Temperature




Figure 11 Typical Breakdown Voltage vs Junction Temperature




Figure 12 Typical Capacitance vs Drain to Source Voltage




Figure 13 Typical Gate Charge vs Gate to Source Voltage

Test Circuit and Waveform:




Figure 17. Gate Charge Test Circuit




Figure 18. Gate Charge Waveform




Figure 19. Resistive Switching Test Circuit




Figure 20. Resistive Switching Waveforms




Figure 21. Diode Reverse Recovery Test Circuit




Figure 22. Diode Reverse Recovery Waveform




Figure 23. Unclamped Inductive Switching Test Circuit





Figure 24. Unclamped Inductive Switching Waveforms

**Package Information:**

Items	Values(mm)	
	MIN	MAX
A	6.18	6.42
B	3.28	3.72
C	1.50	1.82
C1	0.00	0.12
C2	1.48	1.72
D	2.88	3.12
E	0.64	0.85
F	0.23	0.37
L	6.80	7.10
L1	0.88	1.17
N	2.25	2.40
N1	4.50	4.80
θ	0°	10°

SOT-223 Package



The name and content of poisonous and harmful material in products

Warnings

1. Exceeding the maximum ratings of the device in performance may cause damage to the device, even the permanent failure, which may affect the dependability of the machine. It is suggested to be used under 80 percent of the maximum ratings of the device.
 2. When installing the heat sink, please pay attention to the torsional moment and the smoothness of the heat sink.
 3. VDMOSFETs is the device which is sensitive to the static electricity, it is necessary to protect the device from being damaged by the static electricity when using it.
 4. This publication is made by Huajing Microelectronics and subject to regular change without notice.

WUXI CHINA RESOURCES HUAJING MICROELECTRONICS CO., LTD.

Add: No.14 Liangxi RD. Wuxi, Jiangsu, China Mail:214061 <http://www.crhj.com.cn>
Tel: +86 0510-85807228 Fax: +86-0510-85800864

Marketing Part: Post: 214061 Tel: +86 0510-81805277/81805336
Fax: +86 0510-85800360/85803016
E-mail : sales@hj.crmicro.com

Application and Service: Post: 214061 Tel / Fax: +86-0510-81805243/81805110