

## N-Channel Trench Power MOSFET

**General Description**

The CS48N18 is N-channel MOS Field Effect Transistor designed for high current switching applications. Rugged E<sub>AS</sub> capability and ultra low  $R_{DS(ON)}$  is suitable for PWM, load switching especially for E-Bike controller applications.

**Features**


- $V_{DS}=70V$ ;  $I_D=158A$ @  $V_{GS}=10V$ ;  
 $R_{DS(ON)}<4.0m\Omega$  @  $V_{GS}=10V$
- Special Designed for E-Bike Controller Application
- Ultra Low On-Resistance
- High UIS and UIS 100% Test

**Application**

- 48V E-Bike Controller Applications
- Hard Switched and High Frequency Circuits
- Uninterruptible Power Supply



To-220 Top View



Schematic Diagram

 $V_{DSS} = 70V$  $I_{DSS} = 158A$  $R_{DS(ON)} = 3.3m\Omega$ **Package Marking and Ordering Information**

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
CS48N18	48N18	TO-220	-	-	-

**Table 1. Absolute Maximum Ratings (TA=25°C)**

Symbol	Parameter	Value	Unit
$V_{DS}$	Drain-Source Voltage ( $V_{GS}=0V$ )	70	V
$V_{GS}$	Gate-Source Voltage ( $V_{DS}=0V$ )	$\pm 25$	V
$I_D$ (DC)	Drain Current (DC) at $T_c=25^\circ C$	158	A
$I_D$ (DC)	Drain Current (DC) at $T_c=100^\circ C$	110	A
$I_{DM}$ (pulse)	Drain Current-Continuous@ Current-Pulsed <sup>(Note 1)</sup>	632	A
$dv/dt$	Peak Diode Recovery Voltage	7.5	V/ns
$P_D$	Maximum Power Dissipation( $T_c=25^\circ C$ )	230	W
	Derating Factor	1.54	W/°C
$E_{AS}$	Single Pulse Avalanche Energy <sup>(Note 2)</sup>	1300	mJ
$T_J, T_{STG}$	Operating Junction and Storage Temperature Range	-55 To 175	°C

Notes 1.Repetitive Rating: Pulse width limited by maximum junction temperature

2. $E_{AS}$  condition: $T_J=25^\circ C, V_{DD}=33V, V_G=10V$

**Table 2. Thermal Characteristic**

Symbol	Parameter	Value	Max	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	---	0.65	°C/W



**Table 3. Electrical Characteristics (TA=25°C unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
<b>On/Off States</b>						
$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu A$	70			V
$I_{DSS}$	Zero Gate Voltage Drain Current( $T_c=25^\circ C$ )	$V_{DS}=68V, V_{GS}=0V$			1	$\mu A$
$I_{DSS}$	Zero Gate Voltage Drain Current( $T_c=125^\circ C$ )	$V_{DS}=68V, V_{GS}=0V$			1	$\mu A$
$I_{GSS}$	Gate-Body Leakage Current	$V_{GS}=\pm 25V, V_{DS}=0V$			$\pm 100$	nA
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2		4	V
$R_{DS(ON)}$	Drain-Source On-State Resistance	$V_{GS}=10V, I_D=40A$		3.3	4.0	$m\Omega$
<b>Dynamic Characteristics</b>						
$g_{FS}$	Forward Transconductance	$V_{DS}=10V, I_D=40A$	22			S
$C_{iss}$	Input Capacitance	$V_{DS}=25V, V_{GS}=0V, f=1.0MHz$		5489		pF
$C_{oss}$	Output Capacitance			710		pF
$C_{rss}$	Reverse Transfer Capacitance			206		pF
$Q_g$	Total Gate Charge	$V_{DS}=30V, I_D=30A, V_{GS}=10V$		186		nC
$Q_{gs}$	Gate-Source Charge			37		nC
$Q_{gd}$	Gate-Drain Charge			97		nC
<b>Switching Times</b>						
$t_{d(on)}$	Turn-on Delay Time	$V_{DD}=30V, I_D=2A, R_L=15\Omega, V_{GS}=10V, R_G=2.5\Omega$		30		nS
$t_r$	Turn-on Rise Time			37		nS
$t_{d(off)}$	Turn-Off Delay Time			78		nS
$t_f$	Turn-Off Fall Time			36		nS
<b>Source-Drain Diode Characteristics</b>						
$I_{SD}$	Source-Drain Current(Body Diode)			158		A
$I_{SDM}$	Pulsed Source-Drain Current(Body Diode)			632		A
$V_{SD}$	Forward on Voltage <sup>(Note 1)</sup>	$T_J=25^\circ C, I_{SD}=40A, V_{GS}=0V$		0.82	0.99	V
$t_{rr}$	Reverse Recovery Time <sup>(Note 1)</sup>	$T_J=25^\circ C, I_F=75A, di/dt=100A/\mu s$		33		nS
$Q_{rr}$	Reverse Recovery Charge <sup>(Note 1)</sup>			45		nC
$t_{on}$	Forward Turn-on Time	Intrinsic turn-on time is negligible(turn-on is dominated by $L_S+L_D$ )				



Notes 1.Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 1.5%,  $R_G=25\Omega$ , Starting  $T_J=25^\circ C$

## Test Circuit



### 1) E<sub>AS</sub> Test Circuits



### 2) Gate charge Test Circuit:




### 3) Switch Time Test Circuit:




## TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS (Curves)


**Figure1. Output Characteristics**




**Figure2. Transfer Characteristics**




**Figure3. ID vs Junction Temperature**




**Figure5. BV<sub>DSS</sub> vs Junction Temperature**




**Figure4. R<sub>DS(ON)</sub> vs Junction Temperature**



**Figure6. V<sub>GS(th)</sub> vs Junction Temperature**




**Figure7. Gate Charge**




$Q_g$  Gate Charge (nC)

**Figure8. Capacitance vs Vds**




$V_{DS}$  Drain-Source Voltage (V)

**Figure9. Source- Drain Diode Forward**




$V_{SD}$  Source-Drain

**Figure10. Safe Operation Area**




$V_{DS}$  Drain-Source Voltage (V)

**Figure11. Normalized Maximum Transient Thermal Impedance**



## TO-220 Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.300	4.700	0.169	0.185
A1	2.200	2.600	0.087	0.102
b	0.700	0.950	0.028	0.037
b1	1.170	1.410	0.046	0.056
c	0.450	0.650	0.018	0.026
c1	1.200	1.400	0.047	0.055
D	9.600	10.400	0.378	0.409
E	8.8500	9.750	0.348	0.384
E1	12.650	12.950	0.498	0.510
e	2.540 TYP.		0.100TYP.	
e1	4.980	5.180	0.196	0.204
F	2.650	2.950	0.104	0.116
H	7.900	8.100	0.311	0.319
h	0.000	0.300	0.000	0.012
L	12.750	14.300	0.502	0.563
L1	2.850	3.950	0.112	0.156
V	7.500 REF.		0.295 REF.	
Φ	3.400	4.000	0.134	0.157