



Silicon N-Channel Power MOSFET



CS50N20 A8R

General Description:

CS50N20 A8R, the silicon N-channel Enhanced VDMOSFETs, is obtained by the self-aligned planar Technology which reduce the conduction loss, improve switching performance and enhance the avalanche energy. The transistor can be used in various power switching circuit for system miniaturization and higher efficiency. The package form is TO-220AB, which accords with the RoHS standard.

Features:

- | Fast Switching
- | Low ON Resistance($R_{DS(on)} \leq 51\text{m}\Omega$)
- | Low Gate Charge (Typical Data: 49.4nC)
- | Low Reverse transfer capacitances(Typical:34pF)
- | 100% Single Pulse avalanche energy Test

Applications:


Power switch circuit of adaptor and charger.

Absolute ($T_C = 25^\circ\text{C}$ unless otherwise specified):

| Symbol | Parameter | Rating | Units |
|----------------|--|-----------------|---------------------|
| V_{DSS} | Drain-to-Source Voltage | 200 | V |
| I_D | Continuous Drain Current | 50 | A |
| | Continuous Drain Current $T_C = 100^\circ\text{C}$ | 38.5 | A |
| I_{DM}^{a1} | Pulsed Drain Current | 200 | A |
| V_{GS} | Gate-to-Source Voltage | ± 30 | V |
| E_{AS}^{a2} | Single Pulse Avalanche Energy | 1700 | mJ |
| dv/dt^{a3} | Peak Diode Recovery dv/dt | 5.0 | V/ns |
| P_D | Power Dissipation | 250 | W |
| | Derating Factor above 25°C | 2.0 | W/ $^\circ\text{C}$ |
| T_J, T_{stg} | Operating Junction and Storage Temperature Range | 150, -55 to 150 | $^\circ\text{C}$ |
| T_L | Maximum Temperature for Soldering | 300 | $^\circ\text{C}$ |


| | | |
|-----------------------------|-----|------------------|
| V_{DSS} | 200 | V |
| I_D | 50 | A |
| $P_D(T_C=25^\circ\text{C})$ | 250 | W |
| $R_{DS(ON)Typ}$ | 42 | $\text{m}\Omega$ |

TO-220AB



1. Gate 2. Drain 3. Source

Inner Equivalent Principium Chart



**Electrical Characteristics (T_c= 25°C unless otherwise specified):**

| OFF Characteristics | | | | | | |
|--|-----------------------------------|--|--------|------|------|------|
| Symbol | Parameter | Test Conditions | Rating | | | Unit |
| | | | Min. | Typ. | Max. | |
| V _{DSS} | Drain to Source Breakdown Voltage | V _{GS} =0V, I _D =250μA | 200 | -- | -- | V |
| Δ BV _{DSS} / Δ T _J | Bvdss Temperature Coefficient | I _D =250μA, Reference 25°C | -- | 0.3 | -- | V/°C |
| I _{DSS} | Drain to Source Leakage Current | V _{DS} = 200V, V _{GS} = 0V, T _a = 25°C | -- | -- | 1 | μA |
| | | V _{DS} = 160V, V _{GS} = 0V, T _a = 125°C | -- | -- | 100 | μA |
| I _{GSS(F)} | Gate to Source Forward Leakage | V _{GS} = +30V | -- | -- | 100 | nA |
| I _{GSS(R)} | Gate to Source Reverse Leakage | V _{GS} = -30V | -- | -- | -100 | nA |

| ON Characteristics | | | | | | |
|--|-------------------------------|--|--------|------|------|-------|
| Symbol | Parameter | Test Conditions | Rating | | | Units |
| | | | Min. | Typ. | Max. | |
| R _{DS(ON)} | Drain-to-Source On-Resistance | V _{GS} =10V, I _D =20A | -- | 42 | 51 | mΩ |
| V _{GS(TH)} | Gate Threshold Voltage | V _{DS} = V _{GS} , I _D = 250μA | 2.0 | -- | 4.0 | V |
| Pulse width t _p ≤ 300μs, δ ≤ 2% | | | | | | |

| Dynamic Characteristics | | | | | | |
|-------------------------|------------------------------|--|--------|------|------|-------|
| Symbol | Parameter | Test Conditions | Rating | | | Units |
| | | | Min. | Typ. | Max. | |
| g _f | Forward Transconductance | V _{DS} =15V, I _D =20A | -- | 65 | -- | S |
| C _{iss} | Input Capacitance | | -- | 2819 | -- | pF |
| C _{oss} | Output Capacitance | V _{GS} = 0V V _{DS} = 25V f = 1.0MHz | -- | 394 | -- | |
| C _{rss} | Reverse Transfer Capacitance | | -- | 34 | -- | |

| Resistive Switching Characteristics | | | | | | |
|-------------------------------------|---------------------------------|--|--------|------|------|-------|
| Symbol | Parameter | Test Conditions | Rating | | | Units |
| | | | Min. | Typ. | Max. | |
| t _{d(ON)} | Turn-on Delay Time | I _D = 20A V _{DD} = 100V R _G = 10Ω | -- | 35.7 | -- | ns |
| t _r | Rise Time | | -- | 38.9 | -- | |
| t _{d(OFF)} | Turn-Off Delay Time | | -- | 74.7 | -- | |
| t _f | Fall Time | | -- | 21.9 | -- | |
| Q _g | Total Gate Charge | I _D = 20A V _{DD} = 160V V _{GS} = 10V | -- | 49.4 | -- | nC |
| Q _{gs} | Gate to Source Charge | | -- | 13 | -- | |
| Q _{gd} | Gate to Drain ("Miller") Charge | | -- | 18 | -- | |



| Source-Drain Diode Characteristics | | | | | | |
|------------------------------------|--|--|--------|------|-------|-------|
| Symbol | Parameter | Test Conditions | Rating | | | Units |
| | | | Min. | Typ. | Max. | |
| I _S | Continuous Source Current (Body Diode) | | -- | -- | 50 | A |
| I _{SM} | Maximum Pulsed Current (Body Diode) | | -- | -- | 200 | A |
| V _{SD} | Diode Forward Voltage | I _S =40A, V _{GS} =0V | -- | -- | 1.5 | V |
| trr | Reverse Recovery Time | I _S =20A, T _j = 25 °C dI _P /dt=100A/us, V _{GS} =0V | -- | -- | 261.3 | ns |
| Qrr | Reverse Recovery Charge | | -- | -- | 2770 | nC |
| I _{RRM} | Reverse Recovery Current | | -- | -- | 21.2 | A |

Pulse width tp ≤ 300μs, δ ≤ 2%

| Symbol | Parameter | Max. | Units |
|-------------------|---------------------|------|-------|
| R _{θ JC} | Junction-to-Case | 0.5 | °C/W |
| R _{θ JA} | Junction-to-Ambient | 62.5 | °C/W |

^{a1}: Repetitive rating; pulse width limited by maximum junction temperature

^{a2}: L=10mH, I_D=18.5A, Start T_j=25°C

^{a3}: I_{SD}=20A, di/dt ≤ 100A/us, V_{DD} ≤ BV_{DS}, Start T_j=25°C

Characteristics Curve:




Figure 1 Maximum Forward Bias Safe Operating Area




Figure 2 Maximum Power dissipation vs Case Temperature




Figure 3 Maximum Continuous Drain Current vs Case Temperature




Figure 4 Typical Output Characteristics




Figure 5 Maximum Effective Thermal Impedance , Junction to Case




Figure 6 Typical Transfer Characteristics




Figure 7 Typical Body Diode Transfer Characteristics




Figure 8 Typical Drain to Source ON Resistance vs Drain Current








Figure 9 Typical Drian to Source on Resistance vs Junction Temperature



Test Circuit and Waveform




Figure 17. Gate Charge Test Circuit




Figure 18. Gate Charge Waveform




Figure 19. Resistive Switching Test Circuit









Figure 20. Resistive Switching Waveforms





Package Information



| Items | Values(mm) | |
|-------|------------|------|
| | MIN | MAX |
| A | 9.60 | 10.6 |
| B | 15.0 | 16.0 |
| B1 | 8.90 | 9.50 |
| C | 4.30 | 4.80 |
| C1 | 2.30 | 3.10 |
| D | 1.20 | 1.40 |
| E | 0.70 | 0.90 |
| F | 0.30 | 0.60 |
| G | 1.17 | 1.37 |
| H | 2.70 | 3.80 |
| L* | 12.6 | 14.8 |
| N | 2.34 | 2.74 |
| Q | 2.40 | 3.00 |
| Φ P | 3.50 | 3.90 |

*adjustable

TO-220AB Package

**The name and content of poisonous and harmful material in products**

| Part's Name | Hazardous Substance | | | | | | | | | |
|--------------|---|-----------|------------|--------|-------|-------|-------|-------|-------|-------|
| | Pb | Hg | Cd | Cr(VI) | PBB | PBDE | DIBP | DEHP | DBP | BBP |
| Limit | ≤ 0.1% | ≤ 0.1% | ≤ 0.01% | ≤0.1% | ≤0.1% | ≤0.1% | ≤0.1% | ≤0.1% | ≤0.1% | ≤0.1% |
| Lead Frame | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Molding | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Chip | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Wire Bonding | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Solder | × | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ | ○ |
| Note | ○: Means the hazardous material is under the criterion of 2011/65/EU. ×: Means the hazardous material exceeds the criterion of 2011/65/EU. The plumbum element of solder exist in products presently, but within the allowed range of Eurogroup's RoHS. | | | | | | | | | |

Warnings

1. Exceeding the maximum ratings of the device in performance may cause damage to the device, even the permanent failure, which may affect the dependability of the machine. It is suggested to be used under 80 percent of the maximum ratings of the device.
2. When installing the heatsink, please pay attention to the torsional moment and the smoothness of the heatsink.
3. VDMOSFETs is the device which is sensitive to the static electricity, it is necessary to protect the device from being damaged by the static electricity when using it.
4. This publication is made by Huajing Microelectronics and subject to regular change without notice.

WUXI CHINA RESOURCES HUAJING MICROELECTRONICS CO., LTD.

Add: No.14 Liangxi RD. Wuxi, Jiangsu, China Mail:214061 <http://www.crhj.com.cn>
 Tel: +86 0510-85807228 Fax: +86-0510-85800864

Marketing Part: Post: 214061 **Tel:** +86 0510-81805277/81805336
Fax: +86 0510-85800360/85803016
E-mail : sales@hj.crmicro.com

Application and Service: Post: 214061 Tel / Fax: +86-0510-81805243/81805110