

CapStone
Technology

CS5263AN Datasheet
DP1.4 to HDMI2.0b Converter

Confidential for Preview Only

Contents

1	Introduction.....	5
2	Features.....	6
3	Pin Definition.....	7
3.1	Pin Assignments.....	7
3.2	Pin Description.....	7
4	Electrical Specifications	10
4.1	Absolute Maximum Conditions	10
4.2	Operating Conditions.....	10
4.3	Electrical Specification	10
5	Package Specification.....	12
6	Ordering Information.....	13
7	Revision History	14

List of Figures

Figure 1-1 CS5263AN Block Diagram	5
Figure 3-1 CS5263AN Pin Layout	7
Figure 5-1 CS5263AN Package Outline (QFN68 Leads 8x8mm2)	12

List of Tables

<i>Table 3-1 CS5263AN Pin Definitions</i> -----	7
<i>Table 4-1 Absolute Maximum Conditions</i> -----	10
<i>Table 4-2 Normal Operating Conditions</i> -----	10
<i>Table 4-3 DC Electrical Specification</i> -----	10
<i>Table 5-1 Package Dimension</i> -----	12
<i>Table 6-1 CS5263AN Ordering Information</i> -----	13
<i>Table 7-1 Document Revision History</i> -----	14

1 Introduction

The Capstone CS5263AN is a high-performance DP1.4 to HDMI2.0b converter, designed to connect a DP1.4 source to an HDMI2.0b sink. The CS5263AN integrates a DP1.4 compliant receiver, and a HDMI2.0b compliant transmitter.

The DP interface comprises 4 main lanes, AUX channel, and HPD signal. The receiver supports maximum 5.4Gbps (HBR2) data rate per lane. The DP receiver incorporates both HDCP1.4 and HDCP2.3 content protection scheme with embedded key for secure transmission of digital audio-video content.

The HDMI interface includes 4 TMDS clock/data pairs, DDC, and HPD signal. The HDMI transmitter is capable of supporting up to 6Gpbs data rate, quite adequate for handling video resolutions up to FHD 1080p 120Hz and UHD 4k 60Hz formats. The HDMI transmitter incorporates HDCP engines which support both HDCP1.4 and HDCP2.3. With the inclusion of HDCP, the CS5263AN allows secure transmission of protected content.

Embedded key is available that provides the highest level of HDCP key security.

The CS5263AN is a highly integrated single chip suitable for multiple market segments and display applications, such as the dongle, docking station etc.




Figure 1-1 CS5263AN Block Diagram

2 Features

General

- VESA DisplayPort™ (DP) v1.4 compliant receiver
- HDMI specification v2.0b compliant transmitter, data rate up to 6-Gbps per channel.
- Embedded oscillator and there's no need for the external crystal
- Embedded MCU and SPI flash
- Embedded EDID (CS5263AN will response EDID if terminal device doesn't have it)
- Support both HDCP 1.4 & HDCP2.3 with on-chip keys to support HDCP repeater.
- Support RGB 4:4:4 8/10bit bpc and YCbCr 4:4:4 , 4:2:2 ,4:2:0 8/10-bit bpc
- Max audio sample rate of 192KHz x8 channels
- LPCM and Compressed Audio encoding formats
- AUX channel, I2C host interface for chip control

DisplayPort Input (receiver)

- VESA DisplayPort™ v1.4 compliant. Support 4-lane.
- Up to HBR2(5.4-Gbps) input. Built-in high-performance adaptive equalizer. Support 1-MHz AUX channel
- Support Hot Plug Detect (HPD)

HDMI Digital Output

- HDMI 2.0b compliant
- Max data rate up to 6-Gbps per channel
- Support up to 3840 x 2160@60Hz or 4096x2160@60Hz
- Audio stream handling
- LPCM and Compressed Audio encoding formats
- Max audio sample rate of 192k Hz x8 channels Support High Dynamic Range (HDR) metadata handling

MISC

- Support I2C Master and Slave up to 400-kHz.
- HBM 4KV for connector pins
- 8*8mm 68-pin QFN package with e-Pad

Power & Technology

- 5V/1.0V system voltage, integrated 3.3V LDO and 1.8V LDO.

3 Pin Definition

3.1 Pin Assignments




Figure 3-1 CS5263AN Pin Layout

3.2 Pin Description

Table 3-1 CS5263AN Pin Definitions

Pin #	Description	Type	PU/PD	Note
1	NC	--		Reserved
2	AUX_N	AIO		DisplayPort AUX channel negative

Pin #	Description	Type	PU/PD	Note
3	AUX_P	AIO		DisplayPort AUX channel positive
4	RX_AVDD33	P	-	3.3V power input
5	RX_AVDD10	P	-	1.0V power input
6	LANEO_P	AI		DisplayPort Rx lane0 positive
7	LANEO_N	AI		DisplayPort Rx lane0 negative
8	GND	P		GND
9	LANE1_P	AI		DisplayPort Rx lane1 positive
10	LANE1_N	AI		DisplayPort Rx lane1 negative
11	RX_AVDD18	P	-	1.8V LDO output, connect a 4.7uF capacitor on it.
12	LANE2_P	AI		DisplayPort Rx lane2 positive
13	LANE2_N	AI		DisplayPort Rx lane2 negative
14	GND	P		GND
15	LANE3_P	AI		DisplayPort Rx lane3 positive
16	LANE3_N	AI		DisplayPort Rx lane3 negative
17	RX_AVDD10	P	-	1.0V power input
18	RX_AVDD33	P	-	3.3V power input
19	BB_DP	AIO		USB D+ signal for billboard device
20	BB_DM	AIO		USB D- signal for billboard device
21	VDD10	P	-	1.0V power input
22	TEST_EN	I	PD	1: Test mode. 0: Normal mode.
23	GPIO5	I/O		General input output
24	DP_HPD	I/O		GPIO6 as DisplayPort HPD
25	GPIO7	I/O	-	General input output
26	NC	--		Reserved
27	NC	--		Reserved
28	NC	--		Reserved
29	NC	--		Reserved
30	VDD33_OUT	P	-	3.3V power output
31	VDD33_OUT	P	-	3.3V power output
32	VDD5_IN	P	-	5V power input
33	VDD5_IN	P	-	5V power input
34	NC	--		Reserved
35	NC	--		Reserved
36	NC	--		Reserved
37	AVDD33	P	-	3.3V power
38	HDMI_HPD	I/O	PD	HDMI Hot Plug detect input (GPIO11)

Pin #	Description	Type	PU/PD	Note
39	HDMI_SDA	I/O	PU	HDMI DDC data (GPIO10)
40	HDMI_SCL	I/O	PU	HDMI DDC clock (GPIO9)
41	HDMI_CEC	I/O		HDMI CEC Pin (GPIO8)
42	VDD10	P		1.0V power input
43	AVDD10_TX	P	-	1.0V power input
44	HDMI_CKN	I	-	HDMI clock differential pair N output
45	HDMI_CKP	I	-	HDMI clock differential pair P output
46	HDMI_D0N	I	-	HDMI data channel 0 different pair N output
47	HDMI_D0P	I	-	HDMI data channel 0 different pair P output
48	HDMI_D1P	I	-	HDMI data channel 1 different pair N output
49	HDMI_D1P	I	-	HDMI data channel 1 different pair P output
50	HDMI_D2N	I	-	HDMI data channel 2 different pair N output
51	HDMI_D2P	I	-	HDMI data channel 2 different pair P output
52	AVDD10_TX	P		1.0V power input
53	AVDD10_PLL	P	-	1.0V power input
54	AVDD33_PLL	P	-	3.3V power input
55	AVDD33_IO	P		3.3V power input
56	CFG_SCL	I/O	-	I2C slave CLOCK pin for debug
57	CFG_SDA	I/O	-	I2C slave DATA pin for debug
58	GPIO1	I/O		General input output
59	GPIO2	I/O		General input output
60	GPIO3	I/O		General input output
61	GPIO4	I/O		General input output
62	VDD10	P	-	1.0V power input
63	GND	P		GND
64	NC	--		Reserved
65	NC	--		Reserved
66	NC	--		Reserved
67	NC	--		Reserved
68	NC	--		Reserved

4 Electrical Specifications

4.1 Absolute Maximum Conditions

Permanent damage may occur if absolute maximum conditions are violated. Refer to Section 4.2 for functional operating limits.

Table 4-1 Absolute Maximum Conditions

Symbol	Parameter	Min	Typ	Max	Unit
VDD5_IN	5V Power Input	-0.3	—	6	V
VDD33	3.3V power input	-0.3	—	3.96	V
VDD10	1.0V power input	-0.3	—	1.2	V
T _A	Junction temperature	-40	—	125	°C
Q _{JA}	Storage temperature1	-65	—	150	°C
ESD _{HBM}	ESD protection (Human body model)	—	—	±4	kV
ESD _{CDM}	ESD protection (Charge Device model)	—	—	700	V

1. Max 260°C can be guaranteed with max 8 sec soldering time.

4.2 Operating Conditions

Table 4-2 Normal Operating Conditions

Symbol	Parameter	Min	Typ	Max	Unit
VDD33_OUT	3.3V LDO output	3.0	3.3	3.6	V
VDD5_IN	5V Power Input	4.75	5	5.25	V
VDD33	3.3V power input	3.0	3.3	3.6	V
VDD10	1.0V power input	0.95	1.0	1.1	V
T _A	Ambient temperature	0	—	70	°C
Q _{JA}	Package thermal resistance, no air flow	—	39.3	—	°C/W

4.3 Electrical Specification

Table 4-3 DC Electrical Specification

Symbol	Parameter	For 3.3V I/O		
		Min	Typ	Max
V _{il} (V)	Input low voltage	—	—	0.8
V _{ih} (V)	Input high Voltage	2.0	—	—
V _{ol} (V)	Output low voltage	0	—	0.4
V _{oh} (V)	Output high voltage ¹	2.4	—	—

Symbol	Parameter	For 3.3V I/O		
		Min	Typ	Max
I _{in} (uA)	Input leakage current	-10	—	+10
I _{hiz} (uA)	Output tri-state leakage current	-10	—	+10

5 Package Specification

Figure 5-1 CS5263AN Package Outline (QFN68 Leads 8x8mm2)




Table 5-1 Package Dimension

Symbol	Dimension in mm			Dimension in inch		
	Min	Normal	Max	Min	Normal	Max
A	7.9	8.0	8.1	0.311	0.314	0.319
B	5.50	5.70	5.90	0.217	0.224	0.232
C	5.50	5.70	5.90	0.217	0.224	0.232
D		0.40 BSC			0.016 BSC	
E	0.15	0.20	0.25	0.006	0.008	0.010
F	0.30	0.40	0.50	0.012	0.016	0.020
G	0.80	0.85	0.90	0.031	0.033	0.035
H	0	0.02	0.05	0	0.001	0.002
I		0.20 REF			0.008 REF	

6 Ordering Information

The CS5263AN can be ordered using the part numbers in Table 6-1. Please consult sales for further details.

Table 6-1 CS5263AN Ordering Information

Part No.	Description	Temperature Range	Packing Type
CS5263AN	68 Pin (QFN) Lead-free package	Commercial : 0 to 70 degree C	Sample

7 Revision History

Table 7-1 Document Revision History

Revision	Date	Changes
Draft V0.1	Oct. 2020	First draft version.
Draft V0.2	Dec. 2020	Update Pin Assignments.
Draft V0.3	Mar. 2021	First release.
Release V1.0	June. 2021	Update Package Specification.
Release V1.1	June. 2021	Update Some Pin description.