



Silicon N-Channel Power MOSFET



CS540 AR

General Description:

CS540 AR, the silicon N-channel Enhanced VDMOSFETs, is obtained by the self-aligned planar Technology which reduce the conduction loss, improve switching performance and enhance the avalanche energy. The transistor can be used in various power switching circuit for system miniaturization and higher efficiency. The package form is TO-262, which accords with the RoHS standard.

Features:

- | Fast Switching
- | Low ON Resistance($R_{DS(on)} < 44 \text{ m}\Omega$)
- | Low Gate Charge (Typical Data: 37 nC)
- | Low Reverse transfer capacitances(Typical: 10 pF)
- | 100% Single Pulse avalanche energy Test



Applications:

Automotive、DC Motor Control and Class D Amplifier.

Absolute (T_c = 25°C unless otherwise specified):

Symbol	Parameter	Rating	Units
V _{DSS}	Drain-to-Source Voltage	100	V
I _D	Continuous Drain Current	33	A
	Continuous Drain Current T _c = 100 °C	27	A
I _{DM} ^{a1}	Pulsed Drain Current	132	A
V _{GS}	Gate-to-Source Voltage	±20	V
E _{AS} ^{a2}	Single Pulse Avalanche Energy	750	mJ
E _{AR} ^{a1}	Avalanche Energy ,Repetitive	60	mJ
I _{AR} ^{a1}	Avalanche Current	3.5	A
dv/dt ^{a3}	Peak Diode Recovery dv/dt	5.0	V/ns
P _D	Power Dissipation	150	W
	Derating Factor above 25°C	1.0	W/°C
T _J , T _{stg}	Operating Junction and Storage Temperature Range	175, -55 to 175	°C
T _L	Maximum Temperature for Soldering	300	°C

V _{DSS}	100	V
I _D	33	A
P _D (T _c =25 °C)	150	W
R _{DS(ON)Typ}	30	mΩ



**Electrical Characteristics** ($T_c = 25^\circ\text{C}$ unless otherwise specified):

OFF Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
V_{DSS}	Drain to Source Breakdown Voltage	$V_{GS}=0V, I_D=250\mu\text{A}$	100	--	--	V
$\Delta BV_{DSS}/\Delta T_J$	Bvdss Temperature Coefficient	$I_D=250\mu\text{A}, \text{Reference } 25^\circ\text{C}$	--	0.11	--	$^\circ\text{C}$
I_{DSS}	Drain to Source Leakage Current	$V_{DS} = 100\text{V}, V_{GS} = 0\text{V}, T_a = 25^\circ\text{C}$	--	--	1	μA
		$V_{DS} = 80\text{V}, V_{GS} = 0\text{V}, T_a = 125^\circ\text{C}$	--	--	100	
$I_{GSS(F)}$	Gate to Source Forward Leakage	$V_{GS} = +20\text{V}$	--	--	100	nA
$I_{GSS(R)}$	Gate to Source Reverse Leakage	$V_{GS} = -20\text{V}$	--	--	-100	nA

ON Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$R_{DS(ON)}$	Drain-to-Source On-Resistance	$V_{GS}=10\text{V}, I_D=17\text{A}$	--	30	44	$\text{m}\Omega$
$V_{GS(\text{TH})}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	2.0		4.0	V
Pulse width $t_p \leq 380\mu\text{s}, \delta \leq 2\%$						

Dynamic Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
g_{fs}	Forward Transconductance	$V_{DS}=15\text{V}, I_D = 17\text{A}$	--	80	--	S
C_{iss}	Input Capacitance	$V_{GS} = 0\text{V} V_{DS} = 25\text{V}$ $f = 1.0\text{MHz}$	--	2700	--	pF
C_{oss}	Output Capacitance		--	300	--	
C_{rss}	Reverse Transfer Capacitance		--	10	--	

Resistive Switching Characteristics						
Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
$t_{d(\text{ON})}$	Turn-on Delay Time	$I_D = 17\text{A} V_{DD} = 50\text{V}$ $V_{GS} = 10\text{V} R_G = 9.1\Omega$	--	18	--	ns
t_r	Rise Time		--	20	--	
$t_{d(\text{OFF})}$	Turn-Off Delay Time		--	53	--	
t_f	Fall Time		--	7	--	
Q_g	Total Gate Charge	$I_D = 17\text{A} V_{DD} = 50\text{V}$ $V_{GS} = 10\text{V}$	--	37	--	nC
Q_{gs}	Gate to Source Charge		--	11	--	
Q_{gd}	Gate to Drain ("Miller") Charge		--	8	--	

**Source-Drain Diode Characteristics**

Symbol	Parameter	Test Conditions	Rating			Units
			Min.	Typ.	Max.	
I _S	Continuous Source Current (Body Diode)		--	--	33	A
I _{SM}	Maximum Pulsed Current (Body Diode)		--	--	132	A
V _{SD}	Diode Forward Voltage	I _S =33A, V _{GS} =0V	--	--	1.5	V
t _{rr}	Reverse Recovery Time	I _S =33A, T _j = 25°C dI _F /dt=100A/us, V _{GS} =0V	--	150		ns
Q _r r	Reverse Recovery Charge		--	555		nC
Pulse width tp≤380μs, δ≤2%						

Symbol	Parameter	Typ.	Units
R _{θJC}	Junction-to-Case	1.0	°C/W
R _{θJA}	Junction-to-Ambient	62	°C/W

^{a1}: Repetitive rating; pulse width limited by maximum junction temperature

^{a2}: L=10.0mH, I_D=12.2A, Start T_j=25°C

^{a3}: I_{SD}=100A,di/dt ≤100A/us,V_{DD}≤BV_{DS}, Start T_j=25°C

Characteristics Curve:




Figure 2. Maximum Power Dissipation vs Case Temperature




Figure 3. Maximum Continuous Drain Current vs Case Temperature




Figure 4. Typical Output Characteristics




Figure 5. Typical Drain-to-Source ON Resistance vs Gate Voltage and Drain Current






Figure 6. Maximum Peak Current Capability




Figure 7. Typical Transfer Characteristics




Figure 8. Undamped Inductive Switching Capability




Figure 9. Typical Drain-to-Source ON Resistance vs Drain Current




Figure 10. Typical Drain-to-Source ON Resistance vs Junction Temperature




Figure 11. Typical Breakdown Voltage vs Junction Temperature




Figure 12. Typical Threshold Voltage vs Junction Temperature




Figure 13. Maximum Forward Bias Safe Operating Area




Figure 14. Typical Capacitance vs Drain-to-Source Voltage




Figure 15. Typical Gate Charge vs Gate-to-Source Voltage





Figure 16. Typical Body Diode Transfer Characteristics



Test Circuit and Waveform




Figure 17. Gate Charge Test Circuit




Figure 18. Gate Charge Waveform



Figure 19. Resistive Switching Test Circuit




Figure 20. Resistive Switching Waveforms




Figure 21. Diode Reverse Recovery Test Circuit




Figure 22. Diode Reverse Recovery Waveform



Figure 23. Unclamped Inductive Switching Test Circuit





Figure 24. Unclamped Inductive Switching Waveforms

Package Information:

Items	Values(mm)	
	MIN	MAX
A	9.80	10.40
B	8.90	9.50
C	4.30	4.80
D	1.15	1.40
E	0.70	0.91
F	0.28	0.55
G	1.07	1.47
H	0.40	0.60
I	2.50	2.90
K	0.90	1.40
L	12.7	14.7
N	2.35	2.70

TO-262 Package

**The name and content of poisonous and harmful material in products**

Part's Name	Hazardous Substance					
	Pb	Hg	Cd	Cr(VI)	PBB	PBDE
Limit	≤0.1%	≤0.1%	≤0.01%	≤0.1%	≤0.1%	≤0.1%
Lead Frame	○	○	○	○	○	○
Molding Compound	○	○	○	○	○	○
Chip	○	○	○	○	○	○
Wire Bonding	○	○	○	○	○	○
Solder	×	○	○	○	○	○
Note	<p>○: means the hazardous material is under the criterion of SJ/T11363-2006.</p> <p>×: means the hazardous material exceeds the criterion of SJ/T11363-2006.</p> <p>The plumbum element of solder exist in products presently, but within the allowed range of Eurogroup's RoHS.</p>					

Warnings

1. Exceeding the maximum ratings of the device in performance may cause damage to the device, even the permanent failure, which may affect the dependability of the machine. It is suggested to be used under 80 percent of the maximum ratings of the device.
2. When installing the heatsink, please pay attention to the torsional moment and the smoothness of the heatsink.
3. VDMOSFETs is the device which is sensitive to the static electricity, it is necessary to protect the device from being damaged by the static electricity when using it.
4. This publication is made by Huajing Microelectronics and subject to regular change without notice.

WUXI CHINA RESOURCES HUAJING MICROELECTRONICS CO., LTD.

Add: No.14 Liangxi RD. Wuxi, Jiangsu, China Mail:214061 <http://www.crhj.com.cn>
Tel: +86 0510-85807228 Fax: +86- 0510-85800864

Marketing Part: Post: 214061 Tel: +86 0510-81805277/81805336
Fax: +86 0510-85800360/85803016
E-mail: sales@hj.crmicro.com

Application and Service: Post: 214061 Tel / Fax: +86- 0510-81805243/81805110