





| Thyristor Typ/type | V _{DRM} V _{RRM} V | I _{TRMS} A | T _{AV1} /T _C A/°C | I _{TAVM} T _c = 85°C A | I _{TSM} (T _{VJM}) | | P _t (10 ms) | | V _T V | I _T A | I _{DRM} I _{RRM} mA | (dv/dt) _c V/μs | (di/dt) _c A/μs | I _{GT} mA | V _{GT} V | I _H mA |
|--|---|------------------------|--|---|---|-------|---------------------------|------------------|---------------------|---------------------|--|------------------------------|------------------------------|---------------------------------|----------------------|----------------------|
| | | | | | 8,3 ms | 10 ms | T _{VJ} :45°C | T _{VJM} | | | | | | | | |
| | | | | | A | A | A²s | A²s | | | | | | | | |
| CS 0,8-02 do 2 CS 0,8-04 do 2 CS 0,8-06 do 2 } bzw. CS 0,8-07 do 2 } resp. CS 0,8-08 do 2 } 7 | 200 400 600 700 800 | 8 | 0,8 T _A = 45°C | 0,8 T _A = 45°C | 50 | 45 | 12 | 10 | 1,65 | 10 | 1 | 20 | 150 | 10 Vers. 2 4 Vers. 7 | 2 | 20 |
| CS 3-02 do 2 CS 3-04 do 2 CS 3-06 do 2 } bzw. CS 3-07 do 2 } resp. CS 3-08 do 2 } 7 | 200 400 600 700 800 | 8 | 5/85 | 5 | 50 | 45 | 12 | 10 | 1,65 | 10 | 1 | 20 | 150 | 10 Vers. 2 4 Vers. 7 | 2 | 20 |
| CS 5-02 go 2 CS 5-04 go 2 CS 5-06 go 2 } bzw. CS 5-08 lo 2 } resp. CS 5-10 lo 2 } 3 CS 5-12 lo 2 } | 200 400 600 800 1000 1200 | 25 | 16/59 | 11,4 | 155 | 140 | 160 | 100 | 1,9 | 27 | 3 | 200 | 150 | 30 | 2,5 | 80 |
| CS 6-04 do 1 CS 6-06 do 1 CS 6-07 do 1 } bzw. CS 6-08 do 1 } resp. 7 | 400 600 700 800 | 10 | 6/95 | 6 | 88 | 80 | 40 | 32 | 1,45 | 15 | 1 | 20 | 150 | 15 Vers. 1 6,5 Vers. 7 | 2 | 25 |
| CS 8-02 go 2 CS 8-04 go 2 CS 8-06 go 2 } bzw. CS 8-08 lo 2 } resp. CS 8-10 lo 2 } 3 CS 8-12 lo 2 } | 200 400 600 800 1000 1200 | 25 | 16/85 | 16 | 220 | 200 | 310 | 200 | 1,6 | 33 | 3 | 200 | 150 | 30 | 2,5 | 80 |
| CS 10-02 go 2 CS 10-04 go 2 CS 10-06 go 2 } bzw. CS 10-07 go 2 } resp. CS 10-08 go 2 } 7 CS 10-10 go 2 } | 200 400 600 700 800 1000 | 22 | 14/60 | 10 | 165 | 150 | 145 | 112 | 1,81 | 30 | 1 | 200 | 150 | 40 Vers. 2 Vers. 7 | 1 | 100 |
| ▲ CS 13-04 go 4 ▲ CS 13-06 go 4 ▲ CS 13-08 go 4 ▲ CS 13-10 go 4 | 400 600 800 1000 | 35 | 22/65 | 17 | 330 | 300 | 610 | 450 | 2,0 | 50 | 10 | 200 | 150 | 120 | 3 | 150 |
| CS 15-02 go 2 CS 15-04 go 2 CS 15-06 go 2 CS 15-07 go 2 CS 15-08 go 2 CS 15-10 go 2 | 200 400 600 700 800 1000 | 25 | 15/80 | 13,5 | 265 | 250 | 390 | 310 | 1,81 | 45 | 1 | 200 | 150 | 40 | 1,0 | 100 |
| CS 16-04 go 2 CS 16-06 go 2 CS 16-08 lo 2 } bzw. CS 16-10 lo 2 } resp. CS 16-12 lo 2 } 3 CS 16-14 lo 2 } CS 16-16 lo 2 } | 400 600 800 1000 1200 1400 1600 | 30 | 19/95 | 19 | 265 | 250 | 610 | 310 | 1,8 | 60 | 10 | 200 | 150 | 50 | 2,5 | 100 |
| CS 23-04 go 2 CS 23-06 go 2 CS 23-08 lo 2 } bzw. CS 23-10 lo 2 } resp. CS 23-12 lo 2 } 3 CS 23-14 lo 2 } CS 23-16 lo 2 } | 400 600 800 1000 1200 1400 1600 | 50 | 32/69 | 25 | 430 | 400 | 1010 | 800 | 1,8 | 80 | 10 | 200 | 150 | 50 | 2,5 | 100 |

▲ - Neuer Typ / New type / Nouveau type

Ⓞ bei Montage mit Befestigungsschraube/for screw mounting/pour montage à vis



CS 0,8

CS 3
CS 6

CS 5...2
CS 8...2

DataSheet4U.com

CS 5...3
CS 8...3


Thyristors à commutation par le réseau

| Masse mass | M _d Nm | t _q μs | V _{TO} V | r _T mΩ | T _{VJM} °C | R _{thJC} K/W | R _{thCK} k/W | Fig. Nr. | Kühlkörper Heatsink Radiateur Typ/type | Kühlart Cooling mode Refrroi- dissement | R _{thKA} (R _{thJA}) K/W | I _{dAVM} (A) | | | | | I _{RMS} |
|-----------------------------|----------------------|----------------------|----------------------|----------------------|------------------------|--------------------------|--------------------------|---------------------------|---|---|--|----------------------------------|---------------------|----------------------|----------------------|-----------------------|------------------|
| | | | | | | | | | | | | Schaltung · Connection · Montage | | | | | |
| | | | | | | | | | | | | M1 | M2/B2 | M3/B6 | M6 | W1 | |
| 2 | - | 60 | 1 | 70 | 110 | - | - | 1 | Leiterplatte Print board Circuit imprimé (T _A = 45°C) | | (70) | 0,8 | 1,6 | 2,3 | 3,8 | 1,8 | |
| 2,3 | 0,7 ⊕ | 40 | 1 | 70 | 125 | 2,5 | 0,7 | 2 | Leiterplatte Print board Circuit imprimé (T _A = 45°C) | | (40) | 1,6 | 3,2 | 4,5 | 7,6 | 3,6 | |
| 6 | 2,5 | 60 | 1 | 33 | 125 | 1,8 | 1 | Version 2 = 3 3 = 4 | K 0,5 K 2,5 K 4,5 K 11 | S S S S | 15 4,5 2,8 1,05 | 3,5 7 8,5 11 | 7 14 17 22 | 10 20 24 31 | 17 33 40 52 | 7,8 16 19 25 | |
| 2,3 | 0,7 ⊕ | 40 | 1 | 30 | 110 | 1,6 | 0,6 | 2 | Leiterplatte Print board Circuit imprimé (T _A = 45°C) | | (40) | 1,6 | 3,2 | 4,5 | 7,6 | 3,5 | |
| 6 | 2,5 | 60 | 1 | 18 | 125 | 1,5 | 1 | Version 2 = 3 3 = 4 | K 2,5 K 4,5 K 11 | S S S | 4,5 2,8 1,05 | 8,5 10,5 14 | 17 21 28 | 24 30 40 | 40 50 67 | 19 23 31 | |
| 2,3 | 0,7 ⊕ | 80 | 1 | 27 | 125 | 2,4 | 0,6 | 5 | Leiterplatte Print board Circuit imprimé Al 35 x 35 x 2 Al 50 x 50 x 2 (T _A = 45°C) | | (40) (22) (13) | 1,8 3,0 4,7 | 3,6 6,0 9,4 | 5,1 8,6 13 | 8,5 14 22 | 4,0 6,7 10,5 | |
| 12 | 3,0 | 50 | 1,2 | 16 | 125 | 1,3 | 0,6 | 6 | K 2,5 K 4,5 | S S | 4,5 2,8 | 8,2 10,5 | 16 21 | 24 30 | 40 50 | 18 23 | |
| 2,3 | 0,7 ⊕ | 80 | 1 | 18 | 125 | 1,6 | 0,6 | 5 | Leiterplatte Print board Circuit imprimé Al 35 x 35 x 2 Al 50 x 50 x 2 (T _A = 45°C) | | (40) (22) (13) | 1,9 3,2 5,0 | 3,7 6,4 10 | 5,3 9,0 14,2 | 8,8 15 24 | 4,2 7 11 | |
| Version 2 = 12 3 = 12 | 3,0 | 130 | 1 | 12 | 125 | 1 | 0,6 | Version 2 = 6 3 = 7 | K 2,5 K 4,5 | S S | 4,5 2,8 | 10 13 | 20 26 | 29 37 | 48 62 | 22 29 | |
| Version 2 = 12 3 = 12 | 3,0 | 130 | 1 | 10 | 125 | 1 | 0,6 | Version 2 = 6 3 = 7 | K 2,5 K 4,5 K 11 | S S S | 4,5 2,8 1,05 | 11 13,5 20 | 22 27 40 | 31 38 57 | 52 64 95 | 24 30 44 | |

A = Anode, K = Cathode, G = Gate, HK = Hilfskathode, auxiliary cathode, cathode auxiliaire


Maße in mm / Dimensions in mm / Dimensions en mm
(1 mm = 0,0394")

5 TO-220 AB




CS 10
CS 15

6 ~TO-48



CS 13...4
CS 16...2
CS 23...2

7 ~TO-48



CS 16...3
CS 23...3