



Phase Control Thyristors

$V_{RRM} = 800-1200 \text{ V}$
 $I_{T(RMS)} = 25 \text{ A}$
 $I_{T(AV)M} = 16 \text{ A}$

V_{RSM} V_{DSM} V	V_{RRM} V_{DRM} V	Type
900	800	CS 8-08io2
1300	1200	CS 8-12io2



TO-64



1 = Anode, 2 = Cathode, 3 = Gate

Symbol	Test Conditions	Maximum Ratings	
$I_{T(RMS)}$	$T_{VJ} = T_{VJM}$	25	A
$I_{T(AV)M}$	$T_{case} = 85^\circ\text{C}$; 180° sine	16	A
I_{TSM}	$T_{VJ} = 45^\circ\text{C}$; $V_R = 0$	250	A
	$t = 10 \text{ ms}$ (50 Hz), sine $t = 8.3 \text{ ms}$ (60 Hz), sine	270	A
	$T_{VJ} = T_{VJM}$ $V_R = 0$	200	A
	$t = 10 \text{ ms}$ (50 Hz), sine $t = 8.3 \text{ ms}$ (60 Hz), sine	220	A
I^2t	$T_{VJ} = 45^\circ\text{C}$ $V_R = 0$	310	A^2s
		306	A^2s
	$T_{VJ} = T_{VJM}$ $V_R = 0$	200	A^2s
		200	A^2s
$(di/dt)_{cr}$	$T_{VJ} = T_{VJM}$ $f = 50 \text{ Hz}$, $t_p = 200 \mu\text{s}$ $V_D = 2/3 V_{DRM}$ $I_G = 0.2 \text{ A}$ $di_G/dt = 0.2 \text{ A}/\mu\text{s}$	150	$\text{A}/\mu\text{s}$
	repetitive, $I_T = 48 \text{ A}$	500	$\text{A}/\mu\text{s}$
$(dv/dt)_{cr}$	$T_{VJ} = T_{VJM}$; $R_{GK} = \infty$; method 1 (linear voltage rise)	1000	$\text{V}/\mu\text{s}$
P_{GM}	$T_{VJ} = T_{VJM}$ $I_T = I_{T(AV)M}$	10	W
	$t_p = 30 \mu\text{s}$	5	W
$P_{G(AV)}$	$t_p = 300 \mu\text{s}$	0.5	W
V_{RGM}		10	V
T_{VJ}		-40...+125	$^\circ\text{C}$
T_{VJM}		125	$^\circ\text{C}$
T_{stg}		-40...+125	$^\circ\text{C}$
M_d	Mounting torque	2.5 22	Nm lb.in.
Weight		6	g

Features


- Thyristor for line frequencies
- International standard package JEDEC TO-64
- Planar glassivated chip
- Long-term stability of blocking currents and voltages

Applications

- Motor control
- Power converter
- AC power controller

Advantages

- Space and weight savings
- Simple mounting
- Improved temperature and power cycling

Dimensions in mm (1 mm = 0.0394")

Data according to IEC 60747
 IXYS reserves the right to change limits, test conditions and dimensions

Symbol	Test Conditions	Characteristic Values			
I_R, I_D	$T_{VJ} = T_{VJM}$; $V_R = V_{RRM}$; $V_D = V_{DRM}$	\leq	3	mA	
V_T	$I_T = 33 \text{ A}$; $T_{VJ} = 25^\circ\text{C}$	\leq	1.6	V	
V_{TO}	For power-loss calculations only ($T_{VJ} = 125^\circ\text{C}$)	1.0		V	
r_T		18		$\text{m}\Omega$	
V_{GT}	$V_D = 6 \text{ V}$; $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = -40^\circ\text{C}$	\leq	2.5	V	
I_{GT}	$V_D = 6 \text{ V}$; $T_{VJ} = 25^\circ\text{C}$ $T_{VJ} = -40^\circ\text{C}$	\leq	30	mA	
\leq		\leq	50	mA	
V_{GD}	$T_{VJ} = T_{VJM}$;	$V_D = 2/3 V_{DRM}$	\leq	0.2	V
I_{GD}			\leq	1	mA
I_L	$T_{VJ} = 25^\circ\text{C}$; $t_p = 10 \mu\text{s}$ $I_G = 0.09 \text{ A}$; $di_G/dt = 0.09 \text{ A}/\mu\text{s}$	\leq	100	mA	
I_H	$T_{VJ} = 25^\circ\text{C}$; $V_D = 6 \text{ V}$; $R_{GK} = \infty$	\leq	80	mA	
t_{gd}	$T_{VJ} = 25^\circ\text{C}$; $V_D = 1/2 V_{DRM}$ $I_G = 0.09 \text{ A}$; $di_G/dt = 0.09 \text{ A}/\mu\text{s}$	\leq	2	μs	
t_q	$T_{VJ} = T_{VJM}$; $I_T = 16 \text{ A}$, $t_p = 300 \mu\text{s}$; $di/dt = -20 \text{ A}/\mu\text{s}$ $V_R = 100 \text{ V}$; $dv/dt = 20 \text{ V}/\mu\text{s}$; $V_D = 2/3 V_{DRM}$	typ.	60	μs	
R_{thJC}	DC current		1.5	K/W	
R_{thJH}	DC current		2.5	K/W	
d_s	Creepage distance on surface	1.55		mm	
d_A	Strike distance through air	1.55		mm	
a	Max. acceleration, 50 Hz	50		m/s^2	

Accessories:

Nut M5 DIN 439/SW8

Lock washer A5 DIN 128




Fig. 1 Gate voltage and gate current
Triggering:
A = no; B = possible; C = safe



Fig. 2 Gate controlled delay time t_{gd} 

Fig. 3 On-state characteristics




Fig. 4 Surge overload current
 I_{TSM} : crest value, t : duration




Fig. 5 I^2t versus time (1-10 ms)




Fig. 6 Maximum forward current at
case temperature 180° sine




Fig. 7 Power dissipation versus on-state current and ambient temperature




Fig. 8 Transient thermal impedance junction to heatsink

R_{thJH} for various conduction angles d :

d	R_{thJH} (K/W)
DC	2.5
180°	2.79
120°	2.95
60°	3.17
30°	3.32

Constants for Z_{thJH} calculation:

i	R_{thi} (K/W)	t_i (s)
1	0.252	0.005
2	0.333	0.0225
3	0.5	0.145
4	0.833	0.43
5	0.416	2.75
6	0.166	23