

■ Features

- Low forward voltage drop.
- Excellent high temperature stability.
- Fast switching capability.
- Suffix "G" indicates Halogen-free part, ex. CSTF30L40CTG.
- Lead-free parts meet environmental standards of MIL-STD-19500 /228

■ Mechanical data


- Epoxy : UL94-V0 rated flame retardant.
- Case : JEDEC ITO-220AB molded plastic body.
- Terminals : Solder plated, solderable per MIL-STD-750, Method 2026.
- Polarity: As marked.
- Mounting Position : Any.
- Weight : Approximated 2.25 gram.

■ Maximum ratings and electrical characteristics


Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

■ Outline

ITO-220AB




| symbol | Dimensions in inches(millimeters) | |
|--------|-----------------------------------|--------------|
| | Min | Max |
| A | 0.390(9.9) | 0.408(10.36) |
| B | 0.268(6.8) | 0.283(7.2) |
| C | 0.583(14.8) | 0.598(15.2) |
| D | 0.512(13.0) | 0.543(13.8) |
| E | 0.102(2.6) | 0.150(3.8) |
| F | 0.101(2.55) | 0.112(2.85) |
| G | 0.043(1.1) | 0.053(1.35) |
| H | 0.043(1.1) | 0.053(1.35) |
| I | 0.020(0.5) | 0.028(0.7) |
| J | 0.098(2.49) | 0.102(2.59) |
| K | 0.169(4.3) | 0.185(4.7) |
| L | 0.112(2.85) | 0.128(3.25) |
| M | 0.098(2.5) | 0.114(2.9) |
| N | 0.020(0.5) | 0.028(0.7) |
| ØP | 0.130(3.3) | 0.134(3.5) |



Alternate

| symbol | Dimensions in inches(millimeters) | |
|--------|-----------------------------------|--------------|
| | Min | Max |
| A | 0.383(9.72) | 0.404(10.27) |
| B | 0.248(6.3) | 0.272(6.9) |
| C | 0.571(14.5) | 0.610(15.5) |
| D | 0.516(13.1) | 0.547(13.9) |
| E | - | 0.161(4.1) |
| F | 0.094(2.4) | 0.126(3.2) |
| G | 0.039(1.0) | 0.051(1.3) |
| H | 0.039(1.0) | 0.051(1.3) |
| I | 0.020(0.5) | 0.035(0.9) |
| J | 0.095(2.41) | 0.105(2.67) |
| K | 0.169(4.3) | 0.189(4.8) |
| L | 0.055(1.4) | 0.122(3.1) |
| M | 0.091(2.3) | 0.117(2.96) |
| N | 0.014(0.35) | 0.031(0.8) |
| ØP | 0.122(3.1) | 0.142(3.6) |



| Parameter | Conditions | Symbol | CSTF30L40CT | UNIT |
|---|--|----------------|-------------|------|
| Marking code | | | CSTF30L40CT | |
| Peak repetitive reverse voltage | | V_{RRM} | | |
| Working peak reverse voltage | | V_{RWM} | 40 | V |
| DC blocking voltage | | V_{RM} | | |
| Forward rectified current (total device) | | I_O | 30 | A |
| Forward surge current (per diode) | 8.3ms single half sine-wave superimposed on rate load (JEDEC method) | I_{FSM} | 250 | A |
| Peak repetitive reverse surge current (per diode) | 2us - 1kHz | I_{RRM} | 3 | A |
| Thermal resistance(1) (per diode) | Junction to case | R_{BJC} | 2 | °C/W |
| Operating and Storage temperature | | T_J, T_{STG} | -65 ~ +150 | °C |

| Parameter | Conditions | Symbol | MIN. | TYP. | MAX. | UNIT |
|----------------------------------|------------------------------------|--------|------|------|------|------|
| Forward voltage drop (per diode) | $I_F = 15A, T_J = 25^\circ C$ | V_F | | 450 | 500 | mV |
| | $I_F = 15A, T_J = 125^\circ C$ | | | 420 | 450 | |
| | $I_F = 30A, T_J = 25^\circ C$ | | | 600 | | |
| Reverse current (per diode) | $V_R = V_{RRM}, T_J = 25^\circ C$ | I_R | | 0.06 | 0.5 | mA |
| | $V_R = V_{RRM}, T_J = 125^\circ C$ | | | | 100 | |

Note : 1. Thermal resistance from junction to case per leg, with heatsink size(1.35" x 0.95" x 0.18") Al-plate.

Rating and characteristic curves

Fig. 1 - Forward Current Derating Curve (per diode)




Fig. 2 - Instantaneous Forward Characteristics (per diode)





Fig. 3 - Reverse Characteristics (per diode)



- CITC reserves the right to make changes to this document and its products and specifications at any time without notice.
- Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- CITC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does CITC assume any liability for application assistance or customer product design.
- CITC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.
- No license is granted by implication or otherwise under any intellectual property rights of CITC.
- CITC products are not authorized for use as critical components in life support devices or systems without express written approval of CITC.