



- UL, cUL Recognized and CSA Certified
- As per ANSI/IEEE C57.13 OR IEC 60044 OR relevant standard

INSULATION LEVEL

600 V, BIL 10kV full wave

FREQUENCY

50-400 Hz

THERMAL RATING

50:5-4000:5 - 1.33 @ 30 deg. C ambient

OUTER ENCAPSULATION

Plastic Cased

SECONDARY TERMINALS

Brass screw # 10-32 with one flat washer and lock washer

APPROX. WEIGHT

26 lbs.

CUSTOM OPTIONS (CONTACT US)

- Different Ratios
- IEC Ratios/Accuracies
- Non-standard thermal rating
- Different secondary termination
- Special mounting needs

TABLES

CATALOG NUMBER	CURRENT RATIO	RELAY CLASS (@ 60 HZ)	ANSI METERING CLASS @ 60 HZ					SECONDARY WINDING RESISTANCE (Ω @75° C)	CONTINUOUS THERMAL RATING FACTOR	
			B0.1	B0.2	B0.5	B0.9	B1.8		@ 30°C	@ 55°C
CT216-201	200:5	C20	0.6	0.6	1.2	2.4	-	0.064	2.0	2.0
CT216-251	250:5	C20	0.3	0.6	1.2	1.2	2.4	0.081	2.0	2.0
CT216-301	300:5	C20	0.3	0.6	0.6	1.2	1.2	0.097	2.0	2.0
CT216-401	400:5	C20	0.3	0.3	0.3	0.6	1.2	0.129	2.0	2.0
CT216-501	500:5	C50	0.3	0.3	0.3	0.3	0.6	1.161	2.0	2.0
CT216-601	600:5	C50	0.3	0.3	0.3	0.3	0.6	0.193	2.0	2.0
CT216-751	750:5	C100	0.3	0.3	0.3	0.3	0.3	1.242	2.0	2.0
CT216-801	800:5	C100	0.3	0.3	0.3	0.3	0.3	0.324	2.0	2.0
CT216-102	1000:5	C100	0.3	0.3	0.3	0.3	0.3	0.405	2.0	1.5
CT216-122	1200:5	C200	0.3	0.3	0.3	0.3	0.3	0.485	2.0	1.5
CT216-152	1500:5	C200	0.3	0.3	0.3	0.3	0.3	0.961	1.3	1.0
CT216-162	1600:5	C200	0.3	0.3	0.3	0.3	0.3	1.292	1.3	1.0
CT216-202	2000:5	C200	0.3	0.3	0.3	0.3	0.3	1.194	1.0	0.8
CT216-252	2500:5	C200	0.3	0.3	0.3	0.3	0.3	1.493	1.0	0.8
CT216-302	3000:5	C200	0.3	0.3	0.3	0.3	0.3	1.791	1.0	0.6
CT216-402	4000:5	C100	0.3	0.3	0.3	0.3	0.3	2.214	1.0	0.6
CT216-502	5000:5	C100	0.3	0.3	0.3	0.3	0.3	3.472	0.8	0.3

DIMENSIONS (ALL DIMENSIONS ARE IN INCHES [mm]):

