



Features

- High isolation 3750 V_{RMS}
- OFF-state output terminal voltage: 100 V
- Typical ON-state resistance: 0.6 Ω
- Operating Temperature range - 40 °C to 85 °C
- Creepage distance ≥ 5mm
- Distance Through Isolation > 0.4mm
- RoHS and REACH Compliance
- Halogen Free Compliance
- MSL class 1
- Regulatory Approvals
 - ✓ UL - UL1577 (E364000)
 - ✓ VDE - EN60747-5-5(VDE0884-5)
 - ✓ CQC – GB4943.1, GB8898 (14001105803)
 - ✓ IEC62368 (FI/41119)


Description

The CTR215-M4 (1-form-A) consists of two MOSFET and one photovoltaic chip optically coupled to an Infrared-emitting diode in 4-lead Mini-Flat package.


Applications

- Battery Management System (BMS)
- Security Systems
- Smart Meters
- Mechanical relay replacements
- General telecom switching
- Industrial controls
- Automatic measurement equipment

Package Outline



Schematic





Absolute Maximum Ratings $T_A = 25^{\circ}\text{C}$, unless otherwise specified

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

| Symbol | Parameters | Ratings | Units | Notes |
|-----------------------|---|------------|------------------|-------|
| V _{ISO} | Isolation voltage (AC, 1 minute, 40 ~ 60% R.H.) | 3750 | V _{rms} | |
| T _{OPR} | Operating temperature | -40 ~ +85 | °C | |
| T _{STG} | Storage temperature | -40 ~ +100 | °C | |
| T _{SOL} | Soldering temperature (For 10 seconds) | 260 | °C | |
| Emitter | | | | |
| I _F | Forward current | 50 | mA | |
| I _{F(TRANS)} | Peak transient current (≤1μs P.W,300pps) | 1 | A | |
| V _R | Reverse voltage | 5 | V | |
| P _C | Power dissipation | 85 | mW | |
| T _j | Junction Temperature | 115 | °C | |
| Detector | | | | |
| V _{OFF} | OFF-state output terminal Voltage | 100 | V | |
| I _{ON} | ON-state Current | 0.5 | A | |
| P _o | Output Power dissipation | 375 | mW | |
| T _j | Junction Temperature | 125 | °C | |
| T _{jA} | Junction to Ambient Temperature | 60 | °C | |

Recommended Operating Conditions

| Symbol | Parameters | Min | Typ | Max | Units |
|------------------|-----------------------|-----|-----|-----|-------|
| V _{DD} | Supply Voltage | - | - | 80 | V |
| I _{FT} | Trigger LED Current | 5 | 10 | 20 | mA |
| T _{OPR} | Operating temperature | -40 | - | 60 | °C |



Electrical Characteristics $T_A = 25^\circ\text{C}$, unless otherwise specified

Emitter Characteristics

| Symbol | Parameters | Test Conditions | Min | Typ | Max | Units | Notes |
|----------|-------------------|---------------------|-----|-----|-----|---------------|-------|
| V_F | Forward voltage | $I_F = 10\text{mA}$ | - | 1.4 | 1.6 | V | |
| I_R | Reverse Current | $V_R = 6\text{V}$ | - | - | 5 | μA | |
| C_{IN} | Input Capacitance | $f = 1\text{MHz}$ | - | 30 | - | pF | |

Detector Characteristics

| Symbol | Parameters | Test Conditions | Min | Typ | Max | Units | Notes |
|-----------|--------------------|---------------------------------------|-----|-----|-----|---------------|-------|
| I_{OFF} | OFF-state Current | $V_{OFF} = 100\text{V}$ | - | - | 1 | μA | |
| C_{OFF} | Output Capacitance | $V_O = 0\text{V}$, $f = 1\text{MHz}$ | - | 30 | - | pF | |

Transfer Characteristics







| Symbol | Parameters | Test Conditions | Min | Typ | Max | Units | Notes |
|----------|---------------------|--|-----|-----|-----|----------|-------|
| I_{FT} | Trigger LED Current | $I_{ON} = \text{Max}$ | - | 1.5 | 3 | mA | |
| R_{ON} | ON-state resistance | $I_{ON} = \text{Max}$, $I_F = 5\text{mA}$, $t < 1\text{s}$ | - | 0.6 | 1.5 | Ω | |

Switching Characteristics

| Symbol | Parameters | Test Conditions | Min | Typ | Max | Units | Notes |
|-----------|---------------|--|-----|-----|-----|-------|-------|
| T_{ON} | Turn-on Time | $R_L = 200\Omega$, $V_{DD} = 20\text{V}$, $I_F = 5\text{mA}$ | - | 1 | 3 | ms | |
| T_{OFF} | Turn-off Time | $f = 100\text{Hz}$ | - | 0.3 | 2 | ms | |



Typical Characteristic Curves $T_A = 25^\circ\text{C}$, unless otherwise specified





Typical Characteristic Curves $T_A = 25^\circ\text{C}$, unless otherwise specified




Figure 7




Figure 8

Test Circuit






Figure 9: Switching Time Test Circuits



Package Dimension *Dimensions in mm unless otherwise stated*



Marking Information



Note:

- CT : Denotes "CT Micro"
- R215 : Part Number
- X : Option (Blank, A or B)
- V : VDE Safety Mark Option (Blank or V)
- Y : One Digit Year Code
- WW : Two Digit Work Week
- K : Manufacturing Code



Ordering Information


CTR215(V)(Z)-M4

- CT = Denotes "CT Micro"
- R215 = Part Number
- V = VDE Safety Mark Option (Blank or V)
- Z = Tape and Reel Option (T1 or T2)
- M4 = MFP Package

| Option | Description | Quantity |
|--------|--|-----------------|
| T1 | Surface Mount Lead Forming – With Option 1 Tapping | 3000 Units/Reel |
| T2 | Surface Mount Lead Forming – With Option 2 Tapping | 3000 Units/Reel |

Reel Dimension *All dimensions are in mm, unless otherwise stated*

Option T1/T2






Carrier Tape Specifications *Dimensions in mm unless otherwise stated*


Option T1

Input Direction
→



Option T2

Input Direction
→





Solderability spec (Follow the JEDEC standard JESD22-B102)

Reflow Soldering: Immersed surface, other than the end of pin as cut-surface, must be covered by solder.

Solder-Bath: More than 95% of the electrode must be covered with solder.

Wave soldering (Follow the JEDEC standard JESD22-A111)


One time soldering is recommended within the condition of temperature.

Temperature: $260 \pm 0/-5^\circ\text{C}$.

Time: 10 sec.

Preheat temperature: 25 to 140°C .

Preheat time: 30 to 80 sec.



Iron soldering (Follow the standard MIL-STD 202G, Method 210F)


Allow single lead soldering in every single process.

One time soldering is recommended. Temperature: $350 \pm 10^\circ\text{C}$

Time: 5 sec max.



Reflow Profile (Follow the JEDEC standard J-STD-020)



| Profile Feature | Pb-Free Assembly Profile |
|-----------------------------------|--------------------------|
| Temperature Min. (Tsmmin) | 150°C |
| Temperature Max. (Tsmmax) | 200°C |
| Time (ts) from (Tsmmin to Tsmmax) | 60-120 seconds |
| Ramp-up Rate (tL to tp) | 3°C/second max. |
| Liquidous Temperature (TL) | 217°C |
| Time (tL) Maintained Above (TL) | 60 – 150 seconds |
| Peak Body Package Temperature | 260°C +0°C / -5°C |
| Time (tp) within 5°C of 260°C | 30 seconds |
| Ramp-down Rate (TP to TL) | 6°C/second max |
| Time 25°C to Peak Temperature | 8 minutes max. |



DISCLAIMER

DMC-Isolator® IS A TRADEMARK OF CT MICRO INTERNATIONAL CORPORATION AND/OR ITS SUBSIDIARIES. CT MICRO OWNS THE RIGHTS TO A NUMBER OF PATENTS, TRADEMARKS, COPYRIGHTS AND OTHER INTELLECTUAL PROPERTY.

CT MICRO RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. CT MICRO DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

DISCOLORATION MIGHT OCCUR ON THE PACKAGE SURFACE AFTER SOLDERING, REFLOW OR LONG TERM USE. THIS DOES NOT IMPACT THE PRODUCT PERFORMANCE NOR THE PRODUCT RELIABILITY.

CT MICRO ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT EXPRESS WRITTEN APPROVAL OF CT MICRO INTERNATIONAL CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instruction for use provided in the labelling, can be reasonably expected to result in significant injury to the user.*
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.*