

## 2SD2485


Silicon NPN Epitaxial

### Application

Low frequency power amplifier

### Features

- Low saturation voltage  
 $V_{CE(sat)} = 0.1 \text{ V typ. (at } I_C = 1 \text{ A, } I_B = 50 \text{ mA)}$
- Large current capacitance  
 $I_C = 2 \text{ A}$



**Table 1 Absolute Maximum Ratings** ( $T_a = 25^\circ\text{C}$ )

Item	Symbol	Ratings	Unit
Collector to base voltage	$V_{CBO}$	80	V
Collector to emitter voltage	$V_{CEO}$	80	V
Emitter to base voltage	$V_{EBO}$	6	V
Collector current	$I_C$	2	A
Collector peak current	$i_{c(peak)*}$	3	A
Collector power dissipation	$P_C$	0.9	W
Junction temperature	$T_j$	150	$^\circ\text{C}$
Storage temperature	$T_{stg}$	-55 to +150	$^\circ\text{C}$

Note: \*  $PW \leq 10 \text{ ms}$ , duty cycle  $\leq 20 \%$

---

**2SD2485**



---

**Table 2 Electrical Characteristics** (Ta = 25°C)


Item	Symbol	Min	Typ	Max	Unit	Test conditions
Collector to base breakdown voltage	$V_{(BR)CBO}$	80	—	—	V	$I_C = 10 \mu A,$ $I_E = 0$
Collector to emitter breakdown voltage	$V_{(BR)CEO}$	80	—	—	V	$I_C = 1 \text{ mA},$ $R_{BE} = \infty$
Emitter to base breakdown voltage	$V_{(BR)EBO}$	6	—	—	V	$I_E = 10 \mu A$ $I_C = 0$
Collector to base cutoff current	$I_{CBO}$	—	—	1.0	$\mu A$	$V_{CB} = 65 \text{ V},$ $I_E = 0$
Collector to emitter cutoff current	$I_{CEO}$	—	—	5.0	$\mu A$	$V_{CE} = 65 \text{ V},$ $R_{BE} = \infty$
Emitter to base cutoff current	$I_{EBO}$	—	—	1.0	$\mu A$	$V_{EB} = 5 \text{ V},$ $I_C = 0$
DC current transfer ratio	$h_{FE1}$	120	—	300		$V_{CE} = 2 \text{ V},$ $I_C = 0.5 \text{ A}$
DC current transfer ratio	$h_{FE2}$	40	—	—		$V_{CE} = 2 \text{ V},$ $I_C = 1.5 \text{ A}$
Collector to emitter saturation voltage	$V_{CE(sat)}$	—	0.1	0.2	V	$I_C = 1 \text{ A}$ $I_B = 50 \text{ mA}$
Base to emitter saturation voltage	$V_{BE(sat)}$	—	—	1.2	V	$I_C = 1 \text{ A}$ $I_B = 50 \text{ mA}$

---

2SD2485



## 2SD2485



## 2SD2485

