



NPN POWER DARLINGTON TRANSISTOR ARRAY

D74A5D



**100 VOLTS
5 AMP, 3 WATTS**

Designed for high power switching applications, hammer drive, pulse motor drive and inductive load drive applications.


Features:

- High reliability small-sized available (3 in 1)
- Epoxy single-inline package (8 pin)
- High collector power dissipation: $P_D = 3W @ T_A = 25^\circ C$ (Three device action)
- High collector current: $I_C = 5A$ (Max.)
- High DC current gain:
 $h_{FE} = 1000$ (Min.) @ $V_{CE} = 3V, I_C = 3A$

ARRAY CONFIGURATION



CASE STYLE SIP-8 PIN
DIMENSIONS ARE IN INCHES AND (MILLIMETERS)



maximum ratings ($T_A = 25^\circ C$) (unless otherwise specified)

RATING	SYMBOL	D74A5D	UNITS
Collector-Emitter Voltage	V_{CEO}	100	Volts
Collector-Base Voltage	V_{CBO}	100	Volts
Emitter Base Voltage	V_{EBO}	5	Volts
Collector Current — Continuous Peak	I_C I_{CM}	5 8	A
Base Current — Continuous	I_B	0.1	A
Collector Power Dissipation (One Device Action, $T_A = 25^\circ C$)	P_D	1.8	Watts
Collector Power Dissipation (Three Device Action, $T_A = 25^\circ C$)	P_D	3.0	Watts
Operating and Storage Junction Temperature Range	T_J, T_{STG}	-55 to +150	$^\circ C$

thermal characteristics

Thermal Resistance, Junction to Ambient	$\Sigma R_{\theta JA}$	41.7	$^\circ C/W$
Maximum Lead Temperature for Soldering Purpose: 1/8" from Case for 5 Seconds	T_L	260	$^\circ C$

electrical characteristics ($T_A = 25^\circ\text{C}$) (unless otherwise specified)

CHARACTERISTIC	SYMBOL	MIN	TYP	MAX	UNIT
----------------	--------	-----	-----	-----	------

off characteristics

Collector-Emitter Breakdown Voltage ($I_C = 30\text{mA}$, $I_B = 0$)	$V_{BR(GEO)}$	100	—	—	Volts
Collector Cutoff Current ($V_{CE} = 50\text{V}$, $I_B = 0$)	I_{CEO}	—	—	0.5	mA
Collector Cutoff Current ($V_{CB} = 100\text{V}$, $I_E = 0$)	I_{CBO}	—	—	200	μA
Emitter Cutoff Current ($V_{EB} = 5\text{V}$, $I_C = 0$)	I_{EBO}	—	—	2	mA

on characteristics

DC Current Gain ($I_C = 0.5\text{A}$, $V_{CE} = 3\text{V}$) ($I_C = 3\text{A}$, $V_{CE} = 3\text{V}$)	h_{FE}	1000 1000	— —	— —	—
Collector-Emitter Saturation Voltage ($I_C = 3\text{A}$, $I_B = 12\text{mA}$) ($I_C = 5\text{A}$, $I_B = 20\text{mA}$)	$V_{CE(sat)}$	— —	— —	2 4	Volts
Base-Emitter Voltage ($V_{CE} = 3\text{V}$, $I_C = 3\text{A}$)	$V_{BE(on)}$	—	—	2.5	Volts

switching characteristics

Turn-on Time	$I_C = 3\text{A}$, $I_{B1} = -I_{B2} = 12\text{mA}$ $V_{BE(off)} = 5\text{V}$, $R_L = 10\Omega$	t_{on}	—	1.5	—	μs
Turn-off Time		t_f	—	8.5	—	