



POWER-MOS FET

FIELD EFFECT POWER TRANSISTOR

D80AM2,N2


0.32 AMPERES
150, 200 VOLTS
 $R_{DS(ON)} = 5.0 \Omega$

This series of N-Channel Enhancement-mode Power MOSFETs utilizes GE's advanced Power DMOS technology to achieve low on-resistance with excellent device ruggedness and reliability.

This design has been optimized to give superior performance in most switching applications including: switching power supplies, inverters, converters and solenoid/relay drivers. Also, the extended safe operating area with good linear transfer characteristics makes it well suited for many linear applications such as audio amplifiers and servo motors.

Features

- Polysilicon gate — Improved stability and reliability
- No secondary breakdown — Excellent ruggedness
- Ultra-fast switching — Independent of temperature
- Voltage controlled — High transconductance
- Low input capacitance — Reduced drive requirement
- Excellent thermal stability — Ease of paralleling



maximum ratings ($T_A = 25^\circ\text{C}$) (unless otherwise specified)

RATING	SYMBOL	D80AM2	D80AN2	UNITS
Drain-Source Voltage	V_{DS}	150	200	Volts
Drain-Gate Voltage, $R_{GS} = 1M\Omega$	V_{DGR}	150	200	Volts
Continuous Drain Current @ $T_A = 25^\circ\text{C}^{(1)}$ @ $T_C = 100^\circ\text{C}^{(2)}$	I_D	0.32 0.43	0.32 0.43	A A
Pulsed Drain Current ⁽³⁾	I_{DM}	1.5	1.5	A
Gate-Source Voltage	V_{GS}	± 20	± 20	Volts
Total Power Dissipation @ $T_A = 25^\circ\text{C}^{(1)}$ Derate Above 25°C	P_D	1.0 8	1.0 8	Watts mW/ $^\circ\text{C}$
Total Power Dissipation @ $T_C = 100^\circ\text{C}^{(2)}$ Derate Above 100°C	P_D	2.0 40	2.0 40	Watts mW/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{STG}	-55 to 150	-55 to 150	$^\circ\text{C}$

thermal characteristics

Thermal Resistance, Junction to Case	$R_{\theta JC}$	25	25	$^\circ\text{C/W}$
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	125	125	$^\circ\text{C/W}$
Maximum Lead Temperature for Soldering Purposes: $\frac{1}{8}$ " from Case for 5 Seconds	T_L	300	300	$^\circ\text{C}$

(1) Device Lead Mounted in Free Air, No Heatsink. (2) Device Tab Soldered to Heatsink.

(3) Repetitive Rating: Pulse Width Limited by Max. Junction Temperature.

electrical characteristics ($T_A = 25^\circ\text{C}$) (unless otherwise specified)

CHARACTERISTIC	SYMBOL	MIN	TYP	MAX	UNIT
----------------	--------	-----	-----	-----	------

off characteristics

Drain-Source Breakdown Voltage ($V_{GS} = 0\text{V}$, $I_D = 250\text{ }\mu\text{A}$)	D80AM2 D80AN2	BV_{DSS}	150 200	— —	Volts
Zero Gate Voltage Drain Current ($V_{DS} = \text{Max Rating}$, $V_{GS} = 0\text{V}$, $T_A = 25^\circ\text{C}$) ($V_{DS} = \text{Max Rating} \times 0.8$, $V_{GS} = 0\text{V}$, $T_A = 125^\circ\text{C}$)		I_{DSS}	— —	— 250 1000	μA
Gate-Source Leakage Current ($V_{GS} = \pm 20\text{V}$)		I_{GSS}	—	± 500	nA

on characteristics*

Gate Threshold Voltage ($V_{DS} = V_{GS}$, $I_D = 250\text{ }\mu\text{A}$)	$T_A = 25^\circ\text{C}$	$V_{GS(TH)}$	2.0	—	4.0	Volts
Drain-Source On-State Voltage ($V_{GS} = 10\text{V}$)	$I_D = 0.15\text{A}$ $I_D = 0.32\text{A}$ $I_D = 0.15\text{A}$, $T_A = 125^\circ\text{C}$	$V_{DS(ON)}$	— — —	0.66 1.41 1.05	0.75 — —	Volts
Static Drain-Source On-State Resistance ($V_{GS} = 10\text{V}$, $I_D = 0.15\text{A}$)		$R_{DS(ON)}$	—	4.4	5.0	Ohms
Forward Transconductance ($V_{DS} = 10\text{V}$, $I_D = 0.15\text{A}$)		g_{fs}	—	0.11	—	mhos

dynamic characteristics

Input Capacitance	$V_{GS} = 0\text{V}$	C_{iss}	—	37	70	pF
Output Capacitance	$V_{DS} = 25\text{V}$	C_{oss}	—	15	25	pF
Reverse Transfer Capacitance	$f = 1\text{ MHz}$	C_{rss}	—	4	8	pF


switching characteristics*

Turn-on Delay Time	$V_{DS} = 90\text{V}$	$t_{d(on)}$	—	15	—	ns
Rise Time	$I_D = 0.15\text{A}$, $V_{GS} = 15\text{V}$	t_r	—	10	—	ns
Turn-off Delay Time	$R_{GEN} = 50\Omega$, $R_{GS} = 12.5\Omega$	$t_{d(off)}$	—	22	—	ns
Fall Time	($R_{GS} \text{ (EQUIV.)} = 10\Omega$)	t_f	—	28	—	ns


source-drain diode ratings and characteristics*

Continuous Source Current	I_S	—	—	0.32	A
Pulsed Source Current	I_{SM}	—	—	1.5	A
Diode Forward Voltage ($T_A = 25^\circ\text{C}$, $V_{GS} = 0\text{V}$, $I_S = 0.32\text{A}$)	V_{SD}	—	0.86	1.3	Volts
Reverse Recovery Time ($I_S = 0.32\text{A}$, $di_S/dt = 100\text{A}/\mu\text{s}$, $V_{DS} = 80\text{V max.}$, $T_A = 125^\circ\text{C}$)	t_{rr}	—	125	—	ns

Pulse Test: Pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$



MAXIMUM SAFE OPERATING AREA



TYPICAL NORMALIZED $R_{DS(ON)}$ AND $V_{GS(TH)}$ VS. TEMP.