

# VOLTAGE CONTROLLED OSCILLATOR

## SURFACE MOUNT MODEL: DCMO1545

WIDE BANDWIDTH


150 - 450 MHz

**FEATURES:**

- ▶ Exceptional Phase Noise Performance
- ▶ Small Size, Surface Mount
- ▶ Lead Free REL-PRO® Technology







**Phase Noise**



**SPECIFICATIONS ( Rev. E 07/03/07 )**

Frequency	150 - 450 MHz
Tuning Voltage (Full Band)	0.5 - 24 VDC
Bias Voltage	+5 to +12 VDC @ 35 mA (Max)
Output Power	+4 dBm (Min)
Tuning Sensitivity	8 - 20 MHz/V (Typ)
Output Impedance	50 Ohms (Nom)
Harmonic Suppression	10 dBc (Typ)
Frequency Pulling	4 MHz (Max @ 1.75:1 VSWR)
Frequency Pushing	2 MHz/V (Max)
Phase Noise @ 10 kHz	-108 dBc/Hz (Typ)
Operating Temperature Range	-40 to +85 °C

Package # 278LF



OPTIONAL SOLDER AREA FOR HIGH VIBRATION ENVIRONMENT  
 TOLERANCES ON THREE DECIMAL PLACES = ± 0.015  
 PACKAGE MOUNTING: SEE APPLICATION NOTE AN7200

ALL UNLABELED PINS TO BE GROUNDING.

**Guaranteed Tuning Specifications**

Tuning Voltage ( V )	Frequency ( MHz )
0.5	150 (Max)
5	200 (Min)
8	250 (Min)
12	320 (Min)
15	360 (Min)
18	400 (Min)
24	450 (Min)

This product is manufactured under one or more of the following patents: Approved: 5,160,810; 5,122,621; 5,390,349; 5,416,449; 5,650,754; 5,805,431; 6,525,623; 6,850,575; 7,088,189; 7,180,381; 7,196,591 | Pending: 60/493075; 60/501371 & 60/501790; 60/527957 & 60/528670; 60/563481; 60/564173; 60/589090; 60/601823; 60/605791; EV31369834; 11/259766; 60/622485 & 60/710310; 10/937525/60/736901; 60/732787





# VOLTAGE CONTROLLED OSCILLATOR

## SURFACE MOUNT MODEL: DCMO1545

WIDE BANDWIDTH

150 - 450 MHz

PERFORMANCE PLOTS



www.DataSheet4U.com

This product is manufactured under one or more of the following patents: Approved: 5,160,810; 5,122,621; 5,390,349; 5,416,449; 5,650,754; 5,805,431; 6,525,623; 6,850,575; 7,088,189; 7,180,381; 7,196,591 | Pending: 60/493075; 60/501371 & 60/501790; 60/527957 & 60/528670; 60/563481; 60/564173; 60/589090; 60/601823; 60/605791; EV31369834; 11/259766; 60/622485 & 60/710310; 10/937525/60/736901; 60/732787

Copyright © Synergy Microwave Corporation  
 201 McLean Boulevard • Paterson, New Jersey 07504 • Tel: (973) 881-8800 • Fax: (973) 881-8361  
 E-Mail: sales@synergymw.com • World Wide Web: http://www.synergymw.com





# VOLTAGE CONTROLLED OSCILLATOR

## SURFACE MOUNT MODEL: DCMO1545

WIDE BANDWIDTH

150 - 450 MHz

PERFORMANCE PLOTS



www.DataSheet4U.com

This product is manufactured under one or more of the following patents: Approved: 5,160,810; 5,122,621; 5,390,349; 5,416,449; 5,650,754; 5,805,431; 6,525,623; 6,850,575; 7,088,189; 7,180,381; 7,196,591 | Pending: 60/493075; 60/501371 & 60/501790; 60/527957 & 60/528670; 60/563481; 60/564173; 60/589090; 60/601823; 60/605791; EV31369834; 11/259766; 60/622485 & 60/710310; 10/937525/60/736901; 60/732787

Copyright © Synergy Microwave Corporation  
 201 McLean Boulevard • Paterson, New Jersey 07504 • Tel: (973) 881-8800 • Fax: (973) 881-8361  
 E-Mail: sales@synergymw.com • World Wide Web: http://www.synergymw.com

