

### FEATURES

- Double Side Cooling
- High Surge Capability

### APPLICATIONS

- Medium Voltage Soft Starts
- High Voltage Power Supplies
- Static Switches

### VOLTAGE RATINGS

| Part and Ordering Number | Repetitive Peak Voltages<br>$V_{DRM}$ and $V_{RRM}$<br>V | Conditions   |
|--------------------------|--|--|
| DCR760N85                | 8500   | $T_{vj} = -40^{\circ}C$ to $125^{\circ}C$ ,<br>$I_{DRM} = I_{RRM} = 200mA$ ,<br>$V_{DRM}, V_{RRM} t_p = 10ms$ ,<br>$V_{DSM} \& V_{RSM} =$<br>$V_{DRM} \& V_{RRM} + 100V$<br>respectively |
| DCR760N80                | 8000   |  |
| DCR760N75                | 7500   |  |
| DCR760N70                | 7000   |  |

Lower voltage grades available.

### ORDERING INFORMATION

When ordering, select the required part number shown in the Voltage Ratings selection table.

For example:

### DCR760N85

Note: Please use the complete part number when ordering and quote this number in any future correspondence relating to your order.

### KEY PARAMETERS

|             |                |
|-------------|----------------|
| $V_{DRM}$   | 8500V          |
| $I_{T(AV)}$ | 760A           |
| $I_{TSM}$   | 12800A         |
| $dV/dt^*$   | 1500V/ $\mu s$ |
| $dI/dt$     | 200A/ $\mu s$  |

\* Higher  $dV/dt$  selections available




Fig. 1 Package outline

## CURRENT RATINGS

$T_{case} = 60^{\circ}C$  unless stated otherwise

| Symbol                    | Parameter                            | Test Conditions          | Max. | Units |
|---------------------------|--------------------------------------|--------------------------|------|-------|
| <b>Double Side Cooled</b> |                                      |                          |      |       |
| $I_{T(AV)}$               | Mean on-state current                | Half wave resistive load | 760  | A     |
| $I_{T(RMS)}$              | RMS value                            | -                        | 1190 | A     |
| $I_T$                     | Continuous (direct) on-state current | -                        | 1150 | A     |

## SURGE RATINGS

| Symbol    | Parameter                               | Test Conditions                           | Max. | Units             |
|-----------|---|---|------|-------------------|
| $I_{TSM}$ | Surge (non-repetitive) on-state current | 10ms half sine, $T_{case} = 125^{\circ}C$ | 12.8 | kA                |
| $I^2t$    | $I^2t$ for fusing                       | $V_R = 0$                                 | 0.82 | MA <sup>2</sup> s |

## THERMAL AND MECHANICAL RATINGS

| Symbol        | Parameter                             | Test Conditions                                  | Min.        | Max. | Units       |               |
|---------------|---------------------------------------|--|-------------|------|-------------|---------------|
| $R_{th(j-c)}$ | Thermal resistance – junction to case | Double side cooled                               | DC          | -    | 0.0202      | $^{\circ}C/W$ |
|               |                                       | Single side cooled                               | Anode DC    | -    | 0.0379      | $^{\circ}C/W$ |
|               |                                       |  | Cathode DC  | -    | 0.0451      | $^{\circ}C/W$ |
| $R_{th(c-h)}$ | Thermal resistance – case to heatsink | Clamping force 23 kN<br>(with mounting compound) | Double side | -    | 0.004       | $^{\circ}C/W$ |
|               |                                       |  | Single side | -    | 0.008       | $^{\circ}C/W$ |
| $T_{vj}$      | Virtual junction temperature          | On-state (conducting)                            | -           | 135  | $^{\circ}C$ |               |
|               |                                       | Reverse (blocking)                               | -           | 125  | $^{\circ}C$ |               |
| $T_{stg}$     | Storage temperature range             |  | -55         | 125  | $^{\circ}C$ |               |
| $F_m$         | Clamping force                        |  | 20.0        | 25.0 | kN          |               |

**DYNAMIC CHARACTERISTICS**


| Symbol            | Parameter                                     | Test Conditions  | Min.            | Max.  | Units      |            |
|-------------------|---|--|-----------------|-------|------------|------------|
| $I_{RRM}/I_{DRM}$ | Peak reverse and off-state current            | At $V_{RRM}/V_{DRM}$ , $T_{case} = 125^{\circ}C$   | -               | 200   | mA         |            |
| $dV/dt$           | Max. linear rate of rise of off-state voltage | To 67% $V_{DRM}$ , $T_j = 125^{\circ}C$ , gate open  | -               | 1500  | V/ $\mu s$ |            |
| $di/dt$           | Rate of rise of on-state current              | From 67% $V_{DRM}$ to $2x I_{T(AV)}$   | Repetitive 50Hz | -     | 100        | A/ $\mu s$ |
|                   |   | Gate source 30V, 10 $\Omega$ ,<br>$t_r < 0.5\mu s$ , $T_j = 125^{\circ}C$  | Non-repetitive  | -     | 200        | A/ $\mu s$ |
| $V_{T(TO)}$       | Threshold voltage – Low level                 | 100A to 500A at $T_{case} = 125^{\circ}C$  | -               | 1.081 | V          |            |
|                   | Threshold voltage – High level                | 500A to 3000A at $T_{case} = 125^{\circ}C$   | -               | 1.243 | V          |            |
| $r_T$             | On-state slope resistance – Low level         | 100A to 500A at $T_{case} = 125^{\circ}C$  | -               | 1.694 | m $\Omega$ |            |
|                   | On-state slope resistance – High level        | 500A to 3000A at $T_{case} = 125^{\circ}C$   | -               | 1.342 | m $\Omega$ |            |
| $t_{gd}$          | Delay time                                    | $V_D = 67\% V_{DRM}$ , gate source 30V, 10 $\Omega$<br>$t_r = 0.5\mu s$ , $T_j = 25^{\circ}C$                    | TBD             | TBD   | $\mu s$    |            |
| $t_q$             | Turn-off time                                 | $T_j = 125^{\circ}C$ , $V_R = 200V$ , $di/dt = 1A/\mu s$ ,<br>$dV_{DR}/dt = 20V/\mu s$ linear                    | 1000            | 1600  | $\mu s$    |            |
| $Q_S$             | Stored charge                                 | $I_T = 2000A$ , $T_j = 125^{\circ}C$ , $di/dt = 1A/\mu s$ ,<br>$V_{Rpeak} = 60\% V_{drm}$ , $V_R = 40\% V_{drm}$ | 3400            | 5600  | $\mu C$    |            |
| $I_L$             | Latching current                              | $T_j = 25^{\circ}C$ , $V_B = 5V$   | TBD             | TBD   | mA         |            |
| $I_H$             | Holding current                               | $T_j = 25^{\circ}C$ , $R_{G-K} = \infty$ , $I_{TM} = 500A$ , $I_T = 5A$  | TBD             | TBD   | mA         |            |

---

**GATE TRIGGER CHARACTERISTICS AND RATINGS**

| Symbol          | Parameter                | Test Conditions                                  | Max. | Units |
|-----------------|--------------------------|--|------|-------|
| V <sub>GT</sub> | Gate trigger voltage     | V <sub>DRM</sub> = 5V, T <sub>case</sub> = 25° C | 1.5  | V     |
| V <sub>GD</sub> | Gate non-trigger voltage | At V <sub>DRM</sub> , T <sub>case</sub> = 125° C | TBD  | V     |
| I <sub>GT</sub> | Gate trigger current     | V <sub>DRM</sub> = 5V, T <sub>case</sub> = 25° C | 250  | mA    |
| I <sub>GD</sub> | Gate non-trigger current | V <sub>DRM</sub> = 5V, T <sub>case</sub> = 25° C | TBD  | mA    |

**CURVES**




**Fig.2 Maximum & minimum on-state characteristics**

**V<sub>TM</sub> EQUATION**


$$V_{TM} = A + B \ln(I_T) + C \cdot I_T + D \cdot \sqrt{I_T}$$

Where A = 0.882859  
 B = 0.020109  
 C = 0.001177  
 D = 0.012682


these values are valid for T<sub>j</sub> = 125° C for I<sub>T</sub> 100A to 3000A




**Fig.3 On-state power dissipation – sine wave**




**Fig.4 Maximum permissible case temperature, double side cooled – sine wave**




**Fig.5 Maximum permissible heatsink temperature, double side cooled – sine wave**




**Fig.6 On-state power dissipation – rectangular wave**



**Fig.7 Maximum permissible case temperature, double side cooled – rectangular wave**



**Fig.8 Maximum permissible heatsink temperature, double side cooled – rectangular wave**



**Fig.9 Maximum (limit) transient thermal impedance – junction to case (° C/kW)**

|                     |                |          |          |          |         |
|---------------------|----------------|----------|----------|----------|---------|
|                     |                | 1        | 2        | 3        | 4       |
| Double side cooled  | $R_i$ (° C/kW) | 1.2849   | 4.988    | 5.5614   | 8.3856  |
|                     | $T_i$ (s)      | 0.009195 | 0.057825 | 0.43183  | 1.3814  |
| Anode side cooled   | $R_i$ (° C/kW) | 1.4937   | 5.1268   | 6.8498   | 24.2935 |
|                     | $T_i$ (s)      | 0.010286 | 0.064874 | 0.49207  | 7.2582  |
| Cathode side cooled | $R_i$ (° C/kW) | 1.6042   | 5.285    | 5.0921   | 33.032  |
|                     | $T_i$ (s)      | 0.010861 | 0.069332 | 0.464312 | 6.671   |

$$Z_{th} = \sum [R_i \times (1 - \exp. (-t/T_i))] \quad [1]$$

$\Delta R_{th(j-c)}$  Conduction

Tables show the increments of thermal resistance  $R_{th(j-c)}$  when the device operates at conduction angles other than d.c.

| Double side cooling |                     |       | Anode Side Cooling |                     |       | Cathode Sided Cooling |                     |       |
|---------------------|---------------------|-------|--------------------|---------------------|-------|-----------------------|---------------------|-------|
| $\theta^\circ$      | $\Delta Z_{th} (z)$ |       | $\theta^\circ$     | $\Delta Z_{th} (z)$ |       | $\theta^\circ$        | $\Delta Z_{th} (z)$ |       |
|                     | sine.               | rect. |                    | sine.               | rect. |                       | sine.               | rect. |
| 180                 | 2.25                | 1.53  | 180                | 2.23                | 1.52  | 180                   | 2.22                | 1.52  |
| 120                 | 2.60                | 2.19  | 120                | 2.57                | 2.16  | 120                   | 2.56                | 2.15  |
| 90                  | 2.98                | 2.55  | 90                 | 2.94                | 2.52  | 90                    | 2.92                | 2.51  |
| 60                  | 3.32                | 2.94  | 60                 | 3.27                | 2.90  | 60                    | 3.25                | 2.88  |
| 30                  | 3.59                | 3.37  | 30                 | 3.53                | 3.32  | 30                    | 3.50                | 3.29  |
| 15                  | 3.71                | 3.60  | 15                 | 3.65                | 3.53  | 15                    | 3.62                | 3.51  |




Fig.10 Multi-cycle surge current





Fig.11 Single-cycle surge current

**PACKAGE DETAILS**

For further package information, please contact Customer Services. All dimensions in mm, unless stated otherwise. **DO NOT SCALE.**



**Fig.15 Package outline**



## **POWER ASSEMBLY CAPABILITY**

The Power Assembly group was set up to provide a support service for those customers requiring more than the basic semiconductor, and has developed a flexible range of heatsink and clamping systems in line with advances in device voltages and current capability of our semiconductors.

We offer an extensive range of air and liquid cooled assemblies covering the full range of circuit designs in general use today. The Assembly group offers high quality engineering support dedicated to designing new units to satisfy the growing needs of our customers.

Using the latest CAD methods our team of design and applications engineers aim to provide the Power Assembly Complete Solution (PACs).

## **HEATSINKS**

The Power Assembly group has its own proprietary range of extruded aluminium heatsinks which have been designed to optimise the performance of Dynex semiconductors. Data with respect to air natural, forced air and liquid cooling (with flow rates) is available on request.

For further information on device clamps, heatsinks and assemblies, please contact your nearest sales representative or Customer Services.

Stresses above those listed in this data sheet may cause permanent damage to the device. In extreme conditions, as with all semiconductors, this may include potentially hazardous rupture of the package. Appropriate safety precautions should always be followed.



<http://www.dynexsemi.com>

**e-mail: [power\\_solutions@dynexsemi.com](mailto:power_solutions@dynexsemi.com)**

**HEADQUARTERS OPERATIONS  
DYNEX SEMICONDUCTOR LTD**  
Doddington Road, Lincoln  
Lincolnshire, LN6 3LF. United Kingdom.  
Tel: +44(0)1522 500500  
Fax: +44(0)1522 500550

**CUSTOMER SERVICE**  
Tel: +44(0)1522 502753 / 502901. Fax: +44(0)1522 500020

© Dynex Semiconductor 2003 TECHNICAL DOCUMENTATION – NOT FOR  
RESALE. PRODUCED IN UNITED KINGDOM.

This publication is issued to provide information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose nor form part of any order or contract nor to be regarded as a representation relating to the products or services concerned. No warranty or guarantee express or implied is made regarding the capability, performance or suitability of any product or service. The Company reserves the right to alter without prior notice the specification, design or price of any product or service. Information concerning possible methods of use is provided as a guide only and does not constitute any guarantee that such methods of use will be satisfactory in a specific piece of equipment. It is the user's responsibility to fully determine the performance and suitability of any equipment using such information and to ensure that any publication or data used is up to date and has not been superseded. These products are not suitable for use in any medical products whose failure to perform may result in significant injury or death to the user. All products and materials are sold and services provided subject to the Company's conditions of sale, which are available on request.

All brand names and product names used in this publication are trademarks, registered trademarks or trade names of their respective owners.