

Display Elektronik GmbH

DATA SHEET

TFT MODULE

DEM 320240P TMH-PW-N

2,3" TFT

Product Specification

Ver.: 1

24.05.2016

Revision History

| Revision | Date | Originator | Detail | Remarks |
|-----------------|-------------|-------------------|------------------|----------------|
| 0 | 17.07.2015 | MH | Initial Release | - |
| 1 | 24.05.2016 | MH | Modify Interface | P4 |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

Table of Contents

| No. | Item | Page |
|------|--|------|
| 1. | General Description | 4 |
| 2. | Module Parameter | 4 |
| 3. | Absolute Maximum Ratings | 4 |
| 4. | DC Characteristics | 5 |
| 5. | Backlight Characteristic | 5 |
| 5.1. | Backlight Characteristics..... | 5 |
| 5.2. | Backlighting circuit | 5 |
| 6. | Optical Characteristics | 6 |
| 6.1. | Optical Characteristics | 6 |
| 6.2. | Definition of Response Time | 6 |
| 6.3. | Definition of Contrast Ratio | 7 |
| 6.4. | Definition of Viewing Angles..... | 7 |
| 6.5. | Definition of Color Appearance | 8 |
| 6.6. | Definition of Surface Luminance, Uniformity and Transmittance..... | 8 |
| 7. | Block Diagram and Power Supply | 9 |
| 8. | Interface Pins Definition | 10 |
| 9. | Timing Characteristics | 11 |
| 9.1 | Reset Timing | 11 |
| 9.2 | Display Serial Interface Characteristics(3-line SPI system)..... | 12 |
| 9.3 | Parallel Interface Characteristics (6bit RGB Interface)..... | 13 |
| 10. | Quality Assurance | 14 |
| 10.1 | Purpose | 14 |
| 10.2 | Standard for Quality Test..... | 14 |
| 10.3 | Nonconforming Analysis & Disposition | 14 |
| 10.4 | Agreement Items..... | 14 |
| 10.5 | Standard of the Product Visual Inspection | 15 |
| 10.6 | Inspection Specification | 15 |
| 10.7 | Classification of Defects..... | 19 |
| 10.8 | Identification/marketing criteria | 19 |
| 10.9 | Packaging | 19 |
| 11. | Reliability Specification | 20 |
| 12. | Precautions and Warranty | 21 |
| 12.1 | Safety..... | 21 |
| 12.2 | Handling..... | 21 |
| 12.3 | Storage..... | 21 |
| 12.4 | Metal Pin (Apply to Products with Metal Pins)..... | 21 |
| 12.5 | Operation | 22 |
| 12.6 | Static Electricity | 22 |
| 12.7 | Limited Warranty..... | 22 |
| 13. | Outline Drawing | 23 |

1. General Description

The specification is a transmissive type color active matrix liquid crystal display (LCD) which uses amorphous thin film transistor (TFT) as switching devices. This product is composed of a TFT-LCD panel, driver ICs and a backlight unit.

2. Module Parameter

| Features | Details | Unit |
|--------------------------------|---|------------|
| Display Size (Diagonal) | 2.3" | - |
| LCD Type | TN TFT | - |
| Display Mode | Transmissive / Normally White | - |
| Resolution | 320 x RGB x 240 | Pixels |
| View Direction | 6 O'clock | Best Image |
| Gray Scale Inversion Direction | 12 O'clock | - |
| Module Outline | 50.90 x 45.80 x 2.30 (max.) (Note1) | mm |
| Active Area | 46.752 x 35.064 | mm |
| Pixel Size | 146.10 x 146.10 | mm |
| Pixel Arrangement | R.G.B. Vertical-Stripe | - |
| Polarizer Surface Treatment | Normal | - |
| Display Colors | 262k | - |
| Interface | 6-Bit-RGB-Interface (Serial) + 3-Wire-SPI | - |
| Driver IC | ILI9342C (Ilitek) | - |
| With or Without Touch Panel | Without | - |
| Operating Temperature | -20°C to +70°C | °C |
| Storage Temperature | -30°C to +80°C | °C |
| Weight | ~6 | g |

Note 1: Exclusive hooks, posts, FFC/FPC tail etc.

3. Absolute Maximum Ratings

$V_{SS}=0V$, $T_a=25^{\circ}C$

| Item | Symbol | Min. | Max. | Unit |
|-----------------------|------------------|------|------|------|
| Supply Voltage | VCC | -0.3 | 3.6 | V |
| Storage Temperature | T _{STG} | -30 | 80 | °C |
| Operating Temperature | T _{OP} | -20 | 70 | °C |

Note 1: If T_a below 50°C, the maximal humidity is 90%RH, if T_a over 50°C, absolute humidity should be less than 60%RH.

Note 2: The response time will be extremely slow when the operating temperature is around -10°C, and the back ground will become darker at high temperature operating.

4. DC Characteristics

| Item | Symbol | Min. | Typ. | Max. | Unit | |
|----------------------------------|-----------------|---------------------------------|------|---------|------|----|
| Supply Voltage | VCC | 3.0 | 3.2 | 3.3 | V | |
| Logic Low Input Voltage | V _{IL} | -0.3 | - | 0.2*VCC | V | |
| Logic High Input Voltage | V _{IH} | 0.8*VCC | - | VCC | V | |
| Logic Low Output Voltage | V _{OL} | 0 | - | 0.2VCC | V | |
| Logic High Output Voltage | V _{OH} | 0.8*VCC | - | VCC | V | |
| Current Consumption All Black | Logic Analog | I _{CC+ I_{IN}} | - | (6) | - | mA |


5. Backlight Characteristic

5.1. Backlight Characteristics

| Item | Symbol | Condition | Min. | Typ. | Max. | Unit |
|---------------------|--------------------------|---|------|--------|------|------|
| Forward Voltage | V _F | T _a =25 °C, I _F =20mA/LED | 2.9 | 3.2 | 3.4 | V |
| Forward Current | I _F | T _a =25 °C, V _F =3.2V/LED | - | 80 | - | mA |
| Power Dissipation | P _D | | - | 256 | - | mW |
| Uniformity | Avg | | 75 | 80 | - | % |
| LED Lifetime (25°C) | - | | - | 30,000 | - | Hrs |
| Drive Method | Constant Current | | | | | |
| LED Configuration | 4 White LEDs in Parallel | | | | | |

Note: LED life time defined as follows: The final brightness is at 50% of original brightness.
The environmental conducted under ambient air flow, at T_a=25±2°C, 60%RH±5%, I_F=20mA.

5.2. Backlighting Circuit



6. Optical Characteristics


6.1. Optical Characteristics

Ta=25°C, VCC=3.2V, TN LC+ Polarizer

| | Item | Symbol | Condition | Specification | | | Unit |
|----------------------------------|-------------------------------------|----------------|--|---------------|---------|---------|-------------------|
| | | | | Min. | Typ. | Max. | |
| Backlight On (Transmissive Mode) | Luminance on TFT($I_f=20mA/LED$) | Lv | Normally viewing angle $\theta_x = \phi_y = 0^\circ$ | 240 | 300 | - | cd/m ² |
| | Contrast Ratio(See 6.3) | CR | | 400 | 500 | - | |
| | Response Time (See 6.2) | TR+TF | | - | 20 | 30 | ms |
| | Chromaticity Transmissive (See 6.5) | Red | X _R | (0.508) | (0.558) | (0.608) | |
| | | | Y _R | (0.263) | (0.313) | (0.363) | |
| | | Green | X _G | (0.252) | (0.302) | (0.352) | |
| | | | Y _G | (0.578) | (0.628) | (0.678) | |
| | | Blue | X _B | (0.095) | (0.145) | (0.195) | |
| | | | Y _B | (0.051) | (0.101) | (0.151) | |
| | White | X _W | (0.207) | (0.257) | (0.307) | | |
| Y _W | | (0.269) | (0.319) | (0.369) | | | |
| Viewing Angle (See 6.4) | Horizontal | θ_{x+} | Center CR ≥ 10 | 60 | 70 | - | Deg. |
| | | θ_{x-} | | 60 | 70 | - | |
| | Vertical | ϕ_{y+} | | 60 | 70 | - | |
| | | ϕ_{y-} | | 50 | 60 | - | |
| NTSC Ratio(Gamut) | | | | - | 45 | 50 | % |

6.2. Definition of Response Time

6.2.1. Normally Black Type (Negative)




Tr is the time it takes to change from non-selected state with relative luminance 10% to selected state with relative luminance 90%;

Tf is the time it takes to change from selected state with relative luminance 90% to non-selected state with relative luminance 10%.

Note : Measuring machine: LCD-5100

6.2.2. Normally White Type (Positive)



T_r is the time it takes to change from non-selected stage with relative luminance 90% to selected state with relative luminance 10%;

T_f is the time it takes to change from selected state with relative luminance 10% to non-selected state with relative luminance 90%;

Note : Measuring machine: LCD-5100 or EQUI


6.3. Definition of Contrast Ratio

Contrast is measured perpendicular to display surface in reflective and transmissive mode. The measurement condition is:

| | |
|--------------------------|--------------------------|
| Measuring Equipment | Eldim or Equivalent |
| Measuring Point Diameter | 3mm//1mm |
| Measuring Point Location | Active Area centre point |
| Test pattern | A: All Pixels white |
| | B: All Pixel black |
| Contrast setting | Maximum |

Definitions: CR (Contrast) = Luminance of White Pixel / Luminance of Black Pixel

6.4. Definition of Viewing Angles




Measuring machine: LCD-5100 or EQUI

6.5. Definition of Color Appearance

R,G,B and W are defined by (x, y) on the IE chromaticity diagram

NTSC=area of RGB triangle/area of NTSC triangleX100%

Measuring picture: Red, Green, Blue and White (Measuring machine: BM-7)



6.6. Definition of Surface Luminance, Uniformity and Transmittance


Using the transmissive mode measurement approach, measure the white screen luminance of the display panel and backlight.

6.6.1. Surface Luminance: $L_v = \text{average} (L_{P1}:L_{P9})$


6.6.2. Uniformity = $\text{Minimal} (L_{P1}:L_{P9}) / \text{Maximal} (L_{P1}:L_{P9}) * 100\%$

6.6.3. Transmittance = $L_v \text{ on LCD} / L_v \text{ on Backlight} * 100\%$

Note : Measuring machine: BM-7



7. Block Diagram and Power Supply




8. Interface Pins Definition

| No. | Symbol | Function | Remark |
|-----|--------|--|--------|
| 1 | NC | No connection. | |
| 2 | NC | No connection. | |
| 3 | D0 | Data bus. | |
| 4 | D1 | Data bus. | |
| 5 | D2 | Data bus. | |
| 6 | D3 | Data bus. | |
| 7 | D4 | Data bus. | |
| 8 | D5 | Data bus. | |
| 9 | DCLK | Pixel Clock Signal. | |
| 10 | VSYNC | Vertical Sync Signal. | |
| 11 | HSYNC | Horizontal Sync Signal. | |
| 12 | SCL | Serial Communication Clock Input. | |
| 13 | SDA | Serial Communication Data Input and Output. | |
| 14 | CS | Chip select signal. | |
| 15 | VCC | Supply voltage. | |
| 16 | GND | Ground. | |
| 17 | NC | No connection. | |
| 18 | LED_K | LED Cathode. | |
| 19 | GND | Ground. | |
| 20 | LED_A | LED Anode. | |
| 21 | NC | No connection. | |
| 22 | NC | No connection. | |
| 23 | NC | No connection. | |
| 24 | C1M | Connect the charge-pumping capacitor on C11P/C11N for generating DDVDH level. | |
| 25 | C1P | | |
| 26 | NC | No connection. | |
| 27 | C2M | Connect the charge-pumping capacitor on C31P/C31N for generating DDVDH 3X level. | |
| 28 | C2P | | |
| 29 | NC | No connection. | |
| 30 | C3M | Connect the charge-pumping capacitor on C21P/C21N for generating VGH, VGL level. | |
| 31 | C3P | | |
| 32 | VINT3 | Power supply for the source driver and VCOM driver. | |
| 33 | VCAC | A power supply pin for generating GVCL. | |
| 34 | NC | No connection. | |
| 35 | VGH | Supply for The Gate Driver. | |
| 36 | C4M | Connect the charge-pumping capacitor on C22P/C22N for generating DDVDL 3X level. | |
| 37 | C4P | | |
| 38 | VGL | Supply for The Gate Driver. | |
| 39 | NC | No connection. | |
| 40 | NC | No connection. | |

9. Timing Characteristics

9.1 Reset Timing



| Signal | Symbol | Parameter | Min | Max | Unit |
|--------|----------|----------------------|-----|---------------------|---------|
| RESX | t_{RW} | Reset pulse duration | 10 | | μ S |
| | t_{RT} | Reset cancel | | 5 (note 1,5) | mS |
| | | | | 120 (note 1,6,7) | mS |


Note 1: The reset cancel includes also required time for loading ID bytes, VCOM setting and other settings from NV memory to registers. This loading is done every time when there is HW reset cancel time (t_{RT}) within 5 ms after a rising edge of RESX.

Note 2: Spike due to an electrostatic discharge on RESX line does not cause irregular system reset according to the table below: -

| RESX Pulse | Action |
|----------------------|----------------|
| Shorter than 5us | Reset Rejected |
| Longer than 10us | Reset |
| Between 5us and 10us | Reset starts |

Note 3: During the Resetting period, the display will be blanked (The display is entering blanking sequence, which maximum time is 120 ms, when Reset Starts in Sleep Out –mode. The display remains the blank state in Sleep In -mode.) And then return to Default condition for Hardware Reset.

Note 4: Spike Rejection also applies during a valid reset pulse as shown below:




Note 5: When Reset applied during Sleep In Mode.

Note 6: When Reset applied during Sleep Out Mode.


Note 7: It is necessary to wait 5msec after releasing RESX before sending commands. Also Sleep Out command cannot be sent for 120msec.

9.2 Display Serial Interface Characteristics(3-line SPI system)




| Signal | Symbol | Parameter | min | max | Unit | Description |
|--------------|--------|-----------------------------|-----|-----|------|-------------|
| SCL | tscycw | Serial Clock Cycle (Write) | 100 | - | ns | |
| | tshw | SCL "H" Pulse Width (Write) | 35 | - | ns | |
| | tslw | SCL "L" Pulse Width (Write) | 35 | - | ns | |
| | tscycr | Serial Clock Cycle (Read) | 150 | - | ns | |
| | tshr | SCL "H" Pulse Width (Read) | 60 | - | ns | |
| | tslr | SCL "L" Pulse Width (Read) | 60 | - | ns | |
| SDA (Input) | tsds | Data setup time (Write) | 30 | - | ns | |
| | tsdh | Data hold time (Write) | 30 | - | ns | |
| SDA (Output) | tacc | Access time (Read) | 10 | - | ns | |
| | toh | Output disable time (Read) | 15 | 50 | ns | |
| CSX | tsc | SCL-CSX | 20 | - | ns | |
| | tchw | CSX "H" Pulse Width | 40 | - | ns | |
| | tcss | CSX-SCL Time(write) | 30 | - | ns | |
| | tcsh | | 30 | - | ns | |

Note: Ta = 25 °C, IOVCC=1.65V to 2.8V, VCI=2.6V to 3.3V, AGND=GND=0V



9.3 Parallel Interface Characteristics (6bit RGB Interface)



(VCI=3.0 to 3.3V, IOVCC=3.0 to 3.3V, Ta=25°C)

| Signal | Symbol | Parameter | min | max | Unit | Description |
|---------------|-------------------------------------|-----------------------------------|-----|-----|------|----------------------------------|
| VSYNC / HSYNC | tSYNCS | VSYNC/HSYNC setup time | 15 | - | ns | 18/16-bit bus RGB interface mode |
| | tSYNCH | VSYNC/HSYNC hold time | 15 | - | ns | |
| DE | tENS | DE setup time | 15 | - | ns | |
| | tENH | DE hold time | 15 | - | ns | |
| D[17:0] | tPOS | Data setup time | 15 | - | ns | |
| | tPDH | Data hold time | 15 | - | ns | |
| DOTCLK | PWDH | DOTCLK high-level period | 33 | - | ns | |
| | PWDL | DOTCLK low-level period | 33 | - | ns | |
| | tCYCD | DOTCLK cycle time(18 bit) | 100 | - | ns | |
| | t _{rgb} , t _{rgb} | DOTCLK,HSYNC,VSYNC rise/fall time | - | 15 | ns | |
| VSYNC / HSYNC | tSYNCS | VSYNC/HSYNC setup time | 15 | - | ns | 6-bit bus RGB interface mode |
| | tSYNCH | VSYNC/HSYNC hold time | 15 | - | ns | |
| DE | tENS | DE setup time | 15 | - | ns | |
| | tENH | DE hold time | 15 | - | ns | |
| D[17:0] | tPOS | Data setup time | 15 | - | ns | |
| | tPDH | Data hold time | 15 | - | ns | |
| DOTCLK | PWDH | DOTCLK high-level pulse period | 25 | - | ns | |
| | PWDL | DOTCLK low-level pulse period | 25 | - | ns | |
| | tCYCD | DOTCLK cycle time | 50 | - | ns | |
| | t _{rgb} , t _{rgb} | DOTCLK,HSYNC,VSYNC rise/fall time | - | 15 | ns | |

10. Quality Assurance

10.1 Purpose

This standard for Quality Assurance assures the quality of LCD module products supplied to customer.

10.2 Standard for Quality Test

10.2.1 Sampling Plan:

GB2828.1-2012

Single sampling, normal inspection

10.2.2 Sampling Criteria:

Visual inspection: AQL 1.5%

Electrical functional: AQL 0.65%.

10.2.3 Reliability Test:

Detailed requirement refer to Reliability Test Specification.

10.3 Nonconforming Analysis & Disposition

10.3.1 Nonconforming analysis:

10.3.1.1 Customer should provide overall information of non-conforming sample for their complaints.

10.3.1.2 After receipt of detailed information from customer, the analysis of nonconforming parts usually should be finished in one week.

10.3.1.3 If cannot finish the analysis on time, customer will be notified with the progress status.

10.3.2 Disposition of nonconforming:

10.3.2.1 Non-conforming product over PPM level will be replaced.

10.3.2.2 The cause of non-conformance will be analyzed. Corrective action will be discussed and implemented.

10.4 Agreement Items

Shall negotiate with customer if the following situation occurs:

10.4.1 There is any discrepancy in standard of quality assurance.

10.4.2 Additional requirement to be added in product specification.

10.4.3 Any other special problem.


10.5 Standard of the Product Visual Inspection

10.5.1 Appearance inspection:

10.5.1.1 The inspection must be under illumination about 1000 – 1500 lx, and the distance of view must be at 30cm ± 2cm.

10.5.1.2 The viewing angle should be 45° from the vertical line without reflection light or follows customer's viewing angle specifications.

10.5.1.3 Definition of area: A Zone: Active Area, B Zone: Viewing Area,





10.5.2 Basic principle:





10.5.2.1 A set of sample to indicate the limit of acceptable quality level must be discussed by both us and customer when there is any dispute happened.



10.5.2.2 New item must be added on time when it is necessary.

10.6 Inspection Specification

| No. | Item | Criteria (Unit: mm) | | | | | | | | | | | | | | | | |
|--|---|---|------|------|----------|------------------|--|--------|-------------------------|--|---|-------------------------|--|---|---------------|--|---|--------------|
| 01 | Black / White spot Foreign material (Round type) Pinholes Stain Particles inside cell. (Minor defect) | <p>$\phi = (a + b) / 2$</p> | | | | | | | | | | | | | | | | |
| | | <table border="1"> <thead> <tr> <th>Size</th> <th>Area</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$\phi \leq 0.10$</td> <td></td> <td>Ignore</td> </tr> <tr> <td>$0.10 < \phi \leq 0.15$</td> <td></td> <td>2</td> </tr> <tr> <td>$0.15 < \phi \leq 0.25$</td> <td></td> <td>1</td> </tr> <tr> <td>$0.25 < \phi$</td> <td></td> <td>0</td> </tr> <tr> <td>Total</td> <td></td> <td>2 no include $\phi \leq 0.10$</td> </tr> </tbody> </table> | Size | Area | Acc. Qty | $\phi \leq 0.10$ | | Ignore | $0.10 < \phi \leq 0.15$ | | 2 | $0.15 < \phi \leq 0.25$ | | 1 | $0.25 < \phi$ | | 0 | Total |
| Size | Area | Acc. Qty | | | | | | | | | | | | | | | | |
| $\phi \leq 0.10$ | | Ignore | | | | | | | | | | | | | | | | |
| $0.10 < \phi \leq 0.15$ | | 2 | | | | | | | | | | | | | | | | |
| $0.15 < \phi \leq 0.25$ | | 1 | | | | | | | | | | | | | | | | |
| $0.25 < \phi$ | | 0 | | | | | | | | | | | | | | | | |
| Total | | 2 no include $\phi \leq 0.10$ | | | | | | | | | | | | | | | | |
| Distance between 2 defects should more than 3mm apart. | | | | | | | | | | | | | | | | | | |

| 02 | Electrical Defect (Minor defect) | <table border="1"> <tr> <th></th> <th>Display Area</th> <th>Total</th> <th rowspan="3">Note1</th> </tr> <tr> <td>Bright dot</td> <td>0</td> <td>0</td> </tr> <tr> <td>Dark dot</td> <td>$N \leq 2$</td> <td>$N \leq 2$</td> </tr> <tr> <td>Total dot</td> <td>$N \leq 2$</td> <td>$N \leq 2$</td> <td rowspan="2">Note2</td> </tr> <tr> <td>Mura</td> <td colspan="2">Not visible through 5% ND filters.</td> </tr> </table> | | Display Area | Total | Note1 | Bright dot | 0 | 0 | Dark dot | $N \leq 2$ | $N \leq 2$ | Total dot | $N \leq 2$ | $N \leq 2$ | Note2 | Mura | Not visible through 5% ND filters. | |
|--------------|--|--|--------------|--------------|----------|-------|---------------|--------|--------------|----------------------|------------|--------------|----------------------|------------|------------|-----------|------|------------------------------------|--|
| | | | Display Area | Total | Note1 | | | | | | | | | | | | | | |
| Bright dot | 0 | 0 | | | | | | | | | | | | | | | | | |
| Dark dot | $N \leq 2$ | $N \leq 2$ | | | | | | | | | | | | | | | | | |
| Total dot | $N \leq 2$ | $N \leq 2$ | Note2 | | | | | | | | | | | | | | | | |
| Mura | Not visible through 5% ND filters. | | | | | | | | | | | | | | | | | | |
| | | <p>Remark:</p> <p>1. Bright dot caused by scratch and foreign object accords to item 1.</p> | | | | | | | | | | | | | | | | | |
| 03 | Black and White line Scratch Foreign material (Line type) (Minor defect) |  | | | | | | | | | | | | | | | | | |
| | | <table border="1"> <thead> <tr> <th>Length</th> <th>Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>/</td> <td>$W \leq 0.03$</td> <td>Ignore</td> </tr> <tr> <td>$L \leq 2.5$</td> <td>$0.03 < W \leq 0.05$</td> <td>3</td> </tr> <tr> <td>$L \leq 2.5$</td> <td>$0.05 < W \leq 0.10$</td> <td>2</td> </tr> <tr> <td>/</td> <td>$0.1 < W$</td> <td>0</td> </tr> <tr> <td colspan="2">Total</td> <td>3</td> </tr> </tbody> </table> | Length | Width | Acc. Qty | / | $W \leq 0.03$ | Ignore | $L \leq 2.5$ | $0.03 < W \leq 0.05$ | 3 | $L \leq 2.5$ | $0.05 < W \leq 0.10$ | 2 | / | $0.1 < W$ | 0 | Total | |
| Length | Width | Acc. Qty | | | | | | | | | | | | | | | | | |
| / | $W \leq 0.03$ | Ignore | | | | | | | | | | | | | | | | | |
| $L \leq 2.5$ | $0.03 < W \leq 0.05$ | 3 | | | | | | | | | | | | | | | | | |
| $L \leq 2.5$ | $0.05 < W \leq 0.10$ | 2 | | | | | | | | | | | | | | | | | |
| / | $0.1 < W$ | 0 | | | | | | | | | | | | | | | | | |
| Total | | 3 | | | | | | | | | | | | | | | | | |
| | | <p>Distance between 2 defects should more than 3mm apart. Scratches not viewable through the back of the display are acceptable.</p> | | | | | | | | | | | | | | | | | |
| 04 | Glass Crack (Minor defect) |  | | | | | | | | | | | | | | | | | |
| | | <p>Crack is potential to enlarge, any type is not allowed.</p> | | | | | | | | | | | | | | | | | |

| <p>05</p> | <p>Glass Chipping Pad Area: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c > 3.0, b < 1.0$</td> <td>1</td> </tr> <tr> <td>$c < 3.0, b < 1.0$</td> <td>3</td> </tr> <tr> <td colspan="2">$a < \text{Glass Thickness}$</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1 | $c < 3.0, b < 1.0$ | 3 | $a < \text{Glass Thickness}$ | | | |
|------------------------------|---|--|------------------|----------|--------------------|--------|------------------------------|---|------------------------------|---|------------------------------|--|
| Length and Width | Acc. Qty | | | | | | | | | | | |
| $c > 3.0, b < 1.0$ | 1 | | | | | | | | | | | |
| $c < 3.0, b < 1.0$ | 3 | | | | | | | | | | | |
| $a < \text{Glass Thickness}$ | | | | | | | | | | | | |
| <p>06</p> | <p>Glass Chipping Rear of Pad Area: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c > 3.0, b < 1.0$</td> <td>1</td> </tr> <tr> <td>$c < 3.0, b < 1.0$</td> <td>2</td> </tr> <tr> <td>$c < 3.0, b < 0.5$</td> <td>4</td> </tr> <tr> <td colspan="2">$a < \text{Glass Thickness}$</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1 | $c < 3.0, b < 1.0$ | 2 | $c < 3.0, b < 0.5$ | 4 | $a < \text{Glass Thickness}$ | |
| Length and Width | Acc. Qty | | | | | | | | | | | |
| $c > 3.0, b < 1.0$ | 1 | | | | | | | | | | | |
| $c < 3.0, b < 1.0$ | 2 | | | | | | | | | | | |
| $c < 3.0, b < 0.5$ | 4 | | | | | | | | | | | |
| $a < \text{Glass Thickness}$ | | | | | | | | | | | | |
| <p>07</p> | <p>Glass Chipping Except Pad Area: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c > 3.0, b < 1.0$</td> <td>1</td> </tr> <tr> <td>$c < 3.0, b < 1.0$</td> <td>2</td> </tr> <tr> <td>$c < 3.0, b < 0.5$</td> <td>4</td> </tr> <tr> <td colspan="2">$a < \text{Glass Thickness}$</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1 | $c < 3.0, b < 1.0$ | 2 | $c < 3.0, b < 0.5$ | 4 | $a < \text{Glass Thickness}$ | |
| Length and Width | Acc. Qty | | | | | | | | | | | |
| $c > 3.0, b < 1.0$ | 1 | | | | | | | | | | | |
| $c < 3.0, b < 1.0$ | 2 | | | | | | | | | | | |
| $c < 3.0, b < 0.5$ | 4 | | | | | | | | | | | |
| $a < \text{Glass Thickness}$ | | | | | | | | | | | | |
| <p>08</p> | <p>Glass Corner Chipping: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c < 3.0, b < 3.0$</td> <td>Ignore</td> </tr> <tr> <td colspan="2">$a < \text{Glass Thickness}$</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c < 3.0, b < 3.0$ | Ignore | $a < \text{Glass Thickness}$ | | | | | |
| Length and Width | Acc. Qty | | | | | | | | | | | |
| $c < 3.0, b < 3.0$ | Ignore | | | | | | | | | | | |
| $a < \text{Glass Thickness}$ | | | | | | | | | | | | |

| <p>09</p> | <p>Glass Burr: (Minor defect)</p>  | <table border="1" data-bbox="869 257 1340 347"> <thead> <tr> <th>Length</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$F < 1.0$</td> <td>Ignore</td> </tr> </tbody> </table> <p>Glass burr don't affect assemble and module dimension.</p> | Length | Acc. Qty | $F < 1.0$ | Ignore | | | | | | |
|----------------------------|--|---|----------|----------|---------------------|--------|----------------------------|---|----------------------------|---|------------------|------|
| Length | Acc. Qty | | | | | | | | | | | |
| $F < 1.0$ | Ignore | | | | | | | | | | | |
| <p>10</p> | <p>FPC Defect: (Minor defect)</p>  | <p>10.1 Dent, pinhole width $a < w/3$. (w: circuitry width.)</p> <p>10.2 Open circuit is unacceptable.</p> <p>10.3 No oxidation, contamination and distortion.</p> | | | | | | | | | | |
| <p>11</p> | <p>Bubble on Polarizer (Minor defect)</p> | <table border="1" data-bbox="742 1288 1212 1512"> <thead> <tr> <th>Diameter</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$\varphi \leq 0.20$</td> <td>Ignore</td> </tr> <tr> <td>$0.20 < \varphi \leq 0.30$</td> <td>4</td> </tr> <tr> <td>$0.30 < \varphi \leq 0.50$</td> <td>1</td> </tr> <tr> <td>$0.50 < \varphi$</td> <td>None</td> </tr> </tbody> </table> | Diameter | Acc. Qty | $\varphi \leq 0.20$ | Ignore | $0.20 < \varphi \leq 0.30$ | 4 | $0.30 < \varphi \leq 0.50$ | 1 | $0.50 < \varphi$ | None |
| Diameter | Acc. Qty | | | | | | | | | | | |
| $\varphi \leq 0.20$ | Ignore | | | | | | | | | | | |
| $0.20 < \varphi \leq 0.30$ | 4 | | | | | | | | | | | |
| $0.30 < \varphi \leq 0.50$ | 1 | | | | | | | | | | | |
| $0.50 < \varphi$ | None | | | | | | | | | | | |
| <p>12</p> | <p>Dent on Polarizer (Minor defect)</p> | <table border="1" data-bbox="742 1568 1212 1792"> <thead> <tr> <th>Diameter</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$\varphi \leq 0.20$</td> <td>Ignore</td> </tr> <tr> <td>$0.20 < \varphi \leq 0.30$</td> <td>4</td> </tr> <tr> <td>$0.30 < \varphi \leq 0.50$</td> <td>1</td> </tr> <tr> <td>$0.50 < \varphi$</td> <td>None</td> </tr> </tbody> </table> | Diameter | Acc. Qty | $\varphi \leq 0.20$ | Ignore | $0.20 < \varphi \leq 0.30$ | 4 | $0.30 < \varphi \leq 0.50$ | 1 | $0.50 < \varphi$ | None |
| Diameter | Acc. Qty | | | | | | | | | | | |
| $\varphi \leq 0.20$ | Ignore | | | | | | | | | | | |
| $0.20 < \varphi \leq 0.30$ | 4 | | | | | | | | | | | |
| $0.30 < \varphi \leq 0.50$ | 1 | | | | | | | | | | | |
| $0.50 < \varphi$ | None | | | | | | | | | | | |
| <p>13</p> | <p>Bezel</p> | <p>13.1 No rust, distortion on the Bezel.</p> <p>13.2 No visible fingerprints, stains or other contamination.</p> | | | | | | | | | | |

| | | |
|----|-------------------------------------|--|
| 14 | Touch Panel | <p>D: Diameter W: width L: length</p> <p>14.1 Spot: $D < 0.25$ is acceptable $0.25 \leq D \leq 0.4$</p> <p>2dots are acceptable and the distance between defects should more than 10 mm.</p> <p>$D > 0.4$ is unacceptable</p> <p>14.2 Dent: $D > 0.40$ is unacceptable</p> <p>14.3 Scratch: $W \leq 0.03$, $L \leq 10$ is acceptable, $0.03 < W \leq 0.10$, $L \leq 10$ is acceptable</p> <p>Distance between 2 defects should more than 10 mm. $W > 0.10$ is unacceptable.</p> |
| 15 | PCB | <p>15.1 No distortion or contamination on PCB terminals.</p> <p>15.2 All components on PCB must same as documented on the BOM/component layout.</p> <p>15.3 Follow IPC-A-600F.</p> |
| 16 | Soldering | Follow IPC-A-610C standard |
| 17 | Electrical Defect (Major defect) | <p>The below defects must be rejected.</p> <p>17.1 Missing vertical / horizontal segment,</p> <p>17.2 Abnormal Display.</p> <p>17.3 No function or no display.</p> <p>17.4 Current exceeds product specifications.</p> <p>17.5 LCD viewing angle defect.</p> <p>17.6 No Backlight.</p> <p>17.7 Dark Backlight.</p> <p>17.8 Touch Panel no function.</p> |

Remark: LCD Panel Broken shall be rejected. Defect out of LCD viewing area is acceptable.

10.7 Classification of Defects

10.7.1 Visual defects (Except no / wrong label) are treated as minor defect and electrical defect is major.

10.7.2 Two minor defects are equal to one major in lot sampling inspection.

10.8 Identification/marketing criteria

Any unit with illegible / wrong /double or no marking/ label shall be rejected.


10.9 Packaging

10.9.1 There should be no damage of the outside carton box, each packaging box should have one identical label.

10.9.2 Modules inside package box should have compliant mark.

10.9.3 All direct package materials shall offer ESD protection

Note1: Bright dot is defined as the defective area of the dot is larger than 50% of one sub-pixel area.



Bright dot: The bright dot size defect at black display pattern. It can be recognized by 2% transparency of filter when the distance between eyes and panel is 350mm±50mm.

Dark dot: Cyan, Magenta or Yellow dot size defect at white display pattern. It can be recognized by 5% transparency of filter when the distance between eyes and panel is 350mm±50mm.

Note2: Mura on display which appears darker / brighter against background brightness on parts of display area

11. Reliability Specification

| No | Item | Condition | Quantity | Criteria |
|----|-----------------------------|---|----------|------------------|
| 1 | High Temperature Operating | 70°C, 96Hrs | 2 | GB/T2423.2-2008 |
| 2 | Low Temperature Operating | -20°C, 96Hrs | 2 | GB/T2423.1-2008 |
| 3 | High Humidity | 50°C, 90%RH, 96Hrs | 2 | GB/T2423.3-2006 |
| 4 | High Temperature Storage | 80°C, 96Hrs | 2 | GB/T2423.2-2008 |
| 5 | Low Temperature Storage | -30°C, 96Hrs | 2 | GB/T2423.1-2008 |
| 6 | Thermal Cycling Test | -20°C, 60min~70°C, 60min, 20 cycles. | 2 | GB/T2423.22-2012 |
| 7 | Packing vibration | Frequency range:10Hz~50Hz Acceleration of gravity:5G X, Y, Z 30 min for each direction. | 2 | GB/T5170.14-2009 |
| 8 | Electrical Static Discharge | Air: ±8KV 150pF/330Ω 5 times Contact: ±4KV 150pF/330Ω 5 times | 2 | GB/T17626.2-2006 |
| 9 | Drop Test (Packaged) | Height:80 cm,1 corner, 3 edges, 6 surfaces. | 2 | GB/T2423.8-1995 |

Note1. No deflection cosmetic and operational function allowable.

Note2. Total current Consumption should be below double of initial value

12. Precautions and Warranty

12.1 Safety

12.1.1 The liquid crystal in the LCD is poisonous. Do not put it in your mouth. If the liquid crystal touches your skin or clothes, wash it off immediately using soap and water.

12.1.2 Since the liquid crystal cells are made of glass, do not apply strong impact on them. Handle with care.

12.2 Handling

12.2.1 Reverse and use within ratings in order to keep performance and prevent damage.

12.2.2 Do not wipe the polarizer with dry cloth, as it might cause scratch. If the surface of the LCD needs to be cleaned, wipe it swiftly with cotton or other soft cloth soaked with petroleum IPA, do not use other chemicals.

12.3 Storage

12.3.1 Do not store the LCD module beyond the specified temperature ranges.

12.4 Metal Pin (Apply to Products with Metal Pins)

12.4.1 Pins of LCD and Backlight

12.4.1.1 Solder tip can touch and press on the tip of Pin LEAD during the soldering

12.4.1.2 Recommended Soldering Conditions

Solder Type: Sn96.3~94-Ag3.3~4.3-Cu0.4~1.1



Maximum Solder Temperature: 370°C

Maximum Solder Time: 3s at the maximum temperature

Recommended Soldering Temp: 350±20°C

Typical Soldering Time: ≤3s

12.4.1.3 Solder Wetting



12.4.2 Pins of EL

12.4.2.1 Solder tip can touch and press on the tip of EL leads during soldering.

12.4.2.2 No Solder Paste on the soldering pad on the motherboard is recommended.

12.4.2.3 Recommended Soldering Conditions

Solder type: Nippon Alimit Leadfree SR-34, size 0.5mm

Recommended Solder Temperature: 270~290°C


Typical Soldering Time: ≤2s

Minimum solder distance from EL lamp (body):2.0mm


12.4.2.4 No horizontal press on the EL leads during soldering.

12.4.2.5 180° bend EL leads three times is not allowed.

12.4.2.6 Solder Wetting




Recommended




Not Recommended

12.4.2.7 The type of the solder iron:




Recommended



Not Recommended

12.4.2.8 Solder Pad



12.5 Operation

- 12.5.1 Do not drive LCD with DC voltage
- 12.5.2 Response time will increase below lower temperature
- 12.5.3 Display may change color with different temperature
- 12.5.4 Mechanical disturbance during operation, such as pressing on the display area, may cause the segments to appear “fractured”.



12.6 Static Electricity

- 12.6.1 CMOS LSIs are equipped in this unit, so care must be taken to avoid the electro-static charge, by ground human body, etc.
- 12.6.2 The normal static prevention measures should be observed for work clothes and benches.
- 12.6.3 The module should be kept into anti-static bags or other containers resistant to static for storage.

12.7 Limited Warranty

- 12.7.1 Our warranty liability is limited to repair and/or replacement. We will not be responsible for any consequential loss.
- 12.7.2 If possible, we suggest customer to use up all modules in six months. If the module storage time over twelve months, we suggest that recheck it before the module be used.
- 12.7.3 After the product shipped, any product quality issues must be feedback within three months, otherwise, we will not be responsible for the subsequent or consequential events.

13. Outline Drawing



NOTES:

1. Display Type: 2.3\"TFT
2. Viewing Direction: 6 O'CLOCK
3. Grayscale Inversion Direction: 12 O'CLOCK
4. Polarizer mode: Transmissive/Normal white / Anti-Glare
5. Operation Temperature: -20°C to +70°C
6. Storage Temperature: -30°C to +80°C
7. Driver/Controller IC: ILI9342C (Ilitek)
8. Logic Power Supply Voltage: 3.2 Volt (typ.)
9. Backlight: White, Lightguide (4LEDs, 80mA, 3.2Volt (typ.))
10. Brightness: 300cd/m² (typ.)
11. LED Lifetime: 30.000h (typ.)

* Unspecification tolerance are ± 0.2mm

| PIN | SYMBOL |
|-----|--------|
| 1 | NC |
| 2 | NC |
| 3 | D0 |
| 4 | D1 |
| 5 | D2 |
| 6 | D3 |
| 7 | D4 |
| 8 | D5 |
| 9 | DCLK |
| 10 | VSYNC |
| 11 | HSYNC |
| 12 | SCL |
| 13 | SDA |
| 14 | CS |
| 15 | VCC |
| 16 | GND |
| 17 | NC |
| 18 | LED_K |
| 19 | GND |
| 20 | LED_A |
| 21 | NC |
| 22 | NC |
| 23 | NC |
| 24 | C1M |
| 25 | C1P |
| 26 | NC |
| 27 | C2M |
| 28 | C2P |
| 29 | NC |
| 30 | C3M |
| 31 | C3P |
| 32 | VINT3 |
| 33 | VCAC |
| 34 | NC |
| 35 | VGH |
| 36 | C4M |
| 37 | C4P |
| 38 | VGL |
| 39 | NC |
| 40 | NC |