

DIODE(THREE PHASES BRIDGE TYPE)

DF60LA/LB80/160

TOP




Power Diode Module DF60LA/LB is designed for three phase full wave rectification, which has six diodes connected in a three phase bridge configuration. The mounting base of the module is electrically isolated from semiconductor elements for simple heatsink construction output DC current is 60Amp ($T_c=111^\circ C$) Repetitive peak reverse voltage is up to 1600V.

- $T_{jMAX}=150^\circ C$

- Isolated Mounting Base
(Applications)

AC. DC Motor Drive/AVR/Switching
—for three phase rectification



Unit : mm

($T_j=25^\circ C$ unless otherwise specified)

■ Maximum Ratings

Symbol	Item	Ratings		unit
		DF60LA/LB80	DF60LA/LB160	
V_{RRM}	Repetitive Peak Reverse Voltage	800	1600	V
V_{RSM}	Non-Repetitive Peak Reverse Voltage	960	1700	V

Symbol	Item	Conditions	Ratings	unit
I_D	Output Current (D.C.)	Three phase full wave, $T_c=111^\circ C$	60	A
I_{FSM}	Surge Forward Current	$\frac{1}{2}$ cycle, 50/60Hz, Peak value, non-repetitive	730/800	A
T_j	Operating Junction Temperature		-40 to +150	°C
T_{stg}	Storage Temperature		-40 to +125	°C
V_{iso}	Isolation Breakdown Voltage (R.M.S.)	A.C. 1minute	2500	V
I_{RRM}	Mounting torque	Mounting (M5) Recommended Value 1.5-2.5 (15-25)	2.7 (28)	N·m (kgf·cm)
	Terminal (M5)	Recommended Value 1.5-2.5 (15-25)	2.7 (28)	
Mass		Typical Value	100	g

■ Electrical Characteristics

Symbol	Item	Conditions	Ratings	unit
I_{RRM}	Repetitive Peak Reverse Current, max.	$T_j=150^\circ C$, $V_R=V_{RRM}$	8	mA
V_{FM}	Forward Voltage Drop, max.	$I_F=60A$, Inst. measurement	1.30	V
$R_{th(j-c)}$	Thermal Impedance, max.	Junction to case	0.25	°C/W

