"#" indicates a package specification code.

REACH















Last Time Buy Date: 30 Sep 2019

Date of discontinuation: 30 Sep 2020

7.0 mm max.

9.5 ±2.0mm

0.65 ±0.05mm

4.0mm max.

< List of part numbers with package codes > DHRB34A101M2BB


## Shape

Tsize

Lead spacing F

Lead diameter d

Paint dripping e





| Packaging | Specifications  | Minimum quantity |
|-----------|-----------------|------------------|
| В         | Packing in bulk | 200              |

## Specifications

| Capacitance                                      | 100pF ±20%   |
|--|--------------|
| Rated voltage                                    | 10kVdc       |
| Temperature characteristics (complied standard)  | B(JIS)       |
| Capacitance change rate                          | ±10%         |
| Temperature range of temperature characteristics | -25 to 85°C  |
| Operating temperature range                      | -25 to 100°C |

1 of 1



<sup>1.</sup> This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



<sup>2.</sup> This datasheet has only typical specifications because there is no space for detailed specifications.