"#" indicates a package specification code.


















Last Time Buy Date: 30 Sep 2019

Date of discontinuation: 30 Sep 2020

< List of part numbers with package codes > DHRB34B681M2BB

Shape



4.0 max 4.0 max 1.0 max 1.0 max	
L size or outer diameter D (mm) 14.0 mm	ı max.
T size 7.5 mm r	max.
Lead spacing F 9.5 ±2.0	mm
Lead diameter d 0.65 ±0.0	05mm
Paint dripping e 4.0mm n	nax.

References

Packaging	Specifications	Minimum quantity
В	Packing in bulk	50

Specifications

Capacitance	680pF ±20%
Rated voltage	12kVdc
Temperature characteristics (complied standard)	B(JIS)
Capacitance change rate	±10%
Temperature range of temperature characteristics	-25 to 85°C
Operating temperature range	-25 to 100°C

1 of 1



^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

