

PRELIMINARY DATA SHEET



Schottky Diode Quad Mixer Chips Supplied on Film Frame

Features

- Designed for high-performance, double-balanced mixers
- Three barrier heights available
- Schottky diodes supplied 100% tested, sawn, mounted on film frame
- Low cost
- Available lead (Pb)-free, RoHS-compliant, and Green

Description

This Skyworks family of Si Schottky diodes are configured as bridge quads intended for use in double-balanced mixers. Each bridge quad die is comprised of four Schottky junctions. There are three barrier heights available: DMF4102-099 is composed of low-barrier diodes, which can be driven with low-power local oscillator signals; DME4101-099 is composed of medium-barrier diodes, for applications in which moderate-power local oscillator signals are available; and, DMJ4103-099 is composed of high-barrier diodes for applications that require very low distortion performance and have higher local oscillator power available. These bridge quads are 100% tested, sawn and supplied on film frame in wafer quantities.



Electrical and Physical Specifications

Absolute maximum ratings for the Schottky diodes are provided in Table 1. Electrical specifications are noted in Table 2. The chip dimensions are shown in Table 3. SPICE model parameters are defined in Table 4.

Typical performance data is indicated in Figure 1. The outline drawing is shown in Figure 2.



Skyworks Green™ products are compliant with all applicable legislation and are halogen-free. For additional information, refer to *Skyworks Definition of Green™*, document number SQ04-0074.

Table 1. Absolute Maximum Ratings (Note 1)

Parameter	Symbol	Minimum	Typical	Maximum	Units
Forward current	I _F		75		mA
Power dissipation @ 25 °C at the base of the chip	P		75		mW/per junction
Storage temperature	T _{STG}	-65		+200	°C
Operating temperature	T _{OP}	-65		+150	°C
Electrostatic discharge: Human Body Model (HBM), Class 0	ESD			<250	V

Note 1: Exposure to maximum rating conditions for extended periods may reduce device reliability. There is no damage to device with only one parameter set at the limit and all other parameters set at or below their nominal value. Exceeding any of the limits listed here may result in permanent damage to the device.

CAUTION: Although this device is designed to be as robust as possible, electrostatic discharge (ESD) can damage this device. This device must be protected at all times from ESD. Static charges may easily produce potentials of several kilovolts on the human body or equipment, which can discharge without detection. Industry-standard ESD precautions should be used at all times.

Table 2. Electrical Specifications at 25 °C (Notes 1 and 2)

Part Number	V _B I _R = 10 μA (V)	C _J V _R = 0 V, f = 1 MHz (pF)		V _F @ I _F = 1 mA (mV)		ΔV _F @ I _F = 1 mA (mV)	R _T (Note 3) I _F = 10 mA (Ω)
	Min	Min	Max	Min	Max	Max	Max
DMF4102-099	2	0.15	0.30	250	310	10	14
DME4101-099	3	0.15	0.30	325	425	10	14
DMJ4103-099	4	0.15	0.30	550	650	10	14

Note 1: The above Schottky diode chips are processed on 100 mm silicon wafers, 100% DC tested, sawn and shipped on 6" film frame hoops. Electrical rejects are identified with black ink.

Note 2: All parameters are based upon a single junction.

Note 3: R_T is the slope resistance.

Table 3. Chip Dimensions

Part Number	Quantity of Good Diodes Per Wafer		Bonding Pad Nominal (In.)	Chip Size Nominal (In.)	Chip Height Nominal (In.)
	Min.	Nom.			
DMF4102-099	27,000	30,000	0.0035 ± 0.0005	0.0150 ± 0.001	0.006 ± 0.001
DME4101-099	23,000	28,000	0.0035 ± 0.0005	0.0150 ± 0.001	0.006 ± 0.001
DMJ4103-099	27,000	30,000	0.0035 ± 0.0005	0.0150 ± 0.001	0.006 ± 0.001

Table 4. SPICE Model Parameters (Per Junction)

Part Number Prefix	I _s (A)	R _s (Ω)	N	t _r (s)	C _{Jo} (pF)	M	E _g (eV)	V _J (V)	XTI	Fc	B _v (V)	I _{BV} (A)
DMF4102	1.1 x 10 ⁻⁷	6	1.04	1 x 10 ⁻¹¹	0.22	0.32	0.69	0.495	2	0.5	2	1 x 10 ⁻⁵
DME4101	2.4 x 10 ⁻⁹	6	1.04	1 x 10 ⁻¹¹	0.20	0.37	0.69	0.595	2	0.5	3	1 x 10 ⁻⁵
DMJ4103	8.5 x 10 ⁻¹³	6	1.04	1 x 10 ⁻¹¹	0.20	0.42	0.69	0.800	2	0.5	4	1 x 10 ⁻⁵




Figure 1. Typical DC Characteristic at 25 °C




Figure 2. Outline Drawing

Wafer on Film

Figure 3 illustrates the wafer on film.




Figure 3. Wafer on Film

Wafer Film Frame Description

- Wafer on nitto tape
- Color: light blue
- Thickness: 2.2 ~ 3.0 mils
- Tensile strength: 6.6 (lbs. in width)
- Ring material: plastic

Copyright © 2014 Skyworks Solutions, Inc. All Rights Reserved.

Information in this document is provided in connection with Skyworks Solutions, Inc. ("Skyworks") products or services. These materials, including the information contained herein, are provided by Skyworks as a service to its customers and may be used for informational purposes only by the customer. Skyworks assumes no responsibility for errors or omissions in these materials or the information contained herein. Skyworks may change its documentation, products, services, specifications or product descriptions at any time, without notice. Skyworks makes no commitment to update the materials or information and shall have no responsibility whatsoever for conflicts, incompatibilities, or other difficulties arising from any future changes.

No license, whether express, implied, by estoppel or otherwise, is granted to any intellectual property rights by this document. Skyworks assumes no liability for any materials, products or information provided hereunder, including the sale, distribution, reproduction or use of Skyworks products, information or materials, except as may be provided in Skyworks Terms and Conditions of Sale.

THE MATERIALS, PRODUCTS AND INFORMATION ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, WHETHER EXPRESS, IMPLIED, STATUTORY, OR OTHERWISE, INCLUDING FITNESS FOR A PARTICULAR PURPOSE OR USE, MERCHANTABILITY, PERFORMANCE, QUALITY OR NON-INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT; ALL SUCH WARRANTIES ARE HEREBY EXPRESSLY DISCLAIMED. SKYWORKS DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. SKYWORKS SHALL NOT BE LIABLE FOR ANY DAMAGES, INCLUDING BUT NOT LIMITED TO ANY SPECIAL, INDIRECT, INCIDENTAL, STATUTORY, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS THAT MAY RESULT FROM THE USE OF THE MATERIALS OR INFORMATION, WHETHER OR NOT THE RECIPIENT OF MATERIALS HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Skyworks products are not intended for use in medical, lifesaving or life-sustaining applications, or other equipment in which the failure of the Skyworks products could lead to personal injury, death, physical or environmental damage. Skyworks customers using or selling Skyworks products for use in such applications do so at their own risk and agree to fully indemnify Skyworks for any damages resulting from such improper use or sale.

Customers are responsible for their products and applications using Skyworks products, which may deviate from published specifications as a result of design defects, errors, or operation of products outside of published parameters or design specifications. Customers should include design and operating safeguards to minimize these and other risks. Skyworks assumes no liability for applications assistance, customer product design, or damage to any equipment resulting from the use of Skyworks products outside of stated published specifications or parameters.

Skyworks and the Skyworks symbol are trademarks or registered trademarks of Skyworks Solutions, Inc., in the United States and other countries. Third-party brands and names are for identification purposes only, and are the property of their respective owners. Additional information, including relevant terms and conditions, posted at www.skyworksinc.com, are incorporated by reference.