

Linear Systems replaces discontinued Siliconix DPAD5

The DPAD5 is a low leakage Monolithic Dual Pico-Amp Diode

The DPAD5 extremely low-leakage monolithic dual diode provides a superior alternative to conventional diode technology when reverse current (leakage) must be minimized. In addition the monolithic dual construction allows excellent capacitance matching per diode. The DPAD5 features a leakage current of ≤ 5 pA and is well suited for use in applications such as input protection for operational amplifiers.

DPAD5 Benefits:

- Negligible Circuit Leakage Contribution
- Circuit "Transparent" Except to Shunt High-Frequency Spikes
- Simplicity of Operation

DPAD5 Applications:

- Op Amp Input Protection
- Multiplexer Overvoltage Protection

FEATURES

DIRECT REPLACEMENT FOR SILICONIX DPAD5

HIGH ON ISOLATION	20fA
EXCELLENT CAPACITANCE MATCHING	$\Delta C_R \leq 0.5$ pF
ULTRALOW LEAKAGE	≤ 5 pA
REVERSE BREAKDOWN VOLTAGE	$BV_R \geq -45$ V
REVERSE CAPACITANCE	$C_{RSS} \leq 2.0$ pF

ABSOLUTE MAXIMUM RATINGS

@ 25°C (unless otherwise noted)

Maximum Temperatures

Storage Temperature	-65°C to +150°C
Operating Junction Temperature	-55°C to +135°C

Maximum Power Dissipation

Continuous Power Dissipation	500mW
------------------------------	-------

MAXIMUM CURRENT

Forward Current (Note 1)	50mA
--------------------------	------

DPAD5 ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTICS	MIN.	TYP.	MAX.	UNITS	CONDITIONS
BV_R	Reverse Breakdown Voltage	-45	--	--	V	$I_R = -1$ μ A
V_F	Forward Voltage	--	0.8	1.5	V	$I_F = 1$ mA
C_{RSS}	Total Reverse Capacitance	--	--	2.0	pF	$V_R = -5$ V, $f = 1$ MHz
$ C_{R1} - C_{R2} $	Differential Capacitance (ΔC_R)	--	--	0.5	pF	$V_{R1} = V_{R2} = -5$ V, $f = 1$ MHz
I_R	Maximum Reverse Leakage Current	--	--	-5	pA	$V_R = -20$ V

Notes:

1. Absolute maximum ratings are limiting values above which DPAD5 serviceability may be impaired.

Available Packages:

DPAD5 in TO-72
DPAD5 available as bare die

Please contact Micross for full package and die dimensions



Micross Components Europe

Tel: +44 1603 788967
Email: chipcomponents@micross.com
Web: <http://www.micross.com/distribution>

TO-72 (Bottom View)

