

Ultra fast Rectifier

DPG120C300QB

FEATURES



- With TO-3PN packaging
- Low thermal resistance
- Low leakage current
- Super high speed switching
- High reliability by planer design
- Very low on-state loss
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Switching power supply
- Active PFC in air conditioner
- Interleaved PFC topology in switched-mode power supplies

ABSOLUTE MAXIMUM RATINGS(T_a=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
VRRM VRWM VR	Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage $t_w=500ns; duty=1/40$	300	V
IF(AV)	Average Rectified Forward Current @T _c =96°C; Square Wave; Duty=1/2	60	A
IFSM	Nonrepetitive Peak Surge Current 10ms single half sine-wave superimposed on rated load conditions	550	A
TJ	Junction Temperature	-40~150	°C
Tstg	Storage Temperature Range	-40~150	°C



DIM	mm	
	MIN	MAX
A	19.60	20.30
B	15.50	15.70
C	4.70	4.90
D	0.90	1.10
E	1.90	2.10
F	3.40	3.60
G	2.90	3.20
H	3.20	3.40
J	0.595	0.605
K	19.80	20.70
L	1.90	2.20
N	10.89	10.91
Q	4.90	5.10
R	3.35	3.45
S	1.995	2.100
U	5.90	6.20
Y	9.90	10.10

Ultra fast Rectifier**DPG120C300QB****THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-mb}$	Thermal Resistance, Junction to Mounting Base	0.25	°C/W

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$) (Pulse Test: Pulse Width=300 μ s, Duty Cycle \leq 2%)

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT
V_F	Maximum Instantaneous Forward Voltage	$I_F=60\text{A}; T_c=25^\circ\text{C}$ $I_F=60\text{A}; T_c=150^\circ\text{C}$ $I_F=120\text{A}; T_c=25^\circ\text{C}$ $I_F=120\text{A}; T_c=150^\circ\text{C}$	1.4 1.1 1.72 1.45	V
I_R	Maximum Instantaneous Reverse Current	$V_R=V_{RWM}; T_c=25^\circ\text{C}$ $V_R=V_{RWM}; T_c=150^\circ\text{C}$	1 350	μ A
t_{rr}	Maximum Reverse Recovery Time	$I_F=60\text{A}; -diF/dt=200\text{A}/\mu\text{s}; V_R=100\text{V}$	35	ns

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.