

DPS-200PB-143 Series

125 (W) x 63.5 (H) x 100 (L) mm



CE BSMI

CB



cULus



FEATURES

- Complies with SFX 12V V2.1
- Remote On/Off
- High Reliability
- Low Acoustic Noise
- Built-in EMI Filter
- Meets IEC 60950: 1999/UL 60950 3rd Edition
- TTL Compatible Power Good Signal
- All Outputs SELV (Safety Extra Low Voltage)
- Fan Speed Control Function Inside
- Optional PFC Circuit

ENVIRONMENTAL

- MTBF: >100,000 hours at Max. Load, 115Vac and 25°C ambient conditions
- Dielectric Withstand: www.DataSheet4U.com
Input to Output: 2100Vac for 1 sec
Input to Frame Ground: 2100Vac for 1 sec
- ESD: IEC 61000-4-2
- Surge: IEC 61000-4-5
- Harmonic: IEC 61000-3-2 Class D

ELECTRICAL SPECIFICATIONS

Input

- Input Range 90-135/180-265Vac, Switch-Select
- Frequency 47-63Hz
- Input Current 5A @ 115Vac; 2.5A @ 230Vac
- Efficiency >68% @ Max. Load, Nominal Line
- EMI/RFI FCC Part 15 Class B
CISPR 22 Class B

Output

- Maximum Power 200 Watts
- Holdup Time >17mS @ Max. Load, Nominal Line
- Rise Time 0.2mS ~ 20mS
- Leakage Current <0.75mA @ 250Vac
- Overvoltage Protection: +3.3V, +5V, +12V, -12V
- Overcurrent Protection: <240VA
- Short-Circuit Protection: Latch off all main outputs reset by cycling On/Off control or AC power.
- Power Good Signal: TTL/CMOS compatible on delay 100mS to 500mS, off delay 1mS minimum.

Output	Voltage	Regulation	Minimum Load	Maximum Load	Peak Load	Ripple & Noise Vp-p
V1	+3.3V	+/-5%	0.5A	16.7A	-	50mV
V2	+5V	+/-5%	0.5A	16.0A	-	50mV
V3	+12V	+/-5%	0.5A	10.0A	13.0A	120mV
V4	-12V	+/-10%	0A	0.3A	-	120mV
V5	+5Vsb	+/-5%	0A	2.0A	-	50mV

1. Peak-to-peak with 20MHz bandwidth and 10 μ F in parallel with a 0.1 μ F capacitor.
2. Total combined power on +3.3V & +5V rails are 110W maximum.
3. Total combined current on +3.3V, +5V & +12V rails are 186W maximum.

All specifications are subject to change without prior notice.

DELTA ELECTRONICS, INC.
3, TUNG YUAN ROAD,
CHUNGLI INDUSTRIAL ZONE
TAOYUAN SHIEN, TAIWAN, R.O.C.
TEL : 886-3-4526107
FAX : 886-3-4527314
mail: powersales@delta.com.tw

DELTA PRODUCTS CORPORATION
4405 CUSHING PARKWAY
FREMONT, CA 94538, U.S.A.
TEL : 1-510-668-5100
FAX : 1-510-668-0680

DELTA ELECTRONICS (JAPAN) INC.
DELTA SHIBADAIMON BLDG.
2-1-14 SHIBADAIMON, MINATO-KU,
TOKYO, 105-0012, JAPAN
TEL : 81-3-5733-1111
FAX : 81-3-5733-1211

DELTA ELECTRONICS EUROPE LTD.
2 YOUNG PLACE
KELVIN INDUSTRIAL ESTATE
EAST KILBRIDE, GLASGOW G75 0TD, U.K.
TEL : 44-1355-588888
FAX : 44-1355-588889