



DISH AUTOMOTIVE RECTIFIER

DR351 THRU DR356
DRS351 THRU DRS356

VOLTAGE RANGE 100 to 400 Volts
CURRENT 35.0 Amperes


TECHNICAL SPECIFICATION:

FEATURES

- Low Leakage
- Low forward voltage drop
- High current capability
- High forward surge current capacity
- Glass passivated chip

MECHANICAL DATA

- Technology: vacuum soldered
- Case: Copper case
- Polarity: As marked of case bottom
- Lead: Plated Ni lead, solderable per MIL-STD-202E method 208C
- Weight: 0.032 ounces, 0.9 grams (DRS)
0.035 ounces, 1.0 grams (DR)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60HZ, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	DR351 DRS351	DR352 DRS352	DR353 DRS353	DR354 DRS354	DR356 DRS356	UNIT
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	100	200	300	400	600	Volts
Maximum RMS Voltage	V _{RMS}	70	140	210	280	420	Volts
Maximum DC Blocking Voltage	V _{DC}	100	200	300	400	600	Volts
Maximum Average Forward Rectified Current, At Tc=105°C	I _O	35					Amps
Peak Forward Surge Current 3.3mS single half sine wave superimposed on Rated load (JEDEC method)	I _{FSM}	500					Amps
Rating for fusing (t<8.3ms)	I ² t	1038					A ² S
Maximum instantaneous Forward Voltage at 100A	V _F	1.08					Volts
Maximum DC Reverse Current at Rated TA=25°C DC Blocking Voltage TA=100°C	I _R	5.0					UA
		450					
Typical Thermal Resistance	R _{θJC}	0.8					°C/W
Operating and Storage Temperature Range	T _J ,T _{STG}	(-65 to +175)					°C

Notes:

1. Enough heatsink must be considered in application.



DISH AUTOMOTIVE RECTIFIER


DR351 THRU DR356
DRS351 THRU DRS356

VOLTAGE RANGE 100 to 400 Volts
CURRENT 35.0 Amperes


RATINGS AND CHARACTERISTIC CURVES

DR351 THRU DR356
DRS351 THRU DRS356


F1G.1 TYPICAL FORWARD CURRENT
DERATING CURVE



F1G.2 MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT



F1G.3 TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTICS



F1G.4 FORWARD POWER DISSIPATION

