

Flatpack Two-Way Power Divider

5 - 1000 MHz

DS-327

V2.00

Features

- Broadband, IN Phase Divider
- Low Loss - 0.3 dB Typical
- Amplitude Balance - 0.05 dB Typical

Guaranteed Specifications *

(From -55°C to +85°C)

Frequency Range	5-500 MHz	5-1000 MHz
Insertion Loss (Less coupling)	5-500 MHz	0.5 dB Max
	500-1000 MHz	1.0 dB Max
Isolation	5-500 MHz	25 dB Min
	500-1000 MHz	20 dB Min
Amplitude Balance	5-1000 MHz	0.2 dB Max
Phase Balance	5-500 MHz	2° Max
	500-1000 MHz	3° Max
VSWR (All Ports)	10-500 MHz	1.3:1 Max
	5-1000 MHz	1.5:1 Max

Operating Characteristics


Impedance	50 Ohms Nominal
Maximum Power Rating or Input Power	1 Watt Max
Internal Load Dissipation	0.05 Watt Max
Environmental	MIL-STD-883 screening available.
Pin Configuration	Σ; P1, Output 'C'; P4, Output 'D'; P8 Case and all other pins ground.

* All specifications apply with 50 ohm source and load impedance.

Ordering Information




Model No.	Package
DS-327 PIN	Flatpack

FP-2



Dimensions in () are in mm.
Unless Otherwise Noted: .xxx = ± 0.010 (.xx = ± 0.25)
.xx = ± 0.02 (.x = ± 0.5)
WEIGHT (APPROX.): 0.09 OUNCES 2.5 GRAMS

Typical Performance



Specifications Subject to Change Without Notice.

M/A-COM, Inc.

North America: Tel. (800) 366-2266 ■ Asia/Pacific: Tel. +81 (03) 3226-1671 ■ Europe: Tel. +44 (1344) 869 595
Fax (800) 618-8883 Fax +81 (03) 3226-1451 Fax +44 (1344) 300 020