



DVWR2800T Series

HIGH RELIABILITY HYBRID DC-DC CONVERTERS

DESCRIPTION

The DVWR series of high reliability DC-DC converters is operable over the full military (-55 °C to +125 °C) temperature range with no power derating. Unique to the DVWR series are robust and effective input and output filters which provide dramatically reduced input and output noise performance when compared to other manufacturers competing devices. Operating at a nominal fixed frequency of 325 kHz, per stage, these regulated, isolated units utilize a high speed magnetic feedback design and well controlled undervoltage lockout circuitry to eliminate slow start-up problems.

These converters are designed and manufactured in a facility qualified to ISO9001 and certified to MIL-PRF-38534 and MIL-STD-883.

This product may incorporate one or more of the following U.S. patents:

5,784,266
5,790,389
5,963,438
5,999,433
6,005,780
6,084,792
6,118,673

FEATURES

- High Reliability
- Very Low Output Noise
- Wide Input Voltage Range: 15 to 50 Volts per MIL-STD-704
- Up to 25 Watts Output Power
- Fault Tolerant Magnetic Feedback Circuit
- NO Use of Optoisolators
- Undervoltage Lockout
- Indefinite Short Circuit Protection
- Current Limit Protection
- Industry Standard Pinout
- High Input Transient Voltage: 80 Volts for 1 sec per MIL-STD-704A
- Precision Seam Welded Hermetic Package
- High Power Density: > 28 W/in³
- Custom Versions Available
- Additional Environmental Screening Available
- Meets MIL-STD-461C and MIL-STD-461D EMC Requirements When Used With a DVMC28 EMI Filter
- Flanged and Non-flanged Versions Available.
- MIL-PRF-38534 Element Evaluated Components




Figure 1 – DVWR2800T DC-DC Converter
(Exact marking may differ from that shown)

SPECIFICATIONS (T_{CASE} = -55°C to +125°C, V_{IN} = +28V ± 5%, Full Load⁵, Unless Otherwise Specified)

ABSOLUTE MAXIMUM RATINGS

Input Voltage (Continuous)	50 V _{DC}	Junction Temperature Rise to Case	+15°C
Input Voltage (Transient, 1 second)	80 Volts	Storage Temperature	-65°C to +150°C
Output Power	25 Watts	Lead Solder Temperature (10 seconds)	270°C
Power Dissipation (Full Load, T _{CASE} = +125°C)	8 Watts	Weight (Maximum) (Un-Flanged / Flanged)	(54 / 58) Grams
ESD Rating per MIL-PRF-38534	3B		

Parameter		Conditions	DVWR283R312T			DVWR283R315T			Units
			Min	Typ	Max	Min	Typ	Max	
STATIC									
INPUT Voltage		Continuous	15	28	50	15	28	50	V
		Transient, 1 sec ⁴	-	-	80	-	-	80	V
Current		Inhibited	-	3.5	5	-	3.5	5	mA
		No Load	-	20	60	-	20	60	mA
Ripple Current		Full Load ⁵ , 20Hz to 10MHz	-	20	50	-	20	50	mA _{p-p}
Inhibit Pin Input ⁴			0	-	1.5	0	-	1.5	V
Inhibit Pin Open Circuit Voltage ⁴			13	15	17	13	15	17	V
UVLO Turn On			10.5	-	14.5	10.5	-	14.5	V
UVLO Turn Off ⁴			11.0	-	14.5	11.0	-	14.5	V
OUTPUT Voltage		V _{MAIN} +V _{AUX} -V _{AUX} T _{CASE} = 25 °C	3.25	3.30	3.35	3.25	3.30	3.35	V
			11.88	12.0	12.12	14.85	15.0	15.15	V
			11.76	12.0	12.24	14.70	15.0	15.30	V
		V _{MAIN} +V _{AUX} -V _{AUX} T _{CASE} = -55 °C to +125 °C	3.20	3.30	3.40	3.20	3.30	3.40	V
			11.64	12.0	12.36	14.55	15.0	15.45	V
			11.52	12.0	12.48	14.40	15.0	15.60	V
Power ⁴		Total	0	-	25	0	-	25	W
		V _{MAIN}	0	-	10	0	-	10	W
		±V _{AUX} ⁶	0	-	15	0	-	15	W
Current ³		V _{MAIN}	0	-	3.03	0	-	3.03	A
		±V _{AUX}	0	-	0.87	0	-	0.70	A
Ripple Voltage		V _{MAIN} ±V _{AUX} Full Load ⁵ , 20Hz to 10MHz	-	20	60	-	20	60	mV _{p-p}
			-	40	100	-	40	100	mV _{p-p}
Line Regulation		V _{MAIN} +V _{AUX} -V _{AUX} V _{IN} = 15V to 50V	-	10	25	-	10	25	mV
			-	15	50	-	15	50	mV
			-	20	100	-	20	100	mV
Load Regulation		V _{MAIN} +V _{AUX} -V _{AUX} No Load to Full Load ^{5,8}	-	10	25	-	10	25	mV
			-	10	50	-	10	50	mV
			-	50	250	-	50	250	mV
Cross Regulation		±V _{AUX} +V _{OUT} = 30%, -V _{OUT} = 70% +V _{OUT} = 70%, -V _{OUT} = 30%	-	-	550	-	-	550	mV
EFFICIENCY		Full Load ⁵	74	79	-	75	80	-	%
LOAD FAULT POWER DISSIPATION		Overload ⁴	-	-	15	-	-	15	W
		Short Circuit	-	-	10	-	-	10	W
CAPACITIVE LOAD ⁴			-	-	500	-	-	500	μF
SWITCHING FREQUENCY			550	650	700	550	650	700	kHz
SYNCHRONIZATION FREQUENCY ⁷			700	750	800	700	750	800	kHz
ISOLATION		500 V _{DC} , T _{CASE} = 25 °C	100	-	-	100	-	-	MΩ
MTBF (MIL-HDBK-217F)		AIF @ T _C = 55 °C	-	307	-	-	307	-	kHrs

SPECIFICATIONS (T_{CASE} = -55°C to +125°C, V_{IN} = +28V ± 5%, Full Load⁵, Unless Otherwise Specified)

ABSOLUTE MAXIMUM RATINGS

Input Voltage (Continuous)	50 V _{DC}	Junction Temperature Rise to Case	+15°C
Input Voltage (Transient, 1 second)	80 Volts	Storage Temperature	-65°C to +150°C
Output Power	25 Watts	Lead Solder Temperature (10 seconds)	270°C
Power Dissipation (Full Load, T _{CASE} = +125°C)	8 Watts	Weight (Maximum) (Un-Flanged / Flanged)	(54 / 58) Grams
ESD Rating per MIL-PRF-38534	3B		

Parameter	Conditions	DVWR283R312T			DVWR283R315T			Units	
		Min	Typ	Max	Min	Typ	Max		
DYNAMIC									
Load Step Output Transient	V _{MAIN} ±V _{AUX}	Half Load to Full Load	-	150	300	-	150	300	mV _{PK}
			-	500	700	-	500	700	mV _{PK}
Load Step Recovery ²	V _{MAIN} ±V _{AUX}		-	200	400	-	200	400	μSec
			-	200	400	-	200	400	μSec
Line Step Output Transient ⁴	V _{MAIN} ±V _{AUX}	V _{IN} = 15V to 50V	-	80	200	-	80	200	mV _{PK}
			-	300	500	-	300	500	mV _{PK}
Line Step Recovery ^{2, 4}	V _{MAIN} ±V _{AUX}		-	200	400	-	200	400	μSec
			-	200	400	-	200	400	μSec
Turn On Delay		V _{IN} = 0V to 28V	-	-	20	-	-	20	mSec
Turn On Overshoot	V _{MAIN} ±V _{AUX}		-	-	15	-	-	15	mV _{PK}
			-	-	50	-	-	50	mV _{PK}

- Notes:
1. This note intentionally not used.
 2. Time for output voltage to settle within 1% of its nominal value.
 3. Derate linearly to 0 at 135°C.
 4. Verified by qualification testing.
 5. 10W on V_{MAIN} and 15W on ±V_{AUX}.
 6. Up to 70% of the total auxiliary power or current can be drawn from either of the auxiliary outputs.
 7. Synchronization is TTL signal with V_{SYNC MAX} = 6V.
 8. -V_{AUX} is 5% Load to Full Load at -55°C.

BLOCK DIAGRAM




Figure 2

CONNECTION DIAGRAM




Figure 3

INHIBIT DRIVE CONNECTION DIAGRAMS




Figure 4 – Internal Inhibit Circuit and Recommended Drive
(Shown with optional capacitor for turn-on delay)




Figure 5 – Isolated Inhibit Drive
(Shown with optional capacitor for turn-on delay)

EMI FILTER HOOKUP DIAGRAM




Figure 6 – Converter with EMI Filter

EFFICIENCY PERFORMANCE CURVES ($T_{CASE} = 25^{\circ}C$)





Figure 7 – DVWR283R312T
Efficiency (%) vs. Output Power (W)




Figure 8 – DVWR283R315T
Efficiency (%) vs. Output Power (W)

EMI PERFORMANCE CURVES

($T_{CASE} = 25^{\circ}\text{C}$, $V_{IN} = +28\text{V} \pm 5\%$, Full Load, Unless Otherwise Specified)




Figure 9 – DVWR2800T without EMI Filter





Figure 10 – DVWR2800T with EMI Filter


PACKAGE SPECIFICATIONS (NON-FLANGED, SEAM SEAL)



Pin	Function	Pin	Function
1	28V IN	6	CASE
2	+V MAIN	7	CASE
3	OUT COM	8	INHIBIT
4	-V AUX	9	SYNC
5	+V AUX	10	IN COM

Figure 11 – Non-Flanged, Seam Seal Package and Pinout

PACKAGE SPECIFICATIONS (FLANGED, SEAM SEAL)



Pin	Function	Pin	Function
1	28V IN	6	CASE
2	+V MAIN	7	CASE
3	OUT COM	8	INHIBIT
4	-V AUX	9	SYNC
5	+V AUX	10	IN COM

Figure 12 – Flanged, Seam Seal Package and Pinout

PACKAGE PIN DESCRIPTION

Pin	Function	Description
1	28V IN	Positive Input Voltage Connection
2	+V MAIN	Positive Main Output Voltage Connection
3	OUT COM	Output Common Connection
4	-V AUX	Negative Auxiliary Output Voltage Connection
5	+V AUX	Positive Auxiliary Output Voltage Connection
6	CASE	Case Connection
7	CASE	Case Connection
8	INHIBIT	Logic Low = Disabled Output. Connecting the inhibit pin to input common causes converter shutdown. Logic High = Enabled Output. Unconnected or open collector TTL.
9	SYNC	Synchronization Signal
10	IN COM	Input Common Connection

ENVIRONMENTAL SCREENING (100% Tested Per MIL-STD-883 as referenced to MIL-PRF-38534)

Test	MIL-STD-883 Test Method, Condition	No Suffix (Standard) Non-QML ⑤	/ES (Extended) Non-QML ⑤	/H (Class H)	/K (Class K)
Non-Destructive Bond Pull	TM2023	• ④	• ④	• ④	•
Internal Visual	TM2010, TM2017, TM2032 (MIL-STD-750, TM2072, TM2073)	•	•	•	•
Temperature Cycling	TM1010, Condition C -65°C to 150°C, Ambient			•	•
	TM1010, Condition B -55°C to 125°C, Ambient		•		
Constant Acceleration	TM2001, 3000g, Y1 Direction			•	•
	TM2001, 500g, Y1 Direction		•		
PIND ⑦	TM2020, Condition A				•
Pre Burn-In Electrical	25°C				•
Burn-In	TM1015, 320 hrs, 125°C, Case Typ				•
	TM1015, 160 hrs, 125°C, Case Typ			•	
	96 hrs, 125°C, Case Typ		•		
	24 hrs, 125°C, Case Typ	•			
Final Electrical	MIL-PRF-38534, Group A Subgroups 1-6 -55°C, 25°C, 125°C ③			•	•
	MIL-PRF-38534, Group A Subgroups 1 and 4 25°C	•	•		
Hermeticity (Seal)	TM1014, Fine Leak, Condition A2 or B1		•	•	•
	TM1014, Gross Leak, Condition C or B2		•	•	•
	Gross Leak, Dip (1 x 10 ⁻³)	•			
Radiography ⑧	TM2012				•
External Visual	TM2009	•	•	•	•

Notes:

- ① Contact Sales for more information concerning additional environmental screening and testing options desired.
- ② VPT Inc. reserves the right to ship higher screened or SMD products to meet lower screened orders at our sole discretion unless specifically forbidden by customer contract.
- ③ 100% R&R testing with all test data included in product shipment.
- ④ Not required per MIL-PRF-38534. Test is performed for additional product quality assurance.
- ⑤ Non-QML products may not meet all requirements of MIL-PRF-38534.
- ⑥ Note intentionally not used.
- ⑦ PIND test Certificate of Compliance included in product shipment.
- ⑧ Radiographic test Certificate of Compliance and film(s) or data CD included in product shipment.

ORDERING INFORMATION

DVWR	28	3R3	12	T	F	/H	-	XXX
1	2	3	4	5	6	7		8

(1) Product Series	(2) Nominal Input Voltage	(3) Main Output Voltage	(4) Auxiliary Output Voltages
DVWR	28 28 Volts	3R3 + 3.3 Volts	12 15 ± 12 Volts ± 15 Volts

(5) Number of Outputs	(6) Package Option	(7) Screening Code ¹	(8) Additional Screening Code
T Triple	None F Non-Flanged Flanged	None /ES /H /K Standard Extended Class H Class K	Contact Sales

Notes: 1. VPT Inc. reserves the right to ship higher screened or SMD products to meet lower screened orders at our sole discretion unless specifically forbidden by customer contract.

Please contact your sales representative or the VPT Inc. Sales Department for more information concerning additional environmental screening and testing, different input voltage, output voltage, power requirement, source inspection, and/or special element evaluation for space or other higher quality applications.

SMD (STANDARD MICROCIRCUIT DRAWING) NUMBERS

Standard Microcircuit Drawing (SMD)	DVWR2800T Series Similar Part Number
5962-1620301HXC 5962-1620301HXA 5962-1620301HYC 5962-1620301HYA 5962-1620301KXC 5962-1620301KXA 5962-1620301KYC 5962-1620301KYA	DVWR283R312T/H DVWR283R312T/H-E DVWR283R312TF/H DVWR283R312TF/H-E DVWR283R312T/K DVWR283R312T/K-E DVWR283R312TF/K DVWR283R312TF/K-E
5962-1620302HXC 5962-1620302HXA 5962-1620302HYC 5962-1620302HYA 5962-1620302KXC 5962-1620302KXA 5962-1620302KYC 5962-1620302KYA	DVWR283R315T/H DVWR283R315T/H-E DVWR283R315TF/H DVWR283R315TF/H-E DVWR283R315T/K DVWR283R315T/K-E DVWR283R315TF/K DVWR283R315TF/K-E

Do not use the DVWR2800T Series similar part number for SMD product acquisition. It is listed for reference only. For exact specifications for the SMD product, refer to the SMD drawing. SMDs can be downloaded from the DLA Land and Maritime (Previously known as DSCC) website at <https://landandmaritimeapps.dla.mil/programs/defaultapps.asp>. The SMD number listed above represents the Federal Stock Class, Device Type, Device Class Designator, Case Outline, Lead Finish and RHA Designator (where applicable). Please reference the SMD for other screening levels, lead finishes, and radiation levels. All SMD products are marked with a "Q" on the cover as specified by the QML certification mark requirement of MIL-PRF-38534.

CONTACT INFORMATION

To request a quotation or place orders please contact your sales representative or the VPT Inc. Sales Department at:

Phone: (425) 353-3010
Fax: (425) 353-4030
E-mail: vptsales@vptpower.com

All information contained in this datasheet is believed to be accurate, however, no responsibility is assumed for possible errors or omissions. The products or specifications contained herein are subject to change without notice.