



DC COMPONENTS CO., LTD.

DISCRETE SEMICONDUCTORS

DXTD882

TECHNICAL SPECIFICATIONS OF NPN EPITAXIAL PLANAR TRANSISTOR

Description


Designed for the output stage of 0.75W audio, voltage regulator, and relay driver.

Pinning

- 1 = Base
2 = Collector
3 = Emitter

Absolute Maximum Ratings($T_A=25^{\circ}\text{C}$)

Characteristic	Symbol	Rating	Unit
Collector-Base Voltage	V_{CB0}	40	V
Collector-Emitter Voltage	V_{CE0}	30	V
Emitter-Base Voltage	V_{EB0}	5	V
Collector Current	I_C	3	A
Total Power Dissipation	P_D	1.5	W
Junction Temperature	T_J	+150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 to +150	$^{\circ}\text{C}$



Electrical Characteristics

(Ratings at 25°C ambient temperature unless otherwise specified)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Conditions
Collector-Base Breakdown Voltage	BV_{CB0}	40	-	-	V	$I_C=100\mu\text{A}$, $I_E=0$
Collector-Emitter Breakdown Voltage	BV_{CE0}	30	-	-	V	$I_C=1\text{mA}$, $I_B=0$
Emitter-Base Breakdown Voltage	BV_{EB0}	5	-	-	V	$I_E=10\mu\text{A}$, $I_C=0$
Collector Cutoff Current	I_{CBO}	-	-	1	μA	$V_{CB}=30\text{V}$, $I_E=0$
Emitter Cutoff Current	I_{EBO}	-	-	1	μA	$V_{EB}=3\text{V}$, $I_B=0$
Collector-Emitter Saturation Voltage ⁽¹⁾	$V_{CE(sat)}$	-	-	0.5	V	$I_C=2\text{A}$, $I_B=0.2\text{A}$
Base-Emitter Saturation Voltage ⁽¹⁾	$V_{BE(sat)}$	-	-	2	V	$I_C=2\text{A}$, $I_B=0.2\text{A}$
DC Current Gain ⁽¹⁾	h_{FE1}	30	-	-	-	$I_C=20\text{mA}$, $V_{CE}=2\text{V}$
	h_{FE2}	100	-	500	-	$I_C=1\text{A}$, $V_{CE}=2\text{V}$
Transition Frequency	f_T	-	90	-	MHz	$I_C=0.1\text{A}$, $V_{CE}=5\text{V}$, $f=100\text{MHz}$
Output Capacitance	C_{ob}	-	45	-	pF	$V_{CB}=10\text{V}$, $f=1\text{MHz}$, $I_E=0$

(1) Pulse Test: Pulse Width $\leq 380\mu\text{s}$, Duty Cycle $\leq 2\%$

Classification of h_{FE2}

Rank	Q	P	E
Range	100~200	160~320	250~500