


E4WC Series

- RoHS Compliant (Pb-Free)
- 32.768kHz watch crystal
- Miniature cylindrical package
- ± 20 ppm frequency tolerance
- 6.0pF or 12.5pF load capacitance available



www.DataSheet4U.com®
ECLIPTEK
CORPORATION



NOTES

ELECTRICAL SPECIFICATIONS

Frequency	32.768kHz
Frequency Tolerance (at 25°C)	± 20 ppm
Frequency Stability	-0.042ppm / $(\Delta^\circ\text{C})^2$ Maximum, Parabolic; Turn Over Temperature at 25°C $\pm 5^\circ\text{C}$
Operating Temperature Range	-10°C to 60°C
Aging (at 25°C)	± 5 ppm / year Maximum
Storage Temperature Range	-20°C to 70°C
Shunt Capacitance	0.85pF Typical, 2pF Maximum
Motional Capacitance	2.0fF Typical
Drive Level	1 μ Watt Maximum
Equivalent Series Resistance	50,000 Ohms Maximum
Insulation Resistance	100 Megaohms Minimum at 100V _{DC}
Load Capacitance (C _L)	6.0pF or 12.5pF

MANUFACTURER
ECLIPTEK CORP.

CATEGORY
CRYSTAL

SERIES
E4WC

PACKAGE
CYLINDRICAL

CLASS
CR50

REV. DATE
07/06

PART NUMBERING GUIDE

E4WC D A 06 - 32.768K

FREQUENCY TOLERANCE
D=±20ppm at 25°C


OPERATING TEMPERATURE RANGE
A=-10°C to +60°C

NOMINAL FREQUENCY


LOAD CAPACITANCE
06=6.0pF
12=12.5pF

NOTES

MECHANICAL DIMENSIONS
ALL DIMENSIONS IN MILLIMETERS



PARABOLIC TEMPERATURE CURVE



MARKING SPECIFICATIONS

Line 1: 32.768K
32.768 = Nominal Frequency in kHz
K = Blank or K

MANUFACTURER
ECLIPTEK CORP.

CATEGORY
CRYSTAL

SERIES
E4WC

PACKAGE
CYLINDRICAL

CLASS
CR50

REV. DATE
07/06