



EBRT30L45C



Excellent Schottky Barrier Rectifiers



DO-214AB(SMC)

Primary Characteristics		
I_F	30	A
V_{RRM}	45	V
I_{FSM}	350	A
V_F	0.55	V
T_J max	150	°C

Features
• Low profile package • Ideal for automated placement • Guard Ring for over voltage protection • Low forward voltage drop • Component in accordance to RoHS 2002/95/EC

Mechanical Data
• Case: DO-214AB (SMC) • Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 • Terminals: Lead Free Plating (Tin Finish). Solderable per MIL-STD-202, Method 208 • Polarity: Cathode Band • Weight: 0.231 grams (approximate)

Ordering Information			
Part No.	Remark	Package	Packing
EBRT30L45C	General	SMC	3000 / Tape & Reel
EBRT30L45C-H	Halogen Free		
EBRT30L45C-Q	AEC-Q101 qualified		

Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise noted)			
PARAMETER	SYMBOL	EBRT30L45C	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	45	V
Maximum RMS voltage	V_{RMS}	31.5	V
Maximum DC blocking voltage	V_{DC}	45	V
Maximum average forward rectified current	I_F	30	A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	350	A
Maximum Instantaneous Forward Voltage $I_F=3A$ @ 25°C $I_F=30A$ @ 25°C	V_F	0.37 Typ. 0.55 Max.	V
Maximum DC Reverse Current @ $T_A=25^{\circ}\text{C}$ at Rated DC Blocking Voltage @ $T_A=125^{\circ}\text{C}$	I_R	0.5 30	mA
Typical Thermal Resistance	$R_{\theta JC}$	10	°C/W
Operating Temperature Range	T_J	-55 to +150	°C
Storage Temperature Range	T_{STG}	-55 to +150	°C
Marking Code		T30L45C 、 30L45C	

NOTES:

1.Measured at 1.0MHZ and applied reverse voltage of 4.0V DC



Excellent Schottky Barrier Rectifiers

Rating and Characteristics Curves

FIG. 1-Typical Forward Current Derating Curve




FIG. 2-Typical Forward Characteristics




FIG. 3-Maximum Non-Repetitive Forward Surge Current





FIG. 4-Typical Reverse Characteristics






EBRT30L45C



Excellent Schottky Barrier Rectifiers


Package Outline Dimensions



DO-214AB(SMC)


Dimensions in inches and (millimeters)

Marking Information



Suggested Pad Layout

Dimension	Outline	SMC (DO-214AB)
A		9.40
B		4.40
C		3.30
D		2.50
E		6.80



Tape & Reel Specification

ITEM	SYMBOL	SMC (mm)
		DO-214AB
Carrier width	A	6.3(max)
Carrier length	B	8.6(max)
Carrier depth	C	2.9(max)
Sprocket hole	d	1.50±0.1
Reel outside diameter	D	330±2.0
Feed hole diameter	D0	13.5±1
Reel inner diameter	D1	50 (min.)
Sprocket hole position	E	1.75±0.1
Punch hole position	F	7.5±0.05
Sprocket hole pitch	P	8.0±0.1
Sprocket hole pitch	Po	4.0±0.1
Embossment center	P1	2.0±0.05
Overall tape thickness	T	0.6 (max)
Tape width	W	16.0±0.3
Reel width	W2	22.4 (max)
Reel width	W1	18.4 (max)

