



1. CONFIGURATION & DIMENSIONS :



Unit:m/m

A	B	C	D	E1	E2	F	G	H
16.50 Max.	21.00 Max.	5.90 Max.	26.00±0.30	2.54 Ref.	10.16 Ref.	0.98 Ref.	3.10 Ref.	SQ0.584 Ref.

2. SCHEMATIC :



3. SCHEMATIC :

- a) Bobbin : LCP
- b) Core : EFD15
- c) Wire : Polyurethane DD (1UEW)
- d) Tape : Polyester Tape
- e) Varnish : Ripley 468-2FC
- f) Adhesive : Epoxy



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.

23.06.2008



SUPERWORLD ELECTRONICS (S) PTE LTD

PG. 1

4. GENERAL SPECIFICATION :

- a) Operating Temperature Range : -25°C to +105°C
 b) Insulation Class : B (130°C)

5. ELECTRICAL CHARACTERISTICS :

Part No.	Inductance (L)	Conditions	Test Frequency	DCR @ 25°C
EFDB5HSF-10321	L : (3-1) = 21uH ~ 32uH	-	10KHz 0.1V	(2-1) = 0.066Ω Max.
				(3-2) = 0.066Ω Max.
				(5-4) = 0.084Ω Max.
				(6-10) = 176Ω Max.


RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.

23.06.2008


SUPERWORLD ELECTRONICS (S) PTE LTD

PG. 2